Bio-Guard Algae All 60

ACCEPTED 20 MAY 1000 5/85-339

ACTIVE INGREDIENT:

T

Polyloxyethylene (dimethyliminio) ethylene (dimethyliminio) ethylene dichloride].

60 0 %

INERT INGREDIENT ...

40 0^գշ

This product contains 5.76 lb. of active ingredient per gallon and weighs 9.6 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN

CAUTION

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing.

FIRST AID: If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or if these are not available. Jrink large quantities of water Avoid alcohol. Call a physician immediately.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Keep out of lakes, streams, or ponds. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

DIRECTIONS FOR USE GENERAL CLASSIFICATION

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Bio Guard Algae All 60 is used to control the growth of algae in swimming pools, extenor spas, whirlpriols, and not tubs. For maximum effectiveness pools, spas, whirlpools, and hot tubs confaining heavy growth of algae should be cleaned prior to using Bio Guard Alique Ali 60.

For pools having just visible alone growth add an initial abse of 11 to 17 fluid ounces of Bio Guard Algae All 60 per 10,000 gallons of water and remove settled algae debris by cleaning. For treatment of a freshly cleaned and filled pool add initially 6 to 11 fluid ounces of Bio-Guard Algae All builder 10,000 gallons of water. Subsequent additions of 2 to 4 fluid ounces of Bio-Guard Algae All 60 per 10,000 gallons of water should be made every 5 to 7 days after initial treatment for maintenance.

Spas, whiripools, or hot tubs having just visible algae growth require an initial dose of 1 to 2 fluid ounces of Bio Guard Algae Ail 60 per 1000 gallons of water. For treatment of a freshly cleaned and filled spa, whirlpool, or hot tub, add initially 0.6 to 1.1 fluid ounces of Bio Guard Algae All 60 per 1,000 gallons of water. Subsequent additions of 0.2 to 0.4 fluid runces of Bio Guard Algae All 60 should be made every 5 to 7 days after initial treatment for maintenance.

Bio Guard Algae Ail 60 is compatible with triose chemicals normally used to treat pools and spas and is effective at both acid and alkaline pH. Bi. Guard Algae Ali 60 can be used in pools and spas treated with chlorine chemicals and may reduce the amount of those chemicals normally required. However, do not mix Bio Guard Algae Ali 60 with concentrated dry or liquid chlorine products.

STORAGE & DISPOSAL: Keep container closed when not in use. Do not contaminate water, food, or feed by storage, disposal or cleaning of equipment. Rinsate that cannot be used or reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies. Open dumping is prohibited.

METAL CONTAINERS Triple rinse and offer for recycling, reconditioning, or disposal in an approved landfill or bury in a safe place.

PLASTIC CONTAINERS: Do not reuse empty container. Triple rinse and incinerate or dispose of in an approved landfill or bury in safe place.

Mar utactured by. Bio Lab, Inc P. O. Box 1489 Decatur, GA 30030

EPA REGINO

5185-337

EPA EST NO

NET CONTENTS