Oraft labeling with changes marked

{All text in brackets [xxx] is optional and may or may not be included on a final label.} {All text in braces {xxx} is administrative and will not appear on a final label.}

NABR40-E

[For use as a disinfectant, sanitizer, bactericide, slimicide, algicide, and mollusk control agent in recirculating cooling water systems, brewery pasteurizing systems, air washers, once through cooling water and wastewater treatment systems, and pulp and paper mills.]

ACTIVE INGREDIENT:

Sodium bromide OTHER INGREDIENTS:

cha

Total

40.0%

60.0%

100.0%

KEEP OUT OF REACH OF CHILDREN

WARNING

FIRST AID IF SWALLOWED: Drink promptly large quantities of water. DO NOT induce vomiting. Avoid alcohol. Never give anything by mouth to an unconscious person. Call a physician or poison control center immediately. IF IN EYES: Hold eyelids open and flush with a steady, gentle stream of water for 15 minutes. Get medical attention. IF ON SKIN: Wash with plenty of soap and water. Get medical attention. IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferably, mouth-to-mouth. Get medical attention. [IN CASE OF MEDICAL EMERGENCY, CALL [1-303-623-5716] [telephone number supplied by supplemental registrant].]

SEE OTHER PRECAUTIONS ON SIDE PANEL

Net	Weight	
Lot	No.	

EPA Reg. No. 5185-451

EPA Est. No

ACCEPTED

AUG 20 1998

BIOLAB, INC. P.O. BOX 1489 DECATUR, GA 30031 Under the Federa Sucide, Fungicide, and Rodenticide Act as afficiency, for the pesticide, registered under EPA Reg. No. 5185-451

moved from within each application to beginning so that it will only be required once to shorten label

DIRECTIONS FOR USE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

RECIRCULATING COOLING WATER SYSTEMS, INCLUDING AIR WASHERS AND BREWERY PASTEURIZERS.

When used as directed, this product effectively controls algal, bacterial, fungal slime and controls the settlement and growth of mollusks such as the zebra mussel (Dreissena) or the Asiatic clam (Corbicula) in commercial and industrial cooling towers; influent water systems such as flow through filters; heat exchange water systems; and industrial water scrubbing systems.

DOSAGE RATES. Add this product to the system at a 0.125 to 2.0 sodium bromide/oxidant mole ratio. For example:

- 1) 1.6 to 26.5 pounds of chlorine gas (99.9%) per gallon of sodium bromide solution;
- 2) 1.3 to 21.2 gallons sodium hypochlorite (12.5% available chlorine) solution per gallon of sodium bromide solution.

Initial Dose: When the system is noticeably fouled, add 0.0003 to 0.024 gallons of this product per 1000 gallons of water contained in the system and oxidize with either gas chlorine (0.008 to 0.040 lb. gas chlorine per 1000 gallons of contained water), or sodium hypochlorite solution (0.007 to 0.032 gallons of 12.5% sodium hypochlorite solution per 1000 gallons of contained water).

Subsequent Dose: When microbial control is evident, add 0.0002 to 0.024 gallons of this product per 1000 gallons of water contained in the system, and oxidize with either gas chlorine (0.004 to 0.040 lb. gas chlorine per 1000 gallons of contained water), or sodium hypochlorite solution (0.003 to 0.032 gallons of 12.5% sodium hypochlorite solution per 1000 gallons of contained water).

ONCE-THROUGH COOLING WATER AND WASTE WATER TREATMENT SYSTEMS.

When used as directed, this product effectively controls algal, bacterial and fungal slime and controls the settlement and growth of mollusks such as the zebra mussel (*Dreissena*) or the Asiatic clam (*Corbicula*) in oncethrough fresh and sea water cooling systems and disinfects secondary and tertiary wastewater treatment systems.

DOSAGE RATES. Add this product to the system at a 0.125 to 2.0 sodium bromide/oxidant mole ratio. For example:

- 1) 1.6 to 26.5 pounds of chlorine gas (99.9%) per gallon of sodium bromide solution;
- 2) 1.3 to 21.2 gallons sodium hypochlorite (12.5% available chlorine) solution per gallon of sodium bromide solution.

Initial Dose: When the system is noticeably fouled, add 0.0008 to 0.049 gallons of this product per 1000 gallons of water contained in the system and oxidize with either gas chlorine (0.02 to 0.08 lb. gas chlorine per 1000 gallons of contained volume), or sodium hypochlorite solution (0.02 to 0.06 gallons of 12.5% sodium hypochlorite solution per 1000 gallons of contained volume).

Subsequent Dose: When microbial control is evident, add 0.0003 to 0.049 gallons of this product per 1000 gallons of water contained in the system, and oxidize with either gas chlorine (0.008 to 0.08 lb. gas chlorine per 1000 gallons of contained volume), or sodium hypochlorite solution (0.006 to 0.06 gallons of 12.5% sodium hypochlorite solution per 1000 gallons of contained volume).

ed on current Tabel

inis is used listed postely

PULP AND PAPER MILLS

When used as directed this product effectively controls algal, bacterial, and fungal slime in pulp and paper mill fresh and sea water influent water systems; cooling water systems, wastewater treatment systems, nonpotable water systems, and other process water.

text

DOSAGE RATES: Add this product to the system at a 0.125 to 2.0 sodium bromide/oxidant mole ratio. For example:

- 1) 1.6 to 26.5 pounds of chlorine gas (99.9%) per gallon of sodium bromide solution;
- 2) 1.3 to 21.2 gallons sodium hypochlorite (12.5% available chlorine) solution per gallon of sodium bromide solution.

Add sufficient amount of this product and oxidize with either gas chlorine or sodium hypochlorite solution to achieve a residual bromine level of 0.5 to 5 ppm or as needed to maintain control of the system. This product can be added whenever chlorination is applied.

Feed this product either before or after the oxident injection point into the water to be treated. Be sure rapid mixing of the treated water, this product and oxidant is achieved. Pump manufacturers can recommend the appropriate materials of construction and capacity for a pump to feed this product or sodium hypochlorite solution. If used as the oxidant, chlorine gas must be hardled and used only in accordance with practices recommended in The Chlorine Manual published by the Chlorine Institute, Inc., New York. Use chlorine gas only in well ventilated areas.

Treatment levels of this product and oxidant can best be measured with test kits for either bromine or chlorine. Tests should be made immediately after drawing water samples from the system. Use test kits according to directions.

- 1. When a bromine test kit is used, results can be read directly as ppm bromine.
- 2. When a chlorine test kit is used, results can be expressed in terms of bromine by multiplying chlorine values by the conversion factor 2.25.

This product weighs 11.9 lb./gal at 70° F.

4 7 4

STORAGE AND DISPOSAL

STORAGE. Keep product dry in tightly closed original container when not in use. Store in a cool, dry, well ventilated area. Product should be stored at 0°F. or above.

DISPOSAL. Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. DO NOT REUSE EMPTY CONTAINER. Triple rinse the container (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incinerate. Burn only if allowed by state and local authorities. If burned, stay out of smoke.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS. WARNING. Irritation may develop from eye and skin exposure. Avoid contact with eyes. Wear gloves and safety goggles. Wash contaminated clothing before reuse.

PHYSICAL AND CHEMICAL HAZARDS

Sodium bromide is not flammable. However, in fires fueled by other materials, hydrogen bromide or bromine may be released. In case of fire, wear self-contained breathing apparatus.

ENVIRONMENTAL HAZARDS. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

NOTE: Buyer assumes all responsibility for safety and use not in accordance with directions.