

Mobil®

Copper Naphthenate 200-S

**CAUTION! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE.
KEEP OUT OF THE REACH OF CHILDREN.**

If swallowed, do not induce vomiting. Call a physician immediately.

Keep away from heat and open flame.

Avoid skin contact. If contact occurs, wash with soap and water.

Avoid breathing of vapor.

Do not contaminate water by cleaning of equipment or disposal of waste.

**Do not reuse empty drums. Return drum to recor-ditioner or destroy by
perforating or crushing and burying in a safe place.**

DIRECTIONS FOR USE:

To control molds and fungi on cellulosic materials, such as jute, cotton and linen fabrics, and paper, rope and twine, dip the materials in Copper Naphthenate 200-S for one-half to two minutes. Squeeze rolls or centrifuges may be used to remove excess solution. In treating wood to control powder post beetles or molds and fungi, apply by dip or brush till penetration assures a continuous barrier. To control termites, apply, before placing the wood in construction, by brush in two flowing coats or by dipping for at least three minutes. Where possible, make periodic inspections to detect checks and cracks that may develop after treatment, for no treatment can be effective beyond its immediate location.

Active Ingredients: Copper Naphthenate 20%

Inert Ingredients: Petroleum Naphtha 80%

(Copper expressed as metallic--2³/₂)

USDA REG. NO. 5187-2 NET CONTENTS

MOBIL OIL CORPORATION, NEW YORK, N. Y.

L-178(7-71)

001 56 14