

bioMeT® Blue Antifouling Paint No. 12122  
Antifouling Paint

KEEP OUT OF REACH OF CHILDREN!  
DANGER!  
PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS:

Danger! Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed or inhaled. Do not get on skin, in eyes, or on clothing. Wear chemical worker goggles or full face shield. Wear protective clothing such as gloves, long-sleeved shirt, long pants and hat. Avoid breathing spray mist when applying or dust from sanding old paint. Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation.

While spraying paint or sanding vessel surfaces, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

FIRST AID: If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get Medical Attention. Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage. If on skin: Wash with plenty of soap and water. Get medical attention if irritation persists: If in eyes: Flush with plenty of water. Get medical attention.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL or CHEMICAL HAZARDS: Do not use or store near heat or open flame.

Active Ingredients Tributyltin Fluoride.....6.6%  
Inert Ingredients .....93.4%

5204-16

5204-16

DOT

DOT

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with the label.

For Commercial Use Only!

The product is intended for use on fiberglass hulls to prevent fouling in marine service. The product is a suitable anticorrosive for use on fiberglass hulls. Apply two coats of bioMeT® B applied by either spray (E) or brush (B) are required.

STORAGE AND DISPOSAL  
Paint or cleanup solvent should be disposed of according to procedures under Subtitle C, Conservation and Recovery Act. Containers should be triple rinsed for recycling or recon. Dispose of in a sanitary state and

EPA Reg. No. 5204-16  
EPA Est. No. 5204-NJ-1

E

5204-16

le eye damage and burns. Harmful if absorbed through  
t on skin, in eyes, or on clothing. Wear chemical  
ear protective clothing such as gloves, long-sleeved  
athing spray mist when applying or dust from sanding old  
water after handling and before eating or smoking. Use

surfaces, wear a respirator jointly approved by the  
ation and the National Institute for Occupational

ly a large quantity of milk, egg whites, gelatin  
e, drink large quantities of water. Avoid alcohol.  
ian: Probable mucosal damage may contraindicate the  
ash with plenty of soap and water. Get medical  
in eyes: Flush with plenty of water. Get medical

is toxic to fish. Do not apply directly to water by  
astes. Do not allow chips and dust generated during  
of paint debris in an approved landfill.

use or store near heat or open flame.

e.....6.6%  
.....93.4%

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in  
a manner inconsistent with its labeling.

For Commercial Use Only!

The product is intended for application to metal and  
fiberglass hulls to prevent algal, slime and microfouling  
in marine service. The surface should be clean and dry and  
a suitable anticorrosive applied prior to application. One  
to two coats of bioMeT® Blue Antifouling Paint No. 12122  
applied by either spray (preferably airless) or rolling  
are required.

STORAGE AND DISPOSAL

Paint or cleanup solvent that cannot be used must be  
disposed of according to Federal or approved state  
procedures under Subtitle C of the Resource  
Conservation and Recovery Act. Waste paint containers  
should be triple rinsed (or equivalent). Then offer  
for recycling or reconditioning, or puncture and  
dispose of in a sanitary landfill, or by other approved  
state and local procedures.

EPA Reg. No. 5204-16  
EPA Est. No. 5204-NJ-1