

bioMeT[®] White WO-1
Antifouling Paint

For use on vessel hulls to protect from algae, slime and fouling.

KEEP OUT OF REACH OF CHILDREN!

DANGER!

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS:

5/21/71
Danger! Corrosive. Causes skin burns. Wear protective clothing such as gloves, long-sleeved shirt, long pants and hat. Causes eye irritation. May be fatal if swallowed. Harmful if absorbed through skin or inhaled. This product may be a dermal sensitizer. Avoid contact with skin, eyes, or clothing. Avoid breathing spray mist when applying or dust from sanding old paint. Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation.

While spraying paint or sanding vessel surfaces, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

FIRST AID: If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get Medical Attention. Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage. If on skin: Wash with plenty of soap and water. Get medical attention if irritation persists. If in eyes: Flush with plenty of water. Get medical attention if irritation persists.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL or CHEMICAL HAZARDS: Do not use or store near heat or open flame.

Active Ingredient: bis(tributyltin)oxide.....6.3%
Inert Ingredients:93.7%

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with the label.

For Commercial Use Only!

The product is intended for use on fiberglass hulls to prevent fouling in marine service. The surface should be sanded and primed with a suitable anticorrosive primer. Apply two coats of this paint (preferably airless) or roller.

STORAGE AND DISPOSAL

Paint or cleanup solvent should be disposed of according to the procedures under Subtitle C of the Resource Conservation and Recovery Act. Containers should be triple rinsed (for recycling or reconditioning) and disposed of in a sanitary manner in accordance with state and local procedures.

EPA Reg. No. 5204-29
EPA Est. No. 5204-NJ-1

THIS DOCUMENT AVAILABLE

from algae, slimes and fouling.

5204-29

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For Commercial Use Only!

The product is intended for application to metal and fiberglass hulls to prevent algal, slime and microfouling in marine service. The surface should be clean and dry and a suitable anticorrosive applied prior to application. One to two coats of this paint applied by either spray (preferably airless) or rolling are required.

STORAGE AND DISPOSAL

Paint or cleanup solvent that cannot be used must be disposed of according to Federal or approved state procedures under Subtitle C of the Resource Conservation and Recovery Act. Waste paint containers should be triple rinsed (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

EPA Reg. No. 5204-29
EPA Est. No. 5204-NJ-1

ALS: Wear protective clothing such as gloves, long-sleeved eye irritation. May be fatal if swallowed. Harmful if This product may be a dermal sensitizer. Avoid contact breathing spray mist when applying or dust from sanding up and water after handling and before eating or smoking.

el surfaces, wear a respirator jointly approved by the stration and the National Institute for Occupational

ptly a large quantity of milk, egg whites, gelatin ble, drink large quantities of water. Avoid alcohol. ician: Probable mucosal damage may contraindicate the Wash with plenty of soap and water. Get medical if in eyes: Flush with plenty of water. Get medical

l is toxic to fish. Do not apply directly to water by wastes. Do not allow chips and dust generated during se of paint debris in an approved landfill.

ot use or store near heat or open flame.

oxide.....6.3%
.....93.7%

BEST DOCUMENT AVAILABLE



bioMeT[®] Yellow YO-1
Antifouling Paint

For use on vessel hulls to protect from algae, slime and fouling.
KEEP OUT OF REACH OF CHILDREN!

DANGER!

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS:

Danger! Corrosive. Causes skin burns. Wear protective clothing such as gloves, long-sleeved shirt, long pants and hat. Causes eye irritation. May be fatal if swallowed. Harmful if absorbed through skin or inhaled. This product may be a dermal sensitizer. Avoid contact with skin, eyes, or clothing. Avoid breathing spray mist when applying or dust from sanding old paint. Wash thoroughly with soap and water after handling and before eating or smoking. Use with adequate ventilation.

While spraying paint or sanding vessel surfaces, wear a respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.

FIRST AID: If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get Medical Attention. Note to physician: Probable mucosal damage may contraindicate the use of gastric lavage. If on skin: Wash with plenty of soap and water. Get medical attention if irritation persists: If in eyes: Flush with plenty of water. Get medical attention if irritation persists.

ENVIRONMENTAL HAZARDS: This material is toxic to fish. Do not apply directly to water by cleaning of equipment or disposal of wastes. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

PHYSICAL or CHEMICAL HAZARDS: Do not use or store near heat or open flame.

Active Ingredient: bis(tributyltin)oxide.....5.5%
Inert Ingredients:94.5%

5201 30



DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with the label.

For Commercial Use Only!

The product is intended for use on fiberglass hulls to prevent fouling in marine service. The surface should be sanded to a suitable anticorrosive surface and then applied in two coats of this paint (preferably airless) or roller.

STORAGE AND DISPOSAL

Paint or cleanup solvent should be disposed of according to Federal procedures under Subtitle C of the Resource Conservation and Recovery Act. Containers should be triple rinsed (or cleaned) for recycling or reconditioning. Do not dispose of in a sanitary landfill, or in state and local procedures.

EPA Reg. No. 5204-29
EPA Est. No. 5204-NJ-1

E

on algae, slime and fouling.

5204-29

S:
s. Wear protective clothing such as gloves, long-sleeved
e irritation. May be fatal if swallowed. Harmful if
is product may be a dermal sensitizer. Avoid contact
breathing spray mist when applying or dust from sanding
and water after handling and before eating or smoking.

l surfaces, wear a respirator jointly approved by the
tration and the National Institute for Occupational

otly a large quantity of milk, egg whites, gelatin
le, drink large quantities of water. Avoid alcohol.
cian: Probable mucosal damage may contraindicate the
Wash with plenty of soap and water. Get medical
in eyes: Flush with plenty of water. Get medical

is toxic to fish. Do not apply directly to water by
wastes. Do not allow chips and dust generated during
se of paint debris in an approved landfill.

use or store near heat or open flame.

xide.....5.5%
.....94.5%

DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in
a manner inconsistent with its labeling.

For Commercial Use Only!

The product is intended for application to metal and
fiberglass hulls to prevent algal, slime and macrofouling
in marine service. The surface should be clean and dry and
a suitable anticorrosive applied prior to application. One
to two coats of this paint applied by either spray
(preferably airless) or rolling are required.

STORAGE AND DISPOSAL

Paint or cleanup solvent that cannot be used must be
disposed of according to Federal or approved state
procedures under Subtitle C of the Resource
Conservation and Recovery Act. Waste paint containers
should be triple rinsed (or equivalent). Then offer
for recycling or reconditioning, or puncture and
dispose of in a sanitary landfill, or by other approved
state and local procedures.

EPA Reg. No. 5204-29
EPA Est. No. 5204-NJ-1