

M&T* Polyflo 2018

Antifouling Paint

For protecting surfaces from marine fouling and slime.

Active Ingredients: Cuprous Oxide	49.5%
Tributyltin Methacrylate (as part of a polymer)	9.9%
Inert Ingredients	40.6%
Total Tin Content 3.3	Total 100.0%

DANGER! KEEP OUT OF THE REACH OF CHILDREN

PRECAUTIONARY STATEMENTS

HAZARD TO HUMANS & DOMESTIC ANIMALS

Corrosive. Causes severe skin and eye damage. Do not get on skin, clothing or in eyes. Wear a face shield and rubber gloves when handling. Use in a well-ventilated area. When used in confined areas or applied by spraying, wear protective clothing and a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly, the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11. Harmful if swallowed or inhaled. Do not breathe vapors or spray mist.

PRACTICAL TREATMENT: In case of skin contact, remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get immediate medical attention. If swallowed, do not induce vomiting. The product contains petroleum distillates. Get immediate medical attention if in eyes, flush eyes with water. Get medical attention.

ENVIRONMENTAL HAZARD: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning equipment or disposal of waste.

CHEMICAL AND PHYSICAL HAZARDS: Do not use near heat or open flame.

FLASH POINT 65 F

M&T
CHEMICALS INC.

DIREC
POLYF
alumin
tube w
and dr
should
fiberglass
strong
applic
Protec
applic
dispos
Vesse
of Fed
its lab.
STOR
Do not
Pestic
Pestic
instruc
proced
Conta
Triple
dispos
proced