

- -- -- -- --

していたいとうと見て見て

たにに見

ALCHARMAN AND A REAL A

\_\_\_\_\_

66

For use without dilution as a soil fumigant for the c subterranean termites by application beneath concresuch as porches, and where it may be impractival to structural or chemical barriers.

## INGREDIENTS

Active Ingredients 100% Petroleum Hydrocarbon Ethylene Dibromide Technical Chlordane\* \*Consists of actachloro of Linichlander is shown in

\*Consists of octachloro 4, 7-njethonotetrollydroindau ond related cumpoinds DIRECTIONS

S-T-D should be applied beneath concrete slabs throu drilled adjacent to wall and pier foundations, under of failures or where cracks permit entry of insects. Hole be drilled through the slab at points no further apar feet and S-T-D applied through these holes to a point inches beneath the surface. At 5 ft. spacings apply 3 S-T-D per hole, at  $2\frac{1}{2}$  ft. spacings apply 2 pints per h drilled holes should be sealed with cement as quickly as after applying the fumigant. Wherever termites' entubes can be located they should be given direct treat digging down to a depth of at least 12 inches and ap half gallon of S-T-D a, this point then filling the hole a packing the soil down fumily. For best results the act structure should be wetted.

NOTE: S-T-D is designed for use only where it can be as a fumigant. It should never be used as a spray fo wood or the ground.

## **CAUTION:**

## KEEP OUT OF REACH OF CHILDRE

Avoid breathing vapor. Do not get in eyes, on skin or ing. In case of contact, immediately remove clothing, is shoes, and flush skin or eyes with plenty of water for 15 minutes; for eyes, get medical attention. Wash clot air shoes thoroughly before re-use. Do not take internaonly with adequate ventilation. In confined spaces the should wear a gas mask equipped with an organic vapo ter. Harmful if swallowed. Contact with skin can can symptoms. FLAMMABLE—Keep away from heat a flame.

If illness results from inhalation, remove to fresh air a doctor.

If swallowed, call a doctor. Induce vomiting by giving a such as a tablespoonful of table salt in a glass of ward Seller makes no warranty of any kind, express or implied, concerning the product. Buyer assumes all risk of use or handling, whether in accoudirections or not.

Contents

Gallons

NEIL A. MACLEAN CO. INC. 1536 INDUSTRIAL WAY, BELMONT (S.F. AREA), CALIFOR FRESNO EL MONTE (L.A.

EL MONTE (L.A. USDA Reg.

ACCEPT 4-14-

UNDER THE FEDERAL IN FUNDICIDE AND ROUTINT FOR ECCLEMIC PUTON FO UNDER NO

	ररर
ontrol of te slabs, prepare	NEUTRINI DE LE CALENDE DE LE CALENDE
ugh holes cold joint es should rt than 5 bint 12-18 3 pints of hole. The s possible mergence tment by pplying a again and tual tube confined or use on	
EN on cloth- including r at least thing and hally. Use operator ors caris- use toxic and open and call a an emctic rm water. e use of this ordance with	TRADEOUT MANUAL IN MANUAR MADE AND A MANUAR AND
RNIA AREA) No. 5316-2 ED 67 ECTHORF CONFACT REDSTER-	EVENENT TECHNERY
6-2	

ACCEPTED WITH COMMENTS