

There is no substitute for Quality

ALCATRAZ

Dependable Protection

NUMBER 200
COPPER
NAPHTHENATE
WOOD
PRESERVATIVE
LIGHT GREEN

INGREDIENT STATEMENT

Active Ingredient:	
(Copper Naphthenate)	25
Inert Ingredients:	
(Petroleum Solvent)	75
	100.00

CONTAINS 2% COPPER AS METAL

DANGER!

MANUFACTURED BY
THE ALCATRAZ COMPANY, INC.
RICHMOND VIRGINIA U.S.A.

CONTENTS:
5 GALLONS

HARMFUL OR FATAL IF SWALLOWED
See cautions elsewhere on the label.
KEEP OUT OF THE REACH OF CHILDREN

Protective Coatings Manufacturers Since 1888



DIRECTIONS

For treatment of wood exposed for interior or exterior use, protect against rot, decay, insect damage, and mold by applying a liberal coating of Alcatraz Wood Preservative to the wood. For interior use, apply to the wood before it is painted. For exterior use, apply to the wood before it is painted. For use on concrete, apply to the concrete before it is finished.

For use on concrete, apply to the concrete before it is finished. For use on masonry, apply to the masonry before it is finished. For use on metal, apply to the metal before it is painted.

For use on wood, apply to the wood before it is painted. For use on wood, apply to the wood before it is painted. For use on wood, apply to the wood before it is painted.

GENERAL INFORMATION

In fact, we recommend the use of our #200 Copper Naphthenate to 1% copper as metal by the volume of approximately 3 quarts of petroleum solvent per gallon of longer dip for open ends.

For low flash point offers a low fire hazard. For use on masonry, apply to the masonry before it is finished. For use on metal, apply to the metal before it is painted.

ALCATRAZ Copper Naphthenate is a... For use on masonry, apply to the masonry before it is finished. For use on metal, apply to the metal before it is painted.

CONTAINS 2% COPPER AS METAL

ALCATRAZ COMPANY

20