

© PPER NAPHTHENATE

41-1014

CAUTION! HARMFUL OR FATAL IF SWALLOWED. KEEP OUT OF REACH OF CHILDREN.

See Other Cautions on Back Panel.

NET 5 GALLONS 18.925 LITERS

FOR WOOD . CANVAS . NET

Controls Wood Rot . Powder Post Beetles . Termites

Copper Naphthenate helps prevent the cracking, checking, and splitting in wood caused by exposure to moisture and weather. It penetrates the wood and deposits a residue which is insoluble in water. This "built in" protection adds years to the life of the wood.

DIRECTIONS FOR USE

Use Copper Naphthenate as it comes from the can. Wood must be free of bark, dry, and well seasoned. Always brush or spray two liberal coats. Soak two hours for lumber up to two inches thick. Heavier timbers and posts should soak overnight. Air dry for 48 hours before painting.

Soak canvas, rope or net until thoroughly wet. Allow to drain and dry.

After exposure the green color bleaches away; however, the preservative is still present.

DFU-324

CONTAINS PETROLEUM DISTILLATES

If swallowed, do not induce vomiting. CALL PHYSICIAN IMME-DIATELY. Keep away from heat and open flame. Avoid contact with skin. Avoid breathing of vapors or spray mist. Do not transfer contents to unlabeled bottles or other containers. Close container after each use.

This product is toxic to fish. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

Destroy Empty Container—Do not reuse this container for any purpose.

Punch holes in top and bottom of empty metal container, crush under wheels of heavy vehicle or with an axe and bury crushed container deeply in a pit on non-crop land in an isolated area well away from water supplies. Do not burn empty containers.

Use only with adequate ventilation. KEEP OUT OF REACH OF CHILDREN.

CB-198

EPA Est. 5351-SC-01

Fulton Chemical Company
Division of Southern Coatings & Chemical Co., Inc.
Sumter, SC 29150 / Slidell, LA 70459

BEST AVAILABLE