

**PRECAUTIONARY
STATEMENTS
HAZARDS TO HUMANS
AND DOMESTIC ANIMALS
DANGER**

May be fatal if swallowed, inhaled or absorbed through skin. Causes skin and eye irritation. Causes delayed chemical burns. Do not get either the dry material or solutions prepared from it in eyes, on skin or on clothing. Do not breathe vapors, spray mist, or dust. Use with adequate ventilation. Do not take internally. Wash thoroughly after skin contact, before eating, drinking, use of tobacco products, or using restrooms.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

Environmental Hazards

This product is toxic to fish and wildlife. Do not apply directly to water. Do not apply where runoff is likely to occur. Do not apply when weather conditions favor drift from areas treated. Do not contaminate water by cleaning of equipment or disposal of wastes.

Physical and Chemical Hazards

Do not use or store near heat or open flame. Close container after each use.

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

SOLUTIONS FOR TREATING POLES, FENCE POSTS LUMBER AND TIMBERS

Vulcan's Premium Penta Concentrate must be diluted for use. Solvents such as a No. 2 or No. 3 fuel oil, a diesel oil, or comparable products will provide an AWPA P-9, Type A solution. Select the diluent according to the results desired. For methods of application, consult the American Wood-Preservers' Association Standards.

Posts to be treated should be free of bark, normally dry and seasoned, and free of any visible evidence of decay.

This product is for exterior use only. This product is not intended for home and farm use. Do not use on picnic tables, children's playground structures or horticultural lumber. Do not apply to logs used in construction of log homes. Do not use treated wood in farm buildings in area contacted by farm animals or in structures to contain animal feed or agricultural produce. Products treated with or containing this chemical are not to be used in food packaging material or in areas where food is processed, handled or stored.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g., handling freshly treated wood and manually opening cylinder doors).

Individuals who manually open cylinder doors must wear gloves and a respirator.

Individuals who enter, clean or repair pressure treatment cylinders, vats, tanks, and other related equipment that is contaminated with wood treatment formulation (e.g., cylinders that are in operation or are not free of the treatment solution) must wear a respirator, goggles and protective clothing (including overalls, jacket, gloves, boots, and head covering) impervious to the wood treatment formulation.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g., manually opening/closing cylinder doors, moving trams out of cylinders, mixing chemicals, and handling freshly treated wood).

RESTRICTED USE PESTICIDE

For retail sale to and use only by Certified Applicators or persons under their direct supervision and only for those uses covered by the Certified Applicator's certification.

Vulcan

PREMIUM FOUR POUND PENTA (PCP-2) CONCENTRATE

ACTIVE INGREDIENTS: Pentachlorophenol	35.3%*
Other Chlorophenols and Related Compounds	4.1%*
INERT INGREDIENTS:	60.6%
TOTAL	100.0% ...

*Equivalent to 41.0% Technical Pentachlorophenol

ONE GALLON MAKES ELEVEN GALLONS READY-TO-USE PRODUCT

Dilutes to clear, stable product non-blooming on wood
CONTAINS 4 POUNDS PENTACHLOROPHENOL PER GALLON

DILUTE ACCORDING TO DIRECTIONS BEFORE USE

Controls Decay (Rot) and Molds, Preserves Wood Against Attack by Termites, Powder-Post Beetles, and Carpenter Ants.

DANGER



POISON

KEEP OUT OF REACH OF CHILDREN

STATEMENT OF PRACTICAL TREATMENT

If swallowed - Call a physician or Poison Control Center immediately. If possible, vomiting should be induced under medical supervision. Drink one or two glasses of water and induce vomiting by touching the back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.

If on skin - Wash immediately with soap and water. Wash thoroughly with soap and water after handling.

If in eyes - Flush with water for at least fifteen (15) minutes and contact a physician.

If inhaled - Remove victim to fresh air. Get medical attention.

NOTE TO PHYSICIAN: This product is a metabolic stimulant. Causes hyperthermia. Treat symptomatically.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONS

Vulcan Materials Company

MANUFACTURED BY

CHEMICALS DIVISION / P. O. BOX 7889 • BIRMINGHAM, ALABAMA 35253

Pro
tan
or
and
dis
man

For
ope
be
app
mis
(in
vio

NO
pro
res
gas
(e.
tio
pol
add
acc

STC
con
Do
Do
foo

PES
exc
Law
ins
Age
reg

CON
rec
lan
tie

DIRECTIONS FOR USE

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

SOLUTIONS FOR TREATING POLES, FENCE POSTS LUMBER AND TIMBERS

Vulcan's Premium Penta Concentrate must be diluted for use. Solvents such as a No. 2 or No. 3 fuel oil, a diesel oil, or comparable products will provide an AWPA P-9, Type A solution. Select the diluent according to the results desired. For methods of application, consult the American Wood-Preservers' Association Standards.

Posts to be treated should be free of bark, normally dry and seasoned, and free of any visible evidence of decay.

This product is for exterior use only. This product is not intended for home and farm use. Do not use on picnic tables, children's playground structures or horticultural lumber. Do not apply to logs used in construction of log homes. Do not use treated wood in farm buildings in area contacted by farm animals or in structures to contain animal feed or agricultural produce. Products treated with or containing this chemical are not to be used in food packaging material or in areas where food is processed, handled or stored.

Applicators must wear gloves impervious to the wood treatment formulation in all situations where dermal contact is expected (e.g., handling freshly treated wood and manually opening cylinder doors).

Individuals who manually open cylinder doors must wear gloves and a respirator.

Individuals who enter, clean or repair pressure treatment cylinders, vats, tanks, and other related equipment that is contaminated with wood treatment formulation (e.g., cylinders that are in operation or are not free of the treatment solution) must wear a respirator, goggles and protective clothing (including overalls, jacket, gloves, boots, and head covering) impervious to the wood treatment formulation.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to the wood treatment formulation (e.g., manually opening/closing cylinder doors, moving trams out of cylinders, mixing chemicals, and handling freshly treated wood).

NET

lbs.

Other Chlorophenols and Related Compounds 4.1%

INERT INGREDIENTS: 80.6%

TOTAL 100.0%

*Equivalent to 41.0% Technical Pentachlorophenol

ONE GALLON MAKES ELEVEN GALLONS READY-TO-USE PRODUCT

Dilutes to clear, stable product non-blooming on wood

CONTAINS 4 POUNDS PENTACHLOROPHENOL PER GALLON

DILUTE ACCORDING TO DIRECTIONS BEFORE USE

Controls Decay (Rot) and Molds, Preserves Wood Against Attack by Termites, Powder-Post Beetles, and Carpenter Ants.

DANGER POISON

KEEP OUT OF REACH OF CHILDREN

STATEMENT OF PRACTICAL TREATMENT

If swallowed - Call a physician or Poison Control Center immediately. If possible, vomiting should be induced under medical supervision. Drink one or two glasses of water and induce vomiting by touching the back of throat with finger. Do not include vomiting or give anything by mouth to an unconscious person.

If on skin - Wash immediately with soap and water. Wash thoroughly with soap and water after handling.

If in eyes - Flush with water for at least fifteen (15) minutes and contact a physician.

If inhaled - Remove victim to fresh air. Get medical attention.

NOTE TO PHYSICIAN: This product is a metabolic stimulant. Causes hyperthermia. Treat symptomatically.

SEE SIDE PANELS FOR ADDITIONAL PRECAUTIONS

MANUFACTURED BY
Vulcan Materials Company

CHEMICALS DIVISION / P. O. BOX 7689 • BIRMINGHAM, ALABAMA 35253

EPA Reg. No. 5382-36
EPA Est. No. 5382-KS-1

STC
cor
Do
Do
foc

PES
exc
Law
ins
Age
reg

CON
rec
lan
tie

Our
bell
the
supl
obta
safe
incl
in c