

# GAL® S90

FOR USE IN PAINTS, COATINGS,  
SEALANTS, CAULKS AND FILLERS

Reg. No. 5383-102

Pat. No. 5383-NJ-1

.....	9.90%
.....	4.90%
.....	4.50%
.....	80.70%
TOTAL.....	100.0%

## REACH OF CHILDREN

## PER-PELIGRO

Precaución: Si Vd. No lee inglés no use este producto si no ha sido explicado completamente.

INDUSTRIAL USE ONLY



**ACCEPTED**

SEP 12 2002

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the use as a pesticide, registered under EPA Reg. No. 5383-102

EMERGENCY CALL 1-800-CHEMTREC

INDUSTRIAL CORPORATION  
1000 EAST AVENUE L  
ROSELAND, N.J. 07068

Net Weight: \_\_\_\_\_

ALL TRADEMARKS ARE REGISTERED TRADEMARKS

## ENVIRONMENTAL HAZARDS

Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional office of the EPA.

## DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Mergal®S90 is an antimicrobial preservative for control of fungi and algae growing on paints, coatings, plasters, sealants, and fillers used for architectural products, finishes and special purpose coatings which are exposed to warm, moist, and humid conditions favoring microbial growth.

Typically, Mergal®S90 should be added at the beginning of the formulation process while mixing of the final product (paint, plaster, etc.) to assure uniform distribution of the Mergal®S90.  
PAINTS AND COATING MATERIALS: (0.2-2.0%) add 2-20 lbs. (0.9-9.0 kg.) of Mergal®S90 to each 1000 lbs. (453 kg.) of paint. Use higher addition rate within the above listed and registered range in warm, moist, and humid conditions where microbial growth is favored.  
PLASTERS AND STUCCOS: (0.1-1.0) add 1-10 lbs. (0.45-4.5 kg.) of Mergal®S90 to each 1000 lbs. (453 kg.) of plasters. Use higher addition rate within the above listed and registered range in warm, moist, and humid conditions where microbial growth is favored.  
SEALANTS, CAULKS AND FILLERS: (0.1-1.5%) add 1-15 lbs. (0.45-6.8 kg.) of Mergal®S90 to each 1000 lbs. (453 kg.) of sealant or filler. Use higher addition rate within the above listed and registered range in warm, moist, and humid conditions where microbial growth is favored.

## STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.  
PESTICIDE STORAGE: Store unused product in original container only in a cool, dry area out of reach of children or animals. Storage temperature: 32-104°F (0-40°C).  
PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed of at an approved waste disposal facility.  
CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or if allowed by state and local authorities, by burning. If burned, stay out of smoke.

## WARRANTY

This label provides information which Seller believes to be reliable based on Seller's present state of knowledge relating to this product and its application. This information is not intended to be a guarantee of specific properties of this product or its suitability for a particular application. Seller warrants that this product conforms to the chemical description on this label. SELLER MAKES NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, NOR ANY OTHER WARRANTY EXCEPT AS EXPRESSLY STATED ABOVE. In no event, shall Seller be liable for any consequential, special, indirect, or incidental damages relating to the use of this product.

5383-102

9-12-2002

11