



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

August 25, 2017

Patti Golick
Registration Specialist
Troy Corporation
8 Vreeland Road
Florham Park, NJ 07932

Subject: Notification per PRN 98-10 – Adding Not for Use in California
Product Name: Mergal WP45
EPA Registration Number: 5383-156
Application Date: 06/21/2017
Decision Number: 531821

Dear Ms. Golick:

The Agency is in receipt of your Application for Pesticide Notification under Pesticide Registration Notice (PRN) 98-10 for the above referenced product. The Antimicrobials Division (AD) has conducted a review of this request for its applicability under PRN 98-10 and finds that the action requested falls within the scope of PRN 98-10.

The label submitted with the application has been stamped “Notification” and will be placed in our records.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you have any questions, you may contact Aline Heffernan at 703-347-8602 or via email at heffernan.aline@epa.gov.

Sincerely,

A handwritten signature in black ink, appearing to read "Aline Heffernan".

Zeno Bain, Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

DANGER

CORROSIVE. Causes skin burns and irreversible eye damage. Harmful if inhaled, swallowed or absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

Avoid breathing vapor or spray mist. Do not get in eyes, on skin or on clothing.

Wear chemical-resistant gloves, goggles, face shield, chemical-resistant apron worn over long sleeved shirt and long pants and a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any N, R, P or HE pre-filter.

Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Users should remove PPE immediately after handling this product. Wash the outside of gloves before removing. Follow manufacturer's instructions for cleaning/maintaining PPE. Keep and wash PPE separately from other laundry. . If no such instructions for washables exist, use detergent and hot water.

Wash hands thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco or using the restroom. Remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing.

FIRST AID

IF ON SKIN	<ul style="list-style-type: none"> Take off contaminated clothing Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
IF IN EYES:	<ul style="list-style-type: none"> Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for treatment advice.
IF INHALED:	<ul style="list-style-type: none"> Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth to mouth, if possible. Call a poison control center or doctor for further treatment advice.
IF SWALLOWED	<ul style="list-style-type: none"> Call a poison control center or doctor immediately for treatment advice. Have person sip a glass of water if able to swallow. Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give anything to an unconscious person.

Have the product container or label with you when calling a poison control center or doctor or going for treatment.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage following ingestion. Measures against circulatory shock, respiratory depression and convulsions may be necessary.

MERGAL® WP45

Industrial Preservative and Mildewcide for the Protection of Aqueous Adhesives, Wallpaper Pastes and Tackifiers**, Building Materials**, Coatings, Dispersed Pigments**, Emulsions**, Polymers** and Polyurethanes**, Hydraulic Fluids, Metalworking Fluids, Textiles**, Laundry, Fabric**, Fabric Surfaces**, Vinyl and Plastics**, Wood Coatings and Wood Coatings Solutions including Sapstain Control****

[Sapstain control is not approved for use in State of California**]**

EPA Registration Number	5383-156
EPA Establishment Number	5383-NJ-1

ACTIVE INGREDIENT:.....% Weight	
2-n-octyl-4-isothiazolin-3-one.....	45.0%
INERT INGREDIENTS.....	55.0%
TOTAL.....	100.00

NOTIFICATION

5383-156

The applicant has certified that no changes, other than those reported to the Agency have been made to the labeling. The Agency acknowledges this notification by letter dated:

08/25/2017

KEEP OUT OF REACH OF CHILDREN

DANGER

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

IN CASE OF EMERGENCY CALL 1-800-424-9300

Net Weight:

**Manufactured for:
TROY CHEMICAL CORPORATION.**

One Avenue L
Newark, N.J. 07105

ENVIRONMENTAL HAZARDS

This product is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollution Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Antisapstain treated lumber must be stored under cover, indoors, or at least 100 feet from any pond, lake, stream, wetland, or river to prevent possible runoff of the product into the waterway. Treated lumber stored within 100 feet of a pond, lake, stream, or river must be either covered with plastic or surrounded by a berm to prevent surface water runoff into the nearby waterway. If a berm or curb is used around the site, it should consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

MERGAL WP45 is an industrial preservative for use in the following end use areas:
Aqueous Adhesives, Wallpaper Pastes and Tackifiers**:** For use as a mildewcide for the dry film and wet state preservation of water-soluble and water dispersed adhesives such as animal glues, vegetable glues, natural rubber lattices, polyvinyl acetate, styrene-butadiene, polyurethane, epoxy, acrylic lattices, and tackifiers **derived from rosin and hydrocarbon resins. Can also be used for starch and dextrin based wallpaper pastes**. Use 0.02-0.29% (wt) or 0.02-0.29 lbs. of MERGAL WP45 per 100 pounds of formulation.

[Wallpaper pastes and Tackifiers are not approved for use in State of California**]**

Coatings: For use as a mildewcide for the dry film and wet state preservation of latex and oil-based paints and non-food contact coatings. Depending on the conditions, the amount of MERGAL WP45 may vary but in general use 0.02-0.4% (wt) or 0.02-0.4 lbs. of MERGAL WP45 per 100 pounds of formulation.

DRY FILM PRESERVATIVE FOR WOOD COATINGS AND WOOD COATING SOLUTIONS
To control fungi, add 0.02-0.5% (0.2-5.0 pounds) of this product per 100 gallons of wood coatings or wood coating solutions.

****SAPSTAIN CONTROL**

To control sapstain, treat wood with 1 to 5 qts of MERGAL WP45 per 250 gallons of water. Mix thoroughly before and during use. Apply by spray or dip/immersion system that coats all surfaces of the wood evenly and thoroughly. Treated wood must not be used or placed where it may contact food or animal feed.

[Sapstain control is not approved for use in State of California**]**

See accompanying product information sheet for additional rates and directions for use.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Store in original container.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticides, spray mixture, or rinsate is a violation of federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State pesticide or environmental control agency or the hazardous waste representative at the nearest EPA regional office for guidance.

CONTAINER HANDLING: Non-refillable container: Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or mix tank or store rinsate for later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer for recycling or reconditioning if available, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.



Product Information Sheet
MERGAL® WP45, EPA Reg. No. 5383-156
This document must accompany each shipment of MERGAL WP45

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Building Materials:** For control of bacteria and fungus to protect dry film and wet state building materials such as elastomeric roof and wall coatings, mastics, caulks, sealants, joint cements, spackling, stucco, grout and concrete admixtures. Use 0.02-0.29% (wt) or 0.02-0.29 lbs. of MERGAL WP45 per 100 pounds of formulation. **[**Building materials are not approved for use in State of California**]**

Dispersed Pigments: For use as a mildewcide in the manufacture and storage of dispersed pigments, extender slurries and colorants. Use levels range from 0.01% - 0.25% by weight to provide 45 to 1125 ppm of active ingredient. Add at a point in the production process where sufficient mixing will assure good suspension of the material as other ingredients are added. **[**Dispersed Pigments are not approved for use in State of California**]**

Emulsions, Polymers** and Polyurethanes**:** For use as a preservative in the manufacture and storage of synthetic and natural rubber polymer lattices including acrylic, styrene/butadiene, carboxylated styrene/butadiene, ethylene/vinyl acetate, polyurethane, and biopolymers intended for industrial use such as xanthan gum, gum arabic, guar gum, protein derived polymers, starches and casein derived polymers. Use 0.02-0.29% (wt) or 0.02-0.29 lbs. of MERGAL WP45 per 100 pounds of formulation. **[**Emulsions, Polymers and Polyurethanes are not approved for use in State of California**]**

Hydraulic Fluids: For use as a preservative in the manufacture and use of soluble oils, high water-based and emulsion hydraulic fluids. MERGAL WP45 should be applied directly into the hydraulic concentrate or use dilution hydraulic fluid using a metering pump and uniformly dispersed through the fluid. Highly contaminated systems should be cleaned prior to the application of MERGAL WP45.

For fluid concentrates add sufficient MERGAL WP45 to ensure the end-use dilution fluid will contain 55-165 ppm of product (25-73 ppm active ingredient)

For use-dilution fluids add 0.47-1.44 pounds of MERGAL WP45 per 1000 gallons of emulsion. Repeat until microbial control is achieved. For maintenance use, add 0.09-0.58 pounds of MERGAL WP45 per 1000 gallons of emulsion every 4-6 weeks. This will provide 5-30 ppm active ingredient to the emulsion. More frequent dosing may be necessary depending on the degree of microbial contamination and system design. **[Hydraulic Fluids are approved for use in the State of California for control of fungi only]**



Product Information Sheet
MERGAL® WP45, EPA Reg. No. 5383-156
This document must accompany each shipment of MERGAL WP45

Metalworking Fluids: MERGAL WP45 is recommended for fungal control in the manufacture and use of soluble, synthetic and semi-synthetic metalworking fluids. MERGAL WP45 can be applied using a metering pump for uniform application to the fluid.

For fluid concentrates add MERGAL WP45 at a rate that will provide 55-165 ppm of product (25-73 ppm active ingredient) in the diluted metalworking fluid.

Use-Dilution Fluids: For noticeably fouled systems use 0.47-1.44 pounds of MERGAL WP45 per 1000 gallons of fluid. Repeat until control is achieved. For maintenance use add 0.09-0.58 pounds of MERGAL WP45 per 1000 gallons of fluid ever 4-6 weeks.

Higher dose rates and/or frequency of use may be required depending on the degree of microbial contamination and system design.

Textiles, Laundry Fabric** and Fabric Surfaces**:** For use in prevention of bacterial and fungal growth in the presence of moisture in and on fibers, textiles and fabrics including carpets and backing materials. Not for use in carpet fibers. Apply MERGAL WP45 at a rate of 0.1-0.25% by weight. **[**Textiles, Laundry Fabric and Fabric Surfaces are not approved for use in State of California**]**

Vinyl and Plastics**:** For use as a preservative in PVC flooring and wall covering, interior automotive parts, refrigerator gaskets, shower curtains, mattress covers, rain wear, boots, PVC slippers and gloves. Use MERGAL WP45 at a rate of 0.1-0.5% based on the total weight of the formulation (equates to 0.05-0.5% based on platisol).

MERGAL WP45 can also be used for the preservation of other plastic articles such as automotive tops and external trim, tarpaulins, tents, awnings, indoor/outdoor carpeting backing, garden hoses, pool and pond liners, marine upholstery, roof liners, PVC tiles and fibers. It is used at a rate of 0.15-0.75% based on the total weight of the formulation (equates to 4.35 lbs./1000 lbs. of compound).

MERGAL WP45 is best added to the plasticizer in the production process.

Treated Plastics cannot be used to manufacture children's toys.

[Vinyl and Plastics are not approved for use in State of California**]**

TROY CHEMICAL COMPANY
One Avenue L
Newark, N.J. 07105