

# WRICO® TQC

For the control of algae and slime-forming micro-organisms in recirculating water cooling systems.

## APPLICATION

40-400 ppm of Wrico TQC should be added to the water as an initial treatment, followed by 20-80 ppm every week to ten days as required to control algae and slime.

## ACTIVE INGREDIENTS

## Percent by Weight

n-alkyl (C14, C16, C12, C18) dimethyl benzyl ammonium chlorides	23.75 %
bis (tributyltin) oxide	2.50 %
<u>INERT INGREDIENTS</u>	<u>73.75 %</u>
	100.00 %

C14-60%; C16-30%; C12-5%; C18-5%.

Net weight of 15-gallon drums . . . . . 125 lbs.

Net weight of 30-gallon drums . . . . . 250 lbs.

## **CAUTION: "HARMFUL IF SWALLOWED"**

## **FOR INDUSTRIAL USE ONLY**

May be absorbed through skin. Causes skin irritation. Avoid breathing spray mist. Avoid contact with skin, eyes or clothing. In case of contact, immediately remove contaminated clothing and wash skin with soap and water; for eyes, flush with plenty of water and get medical attention. Wash clothing before reuse. Avoid storage near food and food products.

**WRIGHT CHEMICAL CORPORATION**

Chicago, Illinois 60622

USDA Reg. No. 5427-8

**ACCEPTED**