

## DIRECTIONS

READY TO USE

## DIRECTIONS



# PENTA

## WOOD PRESERVATIVE

**Preserves Wood  
Prevents Fungi and  
Molds of Wood**


**Stops Rot and Decay  
Controls Termites  
Controls Powder Post Beetles**

PENTA WOOD PRESERVATIVE is a clean solution for protecting wood against fungus growths which cause rot and stain, Termites, Powder Post Beetles, and Carpenter Ants.

PENTA WOOD PRESERVATIVE is especially effective in termite control, both as a wood preservative and as a soil poison.

### ASSAY

<b>ACCEPTED</b>		
Feb-3-1969		
ACTIVE INGREDIENTS		
Pentachlorophenol .....	4.15%	
Other Chlorophenols and Related Compounds .....	.60%	
Petroleum Solvents .....	95.00%	
NET INGREDIENTS* .....		.25%
Total .....		100.00%
*Derived from Pentachlorophenol		
UNDER THE FEDERAL INSECTICIDE FUNGICIDE AND RODENTICIDE ACT FOR ECONOMIC POISON REGISTER- ED UNDER NO. 5602-25 SUBJECT TO ATTACHED COMMENTS.		

**CAUTION! Keep Out of Reach of Children!**  
See side panel for additional cautions. 

**HUB-STATE CHEMICAL & EQUIPMENT CORP.**

2000 N. Illinois St.  
Indianapolis, Indiana 46202

### WOOD PRESERVATION

Before treatment, all wood should be normally dry. All unsound wood should be removed two feet beyond any visible evidence of decay.

For best results, PENTA WOOD PRESERVATIVE should be applied so as to effect maximum penetration into the wood and maximum absorption at joints and ends. Complete immersion, where possible, in an open tank is the best procedure for accomplishing this. At least five minutes immersion per inch thickness is recommended for all cases. Where wood will be in direct contact with the ground, such as in the case of fence posts, the immersion period should be from 12-48 hours, and the posts should be peeled of bark, dry and well seasoned.

Where the immersion treatment is impractical, heavy brush application may be used. Where the wood will be in direct contact with the ground, several brush applications should be given. Permit PENTA WOOD PRESERVATIVE to dry at least 72 hours before applying paint. Estimated coverage: 5 to 10 gallons per 1,000 board feet for open tank treatment; 200 square feet per gallon for brush application.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

Do not contaminate water by cleaning the equipment or disposal of wastes.

U.S.D.A. No. 5602-25

NET  
CONTENTS

### TERMITE CONTROL

Clean out carefully all loose wood and debris under or around infested buildings. Spray all ground under buildings at rate of 2 gallons of PENTA WOOD PRESERVATIVE per 5 cubic feet of ground. Break all wood-to-earth contacts, such as steps, door frames, etc., and replace with PENTA treated wood or concrete. Where construction permits, dig a trench around all foundations to a depth of 12 to 18 inches. For buildings with deep foundations, trench 30 inches deep. Apply 2½ gallons of PENTA WOOD PRESERVATIVE to 5 lineal feet of trench. Trees, shrubbery or flowers should be protected from the soil by tar or heavy kraft-paper.

The rate of application for soil use of the product against termites should be 5 gallons of the 5% solution per 10 linear feet of trench up to 15 inches deep and 10 gallons per 10 linear feet for deeper trench.

### WARNING

Harmful if swallowed or absorbed through skin. Causes skin irritations. Do not breath vapor fumes or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly after using. Do not use or store near heat or open flame.

Wear protective clothing and rubber gloves when handling the freshly treated lumber.

## DIRECTIONS

## READY TO USE

## DIRECTIONS

### WOOD PRESERVATION

Before treatment, all wood should be normally dry. All unsound wood should be removed two feet beyond any visible evidence of decay.

For best results, PENTA WOOD PRESERVATIVE should be applied so as to effect maximum penetration into the wood and maximum absorption at joints and ends. Complete immersion, where possible, in an open tank is the best procedure for accomplishing this. At least five minutes immersion per inch thickness is recommended for all cases. Where wood will be in direct contact with the ground, such as in the case of fence posts, the immersion period should be from 12-48 hours, and the posts should be peeled of bark, dry and well seasoned.

Where the immersion treatment is impractical, heavy brush application may be used. Where the wood will be in direct contact with the ground, several brush applications should be given. Permit PENTA WOOD PRESERVATIVE to dry at least 72 hours before applying paint. Estimated coverage: 5 to 10 gallons per 1,000 board feet for open tank treatment, 200 square feet per gallon for brush application.

Do not reuse empty drum. Return to drum recycler or destroy by perforating or crushing and burying in a safe place.

Do not contaminate water by cleaning the equipment or disposal of wastes.

U.S.D.A. No. 5602-25

**NET  
CONTENTS**



# PENTA

## WOOD PRESERVATIVE

**Preserves Wood  
Prevents Fungi and  
Molds of Wood**


PENTA WOOD PRESERVATIVE is a clean solution for protecting wood against fungus growths which cause rot and stain, Termites, Powder Post Beetles, and Carpenter Ants.

**Stops Rot and Decay  
Controls Termites  
Controls Powder Post Beetles**

PENTA WOOD PRESERVATIVE is especially effective in termite control, both as a wood preservative and as a soil poison.

### ASSAY

<b>ACCEPTED</b>	
Feb. 3 - 1969	
5603-25	
<b>ACTIVE INGREDIENTS</b>	
Pentachlorophenol .....	4.15%
Other Chlorophenols and Related Compounds .....	.60%
Petroleum Solvents .....	95.00%
<b>INERT INGREDIENTS*</b>	
Total .....	100.00%
*Derived from Pentachlorophenol	

**CAUTION! Keep Out of Reach of Children!**  
See side panel for additional cautions. 

**HUB-STATE CHEMICAL & EQUIPMENT CORP.**

2000 N. Illinois St.  
Indianapolis, Indiana 46202

### TERMITE CONTROL

Clean out carefully all loose wood and debris under or around infested buildings. Spray all ground under buildings at rate of 2 gallons of PENTA WOOD PRESERVATIVE per 5 cubic feet of ground. Break all wood to earth contacts, such as steps, door frames, etc., and replace with PENTA treated wood or concrete. Where construction permits, dig a trench around all foundations to a depth of 12 to 18 inches. For buildings with deep foundations, trench 30 inches deep. Apply 2 1/2 gallons of PENTA WOOD PRESERVATIVE to 5 linear feet of trench. Trees, shrubbery or flowers should be protected from the soil by tar or heavy kraft paper.

The rate of application for soil use of the product against termites should be 5 gallons of the 5% solution per 10 linear feet of trench up to 15 inches deep and 10 gallons per 10 linear feet for deeper trench.

### WARNING

Harmful if swallowed or absorbed through skin. Causes skin irritations. Do not breath vapor fumes or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly after using. Do not use or store near heat or open flame.

Wear protective clothing and rubber gloves when handling the freshly treated lumber.