



# Marine OUTBOARD & OUTDRIVE CLEAR ANTI-FOULING PAINT No. 6987

INGREDIENTS  
EPA Registration No. 5625-1

KEEP OUT OF REACH OF CHILDREN  
DANGER

STATEMENT OF PRACTICAL EXPERIENCE  
Net Contents 12 ounces (340 grams)

### FOR COMMERCIAL AND NON-COMMERCIAL USE.

**PRECAUTIONARY STATEMENTS:**  
**HAZARDOUS TO HUMANS & DOMESTIC ANIMALS:** Corrosive. Causes irreversible eye damage and burns. Harmful if absorbed through skin, swallowed or inhaled. Do not get on skin, in eyes or on clothing. Wear goggles, face shield or safety glasses. Wear protective clothing such as long sleeved cotton shirt, long pants, hat and gloves. Wash thoroughly with soapy water after handling. Remove contaminated clothing and wash before reuse. Avoid breathing vapor or spray mist. Use with adequate ventilation. When used in confined areas, while spraying and/or sanding boat surface, wear a mask or respirator jointly approved by the Mining Enforcement and Safety Administration and the National Institute for Occupational Safety and Health.  
**ENVIRONMENTAL HAZARD:** This pesticide is toxic to aquatic organisms including fish and shellfish. Do not apply directly to water by cleaning of equipment or waste disposal. Do not allow chips or dust generated during paint removal to enter water.  
**PHYSICAL OR CHEMICAL HAZARD:** Contents under pressure. Do not use or store near heat or open flame. Do not puncture or incinerate container. Exposure to temperatures above 130°F may cause bursting.

**DIRECTIONS FOR USE:** It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. For use only on outboard motor and/or lower drive units of vessels. Any other use is unlawful. WHEN PROPERLY APPLIED, THIS AEROSOL ANTI-FOULANT WILL PROVIDE ANTI-FOULING PROTECTION AGAINST BARNACLES AND MARINE GROWTH. Tempo Clear aerosol Antifoulant is specifically designed for coating outdrive and outboard motor lower units. All surfaces to be coated with antifoulant must be prepared in accordance to the following instructions. Users must comply with all applicable OSHA requirements.  
**INSTRUCTIONS FOR USE:** 1. Make sure surface is free of grease, wax, oil, loose paint and surface is dry. 2. Mask off areas not being sprayed. 3. Prime prepared surfaces with Tempo's Clear Primer #6987. 4. Apply Tempo Antifoulant in at least three thin coats, allowing one hour dry time between applications. Hold can 12" to 16" from surface. Spray in short passes to control film thickness and avoid runs. 5. Allow coated unit to air-dry overnight before immersion. Maximum adhesion and durability will be achieved by allowing an additional 8 hour cure time in water before use.

**NOTE:** This can contains sufficient coating for one outdrive. Entire contents MUST be applied to obtain best antifoulant protection.

**STORAGE & DISPOSAL:**  
\* Do not contaminate water, food or feed by storage or disposal.  
**-PESTICIDE DISPOSAL:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste Representative at the nearest EPA Regional Office for guidance. Paint chips, spent abrasives, and any other waste materials from removal of old paint must be disposed of in a sanitary landfill (or, if required by Federal, State or local regulations, handled as a hazardous waste). If possible, use all of the contents by application according to label instructions.  
**-CONTAINER DISPOSAL:** Do not reuse empty container. Replace cap and dispose of in a sanitary landfill or by other approved State and local procedures. Do not puncture or incinerate.  
**OSHA REGULATIONS NCE-CFR 1910.1209**  
Required November 1985  
Exact Chemical Identity Being Withheld as a Trade Secret. Solvents may present an inhalation and/or skin absorption hazard when not used in accordance with safety instructions found on this label. Also, solvents herein may cause skin irritation upon repeated or prolonged contact, eye irritant.



TEMPO PRODUCTS COMPANY  
6200 Cochran Road,  
Solon, Ohio 44139 • U.S.A.

**ACCEPTED**  
FEB 14 1997  
Under the Federal Insecticide,  
Fungicide, and Rodenticide Act,  
as amended, for the pesticide  
registered under  
EPA Reg. No. 5625-1

BEST AVAILABLE COPY

MPC

1096 LE1046903X