

FOR COMMERCIAL USE ONLY

DIRECTIONS FOR USE:

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

58SAF is an extra strong Antifouling paint designed for long term exposure in tropical water.

It may be applied by brush, roller or spray to steel vessels operating in fresh and/or salt water and subject to attack by barnacles, algae, tube worms, and other fouling organisms.

SURFACE PREPARATION: Clean surface thoroughly of grease, oil, loose paint, dirt, mildew, rust scale or any other foreign material.

PRIMING: A Farboil primer must be applied to bare, newly sandblasted or porous surfaces before painting.

Always apply paint to a dry surface.

Stir paint thoroughly from the bottom.

IMPORTANT: If it is necessary to paint under unusual conditions, call your Farboil representative for technical service.

BEST DOCUMENT AVAILA

58SAF

Farboil

A BEATRICE CHEMICAL COMPANY
DIVISION OF BEATRICE FOODS CO.

8200 Fischer Road
Baltimore, Maryland 21222
U.S.A.

5 U.S. C

4.175 H

1A22

Farboil

CHLORINATED RUBBER ANTIFOULING 58SAF

For use on ships and boats. Do not use on
other surfaces.

8.12
91.5%
100%

CONTAINS PETROLEUM DISTILLATES
KEEP OUT OF THE REACH OF CHILDREN

DANGER

PRECAUTIONARY STATEMENTS

HAZARDOUS TO HUMANS & DOMESTIC ANIMALS

Labels and by the Manufacturer for Occupational Safety and Health under the provisions of 29 CFR 1910.1201. May be fatal if swallowed and absorbed through the skin. Wash thoroughly with soap and water after handling. Do not breathe vapors or spray mist.

PRACTICAL TREATMENT: If swallowed: Drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

If in eyes: Flush with plenty of water. Get medical attention.

If on skin: Wash with plenty of soap and water. Get medical attention.

If inhaled: Remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention.

ENVIRONMENTAL HAZARD: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning equipment or disposal of waste. Do not allow chips and dust generated during use to enter water. Dispose of paint debris in an approved landfill.

CHEMICAL AND PHYSICAL HAZARDS: Do not use in areas where fire or explosion may occur.

ASH POINT 85°F PAINT LIQUID

E.P.A. REG. NO. 5633-9
E.P.A. EST. NO. 5633-MD-1

BLE

3 gallons
Imperial Gallons
1 quart

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Pesticide Disposal:

Pesticide, paint or rinsate that cannot be used according to label instructions must be disposed of according to Federal, State or local procedures under Subtitle C of the Resource Conservation and Recovery Act

Container Disposal

Triple rinse (or equivalent) and offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill or by other approved State and local procedures

CONTAINS XYLENE

BEST DOCUMENT AVAILABLE

FLAMMABLE

**DO NOT USE OR STORE NEAR
HEAT OR OPEN FLAME**

58SAF

Farboil

A BEATRICE CHEMICAL COMPANY
DIVISION OF BEATRICE FOODS CO.
8200 Fischer Road
Baltimore, Maryland 21222
U.S.A.