

BEATRICE DIVISION

FARBOIL

**6060S FORMULA 105
COLD PLASTIC
MIL-P-19451B
ANTIFOULING PAINT
FOR SHIP BOTTOMS**

ACTIVE INGREDIENT	37.84%
Cuprous Oxide	62.16%
INERT INGREDIENTS	100.00%

CAUTION: Harmful if swallowed.
KEEP OUT OF REACH OF CHILDREN.
DIRECTIONS FOR USE: 6060S is applied to ship's bottom
by brush, roller or spray.
FOR PROFESSIONAL USE ONLY IN SHIPYARDS
EPA Reg. No. 5633-14

CONTENTS FIVE GALLONS

CAUTION: See Side Panel for
Caution Statement

NET CONTENTS

5 U.S. Gallons
4.175 Imperial Gals.
18.925 Liters

FARBOIL

DIRECTIONS

Preparation: Do not apply any Farboil coating until surface is thoroughly cleaned of grease, oil, loose paint, dirt, mildew, rust scale or any other foreign material.

Apply coating to DRY SURFACE.

Farboil primer should be applied to bare or porous surface before painting.

Painting: Be sure to mix enough color at one time to do the entire job. If more than one container is used, box together thoroughly for complete color uniformity.

Stir Paint Thoroughly From the Bottom.

Apply Farboil paints by brush, spray or roller.


IMPORTANT: If it is necessary to paint under unusual conditions, call your Farboil Company Representative for technical advice.

KEEP AWAY FROM FIRE OR OPEN FLAME

Do not re-use container. Dispose of container properly when empty. Do not contaminate water by cleaning of equipment or disposal of waste.

FARBOIL COMPANY

A DIVISION OF BEATRICE
BALTIMORE
MARYLAND, U.S.A.



CAUTION!

USE WITH ADEQUATE VENTILATION. Avoid contact with skin and breathing of vapor or spray mist.

COMBUSTIBLE. Keep away from heat and open flame. Close container after each use.

KEEP OUT OF THE REACH OF CHILDREN

9462-105 Rev. 4-78

ACCEPTED WITH COMMENTS

5633-14

Comment