

6157S

Farboil

6157S MIL-P-15931-D ANTIFOULING VINYL TYPE II, CLASS I, FORM 124

ACTIVE INGREDIENT: Cuprous Oxide
INERT INGREDIENTS:

55.54%
44.46%
100.00%

CONTAINS PETROLEUM DISTILLATES
KEEP OUT OF THE REACH OF CHILDREN

WARNING

PRECAUTIONARY STATEMENTS

HAZARD TO HUMANS & DOMESTIC ANIMALS

Causes eye irritation. Do not get on skin, clothing or in eyes. Wear a face shield and rubber gloves when handling. Use in a well-ventilated area. Wear protective clothing such as gloves, long sleeved cotton shirt, long pants and hat. When used in confined areas or applied by spraying wear a pesticide respirator jointly approved by the Mining Enforcement and Safety Administration (formerly the U.S. Bureau of Mines) and by the National Institute for Occupational Safety and Health under the provisions of 30 CFR 11. May be fatal if swallowed or inhaled. Harmful if absorbed through the skin. Wash thoroughly with soap and water after handling. Do not breathe vapors or spray mist.

PRACTICAL TREATMENT: In case of skin contact remove contaminated clothing and immediately wash skin with soap and water. Get medical attention. Wash contaminated clothing before reuse. If inhaled, remove to fresh air. Use artificial respiration if breathing has stopped. Get immediate medical attention. If swallowed, do not induce vomiting. The product contains petroleum distillates. Get immediate medical attention. If in eyes, flush eyes with water. Get medical attention.

ENVIRONMENTAL HAZARD: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning equipment or disposal of waste. Do not allow chips and dust generated during paint removal to enter water. Dispose of paint debris in an approved landfill.

CHEMICAL AND PHYSICAL HAZARDS: Do not use near heat or open flame.

FLASH POINT 68 F PAINT LIQUID

E.P.A. REG. NO. 5633-2
E.P.A. EST. NO. 5633-M

allons
perial Gallons
iters



04.03
004 0

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

Pesticide Disposal:

Pesticide, paint or rinsate that cannot be used according to label instructions must be disposed of according to Federal, State or local procedures under Subtitle C of the Resource Conservation and Recovery Act.

Container Disposal:

Triple rinse (or equivalent) and offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved State and local procedures.

**CONTAINS KETONE
AND XYLENE**

FLAMMABLE

**KEEP AWAY FROM HEAT AND
OPEN FLAME**

6157S



TECHNICAL DATA

Farboil

8200 Fischer Road,
Baltimore, Md. 21222
(301) 477-8200

PRODUCT: ANTIFOULING VINYL BLACK
MIL-P-15931 Form 124

CODE: 6157 E

FOR INDUSTRIAL USE ONLY

GENERAL DESCRIPTION:

A heavy duty vinyl antifouling Black that gives protection on underwater structures for extended periods of time. Conforms to Formulas 124, MIL-P-15931.

VEHICLE	Vinyl
COLOR & APPEARANCE	Black Matte
VISCOSITY	Heavy
WT/GAL., LBS.	17.5 ± .2
SOLIDS % BY WT.	81
SOLIDS % BY VOLUME	52.2
THEO. COVERAGE FT ² /GAL/MIL	837
FLASH POINT °F/METHOD	68° C.C.
SHELF LIFE UNMIXED	Single package - One year.
FILM THICKNESS	
WET	4--8 mils
DRY	2--4 mils
REDUCTION	
BRUSH	Small areas.
CONVENTIONAL	Spray Air or Airless
THINNERS - SLOW	SL 36
THINNERS - FAST	SL 21
THINNERS - CLEAN UP	SL 21

The manufacturer makes no warranties of merchantability or freedom from patent infringement and there are no warranties which extend beyond the description on the face hereof including any warranty as to fitness for a particular use.

APPLICATION EQUIPMENT
(TYPICAL)

Air: DeVilbiss MBO gun, D needle and
Pressure Pot, 64 Air can or equal.

Airless: Grayco or Equal: Pump 30-1;
Air Pressure 80 ; Tip .025 - .028

PROCEDURES

Make sure all pigment is mixed well. A
mechanical mixer is advisable.

SURFACE PREPARATION
NEW WORK

Must be applied over Vinyl Anti-Corrosive.

RECOAT

Apply over clean vinyl coating only.

DRY TIME (HOURS)
TYPICAL

Set to Touch 1/4 hour
Hard 3/4 hour
Recoat 4 hours

Immerse when final coat is dried 4 hours
minimum.