(Front Panel)

BOWL GARD® AUTOMATIC BOWL CLEANER



SANITIZES BOWL WATER CONTINUOUSLY FOR FOUR MONTHS

KEEP OUT OF REACH OF CHILDREN

DANGER:

STATEMENT OF PRACTICAL TREATMENT:

IF SWALLOWED, drink large amounts of water. DO NOT induce vomiting. Call a physician or poison control center immediately.

IF ON SKIN: Brush off excess chemical and flush skin with cold water for at least 15 minutes.

If irritation persists get medical attention.

IF IN EYES: Flush with cold water for at least 15 minutes. Get medical attention.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

NET CONTENTS 14 OZ.



PRECAUTIONARY STATEMENT: HAZARDS TO HUMAN AND DOMESTIC ANIMALS

DANGER:

Highly corrosive causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin or on clothing. Irritating to nose and throat. Avoid breathing dust. Wear goggles or face shield and rubber gloves when handling. Remove and wash contaminated clothing before reuse.

PHYSICAL AND CHEMICAL HAZARDS:

Strong oxidizing agent. Mix only with water. Once in the toilet tank, do not remove until completely dissolved.

The Clorox Company Oakland, CA 94612 Made in USA

EPA Reg. No. 5813-47

EPA Est. No 5813-XX-XXX

("Drop-in" label)



AUTOMATIC BOWL CLEANER

To open jar, remove this seal to expose special plug closure. To remove cleavre, hold jar itimly on flat surface, press dot in center of plug to unlock tab, grasp tab and pull plug out.

To install, place far on bottom of toilet tank, underneath the float, with the hole facing upwards.


OATE INSTALLEC (Replace in approximately 4 months)

LIFT HERE



(Side Panel)

ł



DIRECTIONS FOR USE:

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

TO INSTALL: Clean toilet bowl thoroughly especially under the rim, using a good cleanser disinfectant such as PINE-SOL® Cleaner. Remove top of tank. Lift seal from top of jar. Write the month of installation on seal and stick on outside of tank. To remove plug from center of lid, hold jar firmly on that surface, press dot in center of plug to unlock tab, grasp tab and pull plug out. To install, flush toilet to drain out all water from tank, then place jar on tank bottom underneath the float with the hole facing upwards.

STORAGE AND DISPOSAL:

STORAGE: Before use, keep in cool dry well ventilated place away from flame or heat.

DISPOSAL: Wear rubber gloves. Remove top of tank, flush toilet to drain water. Avoid spilling by carefully pouring some of the liquid from the jar into the tank. Leave solids in jar. Wrap jar in plastic bag; seal and place in trash container. Wash hands thoroughly.

BOWL GARD® Automatic Bowl Cleaner helps control germs, odors, bowl ring and stains 24 hours a day for four months (based on a average of ten flushes a day). The formula in BOWL GARD® Automatic Bowl Cleaner gives a clean you can see and smell, plus sanitizing action.

- · Sanitizes toilet bowl water between flushes.
- · Cleans ring, rust and mineral stains from the bowl. So effective it almost eliminates brushing.
- Deodorizes the bathroom area, not by covering up odors, but by eliminating them. Leaves a fresh clan smell.

Use BOWL GARD® Automatic Bowl Cleaner in every toilet in your home. It works hard in heavily-used toilets. Great for guest bathrooms too.

Unusual situations may cause stains to appear over time. For these occasional instances, flush, brush the soiled surfaces with bowl water, then flush again.

BOWL GARD® Automatic Bowl Cleaner sanitizes, cleans and deodorizes.