

Bartel's
REDYCOAT

"BARTEL . . . quality products since 1932"

DESCRIPTION

A clear preservative for wood. Prevents destruction of wood by rot, mold, and termites. Use on fence posts, fencing, siding, and decks. Can be painted when dry. Does not contain water repellents.

CAUTION: DO NOT USE, POUR, SPILL, OR STORE NEAR HEAT OR OPEN FLAME. Harmful if swallowed, inhaled, or absorbed through skin. May cause skin irritation. Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing. Do not reuse container. Destroy when empty. **ANTIDOTE:** External: Wash with rubbing alcohol followed by soap and water. Internal: Call a physician immediately. Drink warm water mixed with tablespoon of salt, milk or egg white to force vomiting. Lie down; keep warm.

KEEP OUT OF REACH OF CHILDREN

EPA Reg. No. 5831-2

"BARTEL . . . Quality Products Since 1932"
 Made in U.S.A.

**PENTALENE
 Wood Preservative**

READY TO USE
 STOPS ROT
 KILLS TERMITES
 DRIES CLEAR
 PAINTABLE

454

ACTIVE INGREDIENTS:	
Pentachlorophenol	4.3%
Other Chlorophenols8%
Mineral Spirits	94.8%
INERT INGREDIENTS:	3%
Total	100.0%

*Contains 5.2% Pentachlorophenol as defined in Federal Specification TT-W-570.

1 GALLON — U.S. MEASURE

GILSONTE, INC., Portland, Oregon

ACCEPTED
Aug. 24, 1972
 UNDER FEDERAL REGULATION
 FOR ENVIRONMENTAL PROTECTION
 E.P.A. REG. NO. 5831-2
 TO ATTACH TO LABELS.

Bartel's

REDYCOAT

"BARTEL . . . quality products since 1932"

DESCRIPTION

A clear preservative for wood. Prevents destruction of wood by rot, mold, and termites. Use on fence posts, fencing, siding, and decks. Can be painted when dry. Does not contain water repellents.

CAUTION: DO NOT USE, POUR, SPILL, OR STORE NEAR HEAT OR OPEN FLAME. Harmful if swallowed, inhaled, or absorbed through skin. May cause skin irritation. Do not breathe vapor or spray mist. Do not get in eyes, on skin, or on clothing. Do not reuse container. Destroy when empty. **ANTIDOTE:** External: Wash with rubbing alcohol followed by soap and water. Internal: Call a physician immediately. Drink warm water mixed with tablespoon of salt, milk or egg white to force vomiting. Lie down; keep warm.

KEEP OUT OF REACH OF CHILDREN

EPA Reg. No. 5831-2

"BARTEL . . . Quality Products Since 1932"
Made in U.S.A.

PENTALENE Wood Preservative

READY TO USE
STOPS ROT
KILLS TERMITES
DRIES CLEAR
PAINTABLE

454

ACTIVE INGREDIENTS:	
Pentachlorophenol	4.3%
Other Chlorophenols	6.9%
Mineral Spirits	94.8%
INERT INGREDIENTS:	3%
Total . . . 100.0%	

*Contains 5.2% Pentachlorophenol as defined in Federal Specification TT-W-570.

1 GALLON -- U.S. MEASURE



GILSONITE, INC., Portland, Oregon

Handwritten notes and stamps:
A
241 19 34
1932-2

Bartel's REDYCOAT

"BARTEL . . . quality products since 1932"

PENTALENE Wood Preservative

READY TO USE
STOPS ROT
KILLS TERMITES
DRIES CLEAR
PAINTABLE

454

1 GALLON -- U.S. MEASURE

ACTIVE INGREDIENTS:	
Pentachlorophenol	4.3%
Other Chlorophenols6%
Mineral Spirits	94.8%
INERT INGREDIENTS:	
.....	.3%
Total	100.0%

*Contains 5.2% Pentachlorophenol as defined in Federal Specification TT-W-570.

GILSONTE, INC., Portland, Oregon

APPLICATION

Stir or shake thoroughly to mix contents. Soak wood for a minimum of three minutes or apply, liberally, two or more brush coats. All possible surfaces should be covered, especially those to be in contact with the soil, joints and end grains. Wood to be treated should be dry and free from bark. For best penetration, use at temperatures above 70 degrees F. At least 24 hours drying time should be allowed before application of top coats. Fence posts should be soaked in preservative for 12 to 48 hours.

For protection against termites treat wood prior to use in construction. Wear protective clothing and rubber gloves when handling the freshly treated lumber. This product is toxic to fish and wildlife. Do not contaminate water by cleaning of equipment or disposal of wastes.

CONDITION OF SALE

Seller makes no warranty, expressed or implied, concerning the use of this product other than indicated on the label. Buyer assumes all risk of use and/or handling of this material when such use and/or handling is contrary to label instructions.