



Nu-Lastic

WOOD PRESERVATIVE

Nu-Lastic Wood preservative prevents the swelling, shrinking, warping, splitting and grain raising caused by moisture penetration. It also protects wood against termites and certain other wood destroying insects and prevents fungus growth that causes rot and stain.

SURFACE PREPARATION

New wood, millwork and other lumber products should be thoroughly dry before applying Nu-Lastic Wood Preservative.

Fence posts and foundation timbers should be dry, well seasoned and free from bark.

DIRECTIONS

Millwork: Dip three (3) minutes for each inch of thickness.

Other Lumber Products: Dip three (3) minutes or apply two (2) or more saturating coats by brush or spray, particularly where wood will contact the soil.

Fence Posts and Foundation Timbers: Immerse in Nu-Lastic Wood Preservative for at least 12 hours. For maximum effect allow 48 hours immersion.

NOTE: Allow wood to dry thoroughly before painting or varnishing. Normally, 48 hours dry is sufficient.

CAUTION!

CONTAINS PETROLEUM DISTILLATE AND PENTACHLOROPHENOL
COMBUSTIBLE

Keep away from heat and open flame. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. Causes skin irritation. Do not get in eyes, on skin or clothing. For eyes, flush with plenty of water for at least 15 minutes and get medical attention. Do not breath vapor or spray mist. Remove and wash contaminated clothing before reuse. Wash thoroughly after using. Do not contaminate any body of water by cleaning of equipment or disposal of waste as this material is toxic to fish.

Use with adequate ventilation.

M. A. BRUDER & SONS

- REDUCES PAINT FAILURE
- IDEAL SEALER FOR NEW WOOD
- GIVES LONG, PROTECTIVE SERVICE

ACCEPTED

Jan-29-1947

5839-3

U. S. P. Reg. No. 42202

NEW PRODUCTS
WOOD TREAT WITH
MU-LASTIC WOOD PRESERVATIVE

- | | |
|--------------------|---------------------|
| <u>Floors</u> | <u>Construction</u> |
| <u>Window Sash</u> | <u>Lumber</u> |
| <u>Doors</u> | <u>Garages</u> |
| <u>Porch Steps</u> | <u>Foils</u> |
| <u>Fence</u> | <u>Boats</u> |
| <u>Railings</u> | <u>Decks</u> |
| <u>Porches</u> | <u>Boxes</u> |
| <u>Screen Sash</u> | <u>Chicken</u> |
| <u>Trim</u> | <u>Coops</u> |
| <u>Shingles</u> | <u>Barns</u> |
| <u>Siding</u> | <u>Wagons</u> |
| <u>Joists</u> | <u>Mouldings</u> |
| <u>Timbers</u> | <u>Cabinets</u> |
| <u>Trellises</u> | |

Wood

Active Ingredients
Pentachlorophenol
Cresol
Phenols
Petroleum Hydrocarbons
Inert Ingredients

carping, split-
protects wood
vents fungus

oroughly dry

ned and free

(2) or more
ntact the soil.

Wood Pre-
rs immersion.

ishing. Nor-

OL

duce vomiting
eyes, on skin
nutes and get
contaminated
e any body of
toxic to fish

S

A. PA.

WOOD

Fence Po