

Maura K. Scott
M.A. Bruder & Sons, Inc.
52nd & Grays Avenue
Philadelphia, PA 19143

Dear Ms. Scott:

Subject: Revised Labeling
Woodlastic Preservative Clear 089-079
EPA Registration No. 5839-9
Your Submission Dated March 15, 1994

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act (FIFRA), as amended is acceptable provided that you:

1. Make the labeling changes listed below before you release the product for shipment bearing the amended labeling:

- The EPA Reg. No. and EPA Est. No. are obscured by the dark line that appears in the picture on the front panel. Move the EPA Reg. No. and EPA Est. No. so both are clearly visible.

2. Submit one (1) copy of your final printed labeling before you release the product for shipment.

A stamped copy of the labeling is enclosed for your records.

Sincerely yours,

(S)

Cynthia Giles-Parker
Product Manger (22)
Fungicide Herbicide Branch
Registration Division (7505C)

Enclosure

WOOD-LASTIC CLEAR 089-079

Jack

Wood-Lastic Clear is for exterior use on above ground wood. It inhibits warping, shrinking, swelling, checking, cracking and water marking of the wood. It also protects and preserves wood against mold, mildew, rot, wood destroying fungi, mildew stain and attack by termites.

RECOMMENDED USES:

Wood-Lastic Clear is for above ground use only. It can be used to protect shingles, millwork, windows, outdoor furniture, posts, fences, decks, porch steps and house siding. Do not apply over bark, painted/varnished surfaces or pressure treated wood surfaces.

SURFACE PREPARATION:

New wood, millwork and other lumber products should be thoroughly dry, well seasoned and free from bark before applying Wood-Lastic Clear. Do not use on wood intended for food, feed, potable water, livestock or dairy animals contact surfaces. May injure living plants during application. Cover plants to protect against direct contact.

APPLICATION: For millwork and other lumber products, dip three minutes for each inch of thickness or apply two or more saturating coats by brush or roller. Wood should be treated after all cuts are made and before use in the structure.

NOTE: Allow treated wood to dry thoroughly before painting, usually 48 hours under normal conditions.

COVERAGE:

100-300 square feet per gallon. Coverage will vary depending on the porosity of the wood and method of application.

USE WITH ADEQUATE VENTILATION: Open windows and doors, or use other means to ensure air entry during application and drying. If dizziness, headaches, or eye watering is experienced, wear respiratory protection (NIOSH/MSHA TC 23C or equivalent) or leave the area.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS CAUTION

Harmful if swallowed or absorbed through skin. Avoid contact with eyes, on skin or on clothing. Wash thoroughly after handling.

FIRST AID PROCEDURE:

If SWALLOWED, do not induce vomiting, CALL PHYSICIAN IMMEDIATELY. IF ON SKIN, wash thoroughly with soap and water. IF IN EYES, flush with plenty of water and get immediate medical attention. CONTAMINATED CLOTHING should be removed and washed thoroughly before reusing.

ENVIRONMENTAL HAZARDS:

This product is toxic to fish. Do not apply directly to water, to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water by disposal of equipment washwaters.

PHYSICAL OR CHEMICAL HAZARDS:

Apply this product only as specified on the label. Use only with adequate ventilation. Close container after each use. Do not use, pour, spill or store near heat or flame.

DIRECTION FOR USE:

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL:

Store at temperatures between 40°F and 100°F. If the product has been spilled or is leaking, remove the source of the spill or leak. Recover free liquid. Spread absorbent, then pick up and place in containers. Then, where applicable, wash area with detergent and water. Store product in the original container only. Keep container closed when not in use. Do not use empty container. Wrap container and put into trash collection.

NOTICE: Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage.

Distributed by: M.A. Bruder & Sons, Incorporated

BR

Philadelphia, PA (215)353-5100 • Orlando, FL (407)851-6160
Terre Haute, IN (812)234-6621 • Dayton, OH (513) 223-3323



BEST

394

1974

1974

ACC
with CO
in EPA

MAR 2

583

**RESERVE
WATER SUPPLY**

Water Above Ground

Clear 09-079

One Gallon (3.785 Liters)

KEEP OUT OF REACH OF CHILDREN

HAZARDOUS TO HUMANS - NOT ALLOWED

BEST AVAILABLE COPY