DIRECTIONS

Bathroom:

Use dilution 1:60 in water or 2 oz. per gallon. Wet all surfaces thoroughly.

Public Areas:

Use 1:60 in water or 2 oz. per gallon. Spray freely so as to wet all surfaces thoroughly.

Garbage Receptacles:

To check the development of putrefactive action and to aid in checking the breeding of flies, spray garbage in receptacle with 1:60 solution in water. Repeat treatment with each addition of garbage.

TOILET BOWLS: DIRECTIONS

The use solution should be 2 ounces of product added directly to the residuater in the bowl. When cleaning toilet bowls, all bowl surfaces should be thoroughly swabbed.

PINE OIL DISINFECTANT

COEF. 5

FOR INDUSTRIAL USE ONLY

E.P.A. REG. NO. 6125-2

· WARNING ·

KEEP OUT OF REACH OF CHILDREN

NOTE: See First Aid and Additional Precautions on Side Panel.

ACTIVE INGREDIENTS

PINE OIL	81.0%
SOAP	9.96%
INERT INGREDIENTS	9.04%

TOTAL 100.0%

CONTENTS

GALLON

Fic

Sto

an

Va

ph

ski

Av

WC

ge

MANUFACTURED BY

Bixon Chemical Corporation 50-19 97th PLACE CORONA, N.Y. 11368

PINE OIL DISINFECTANT

COEF. 5

FOR INDUSTRIAL USE ONLY

E.P.A. REG. NO. 6125-2

• WARNING •

KEEP OUT OF REACH OF CHILDREN

NOTE: See First Aid and Additional Precautions on Side Panel.

ACTIVE INGREDIENTS

PINE OIL	81.0%
SOAP	9.96%
INERT INGREDIENTS	9.04%
TOTAL	100.0%

CONTENTS

GALLON

() 14

MANUFACTURED BY

Bixon Chemical Corporation 50-19 97th PLACE CORONA, N.Y. 11368

NOTE:

Rinse empty container thoroughly with water and discard it.

material is used on surfaces which may come in contact with food, rinse with potable water after using disinfectant. Floors, Walls, Woodwork, Stainless Steel, Porclein Tiles, Sinks, Toilet Seats, and Urinals, Garbage Receptacles.

WARNING:

If swallowed, do not induce vomiting. Vomiting may be harmful, consult a physician. May cause eye damage or skin irritation. Do not get into eyes. Avoid skin contact. If eye contact occurs, wash eyes immediately with water and get medical attention.

6 MAR 1974

Testicides Regulation

nivisim. EPA

z. per y.

allon. fac**e**s

efacg the in revater.

on of

unces residaning

hould