

# HIGHEST *Quality*

ACCEPTED  
May 25 1970  
FOR USE IN THE U.S.A.  
ED UNLESS OTHERWISE SPECIFIED  
TO ATTACHED COMMENTS

## GOODYEAR BLACK WOOD PRESERVER

Active Ingredients .....	100%
Pentachlorophenol .....	4.4%
Other Chlorophenols .....	0.6%
Petroleum Oils .....	57.0%
Petroleum Asphalts .....	38.0%

**WARNING!**

KEEP OUT OF THE REACH OF CHILDREN  
See Other Warnings



U. S. GALLON  
MEASURE



PAINTS AND WATERPROOFING COMPOUNDS FOR INDUSTRY, INSTITUTIONS AND GOVERNMENT

# Quality

Active Ingredients .....	100%
Pentachlorophenol .....	4.4%
Other Chlorophenols .....	0.6%
Petroleum Oils .....	57.0%
Petroleum Asphalts .....	38.0%



U S GALLON  
MEASURE



S FOR INDUSTRY, INSTITUTIONS AND GOVERNMENT

USDA Reg. No. 6173-4

### WARNING

Harmful if swallowed or absorbed through skin! Causes skin irritation! Do not breathe vapor or spray mist. Do not get in eyes, on skin or on clothing. Wash thoroughly with soap and warm water after handling. **KEEP AWAY FROM CHILDREN.** Keep away from heat and open flame. Keep container closed when not in use.

### DIRECTIONS

Stir thoroughly or shake well to mix contents before using. Apply liberally with a paint brush, paint spray gun or dip wood into the liquid and allow to soak for at least 5 minutes. Posts and heavy timbers should be free of bark, dry, well seasoned and should be dipped for 12 to 48 hours, or receive two or more free flowing coats of preservative. Will penetrate best at temperatures above 70° F. Permit treated material to dry at least 24 hours before handling.

Manufactured For



## CONSOLIDATED

