



Net Contents U.S. Gallons

Concentrated Slimicide for industrial re-circulating water cooling systems. Helps keep water systems clear and free of bacterial and algal slimes.

ACTIVE INGREDIENTS: 10%
n-Alkyl (60% C14, 30% C16, 5% C12, 5% C18) dimethyl benzyl ammonium chlorides... 5.00%
n-Alkyl (50% C12, 30% C14, 17% C16, 3% C18) dimethyl ethylbenzyl ammonium chlorides... 5.00%
INERT INGREDIENTS: 90%
Water

When TW-30 is used as directed, it will aid in controlling and/or preventing the development of unsanitary slime conditions which are unsightly, produce foul odors and which are often the cause of equipment breakdown. TW-30 is compatible with virtually all corrosion inhibition additives but should not be used in the presence of soap or other anionic detergents.

DIRECTIONS

INITIAL DOSE: 1-2 gallons TW-30 to 5,000 gallons of water.
PERIODIC DOSE: 1-3 quarts TW-30 to 5,000 gallons of water every 7 days or sooner should visible growth appear.
For best results, rid system of organic debris if possible. If soap or anionic detergent is used, rinse thoroughly before charging with TW-30. Do not be alarmed with the sudden appearance of a considerable amount of organic debris in the system during the first week of operation. This is normal and is a good indication that TW-30 has effectively penetrated and dislodged dead organic material which tenaciously adheres to metal and wooden surfaces as living matter.



MR. SANICO

CAUTION: KEEP OUT OF REACH OF CHILDREN. Avoid contamination of food; harmful if swallowed. Avoid contact with skin and eyes. In case of contact, flush plenty of water. Rinse empty container thoroughly with water and discard it.

U.S.D.A. Reg. No. 6190-7

SANICO

13143 Saticoy St. North Hollywood, California 91605

50-B

North Hollywood ★ Santa Ana ★ Albuquerque ★ Boise ★ Phoenix ★ Denver ★ Portland ★ Honolulu ★ San Francisco ★ San Diego ★ Salt Lake

