

Wood Preserving Compound For Professional Use Only,

For the Control of Termites and Decay

ACCEPTED

May 15.

1973

UNDER THE FEDERAL INSECTICIDE FUNGICIDE AND ROD NTICIDE ACT FOR ECONOMIC POIS IN REGISTER. ED UNDER NO. (3/4-/

ACTIVE INGREDIENTS:

Pentachlorophenol*	8.96%
Other chlorophenols and related products*	1.04%
Coal Tar Creosote Oil	35.00% ~
Sodium Fluoride	40.00%
Potassium Bichromate	3.00%-
INERT INGREDIENTS:	12.00%
.OTAL	100 00%

*Equivalent to 10.42 % Technical Pentachlorophenol as defined by Federal Specification TT.W.570

DANGER: KEEP OUT OF REACH OF CHILDREN

See side panel for additional warning and antidote statements

NET 60 POUNDS

DIRECTIONS FOR USE

Stir well until entire contents have the same consistency. Before treating poles, all decayed wood should be removed. By means of a brush, trowel or other suitable device, apply a coating approximately 1/2-inch thick and over an area 18 inches to 24 inches wide. Usually not over 2 to 6 inches of the treatment extends above the ground line. When treatment is applied below ground line, that portion should be wrapped with suitable plastic coated paper. Covering all of the treatment with such paper is a recommended practice.

DANGER

May be fatal if swallowed. In case of swallowing take an emetic to induce vomiting — CALL A PHYSICIAN. Do not breathe vapors. Do not get in eyes, on skin or on clothing. Harmful if absorbed through skin. Causes skin irritation. If contacts skin, wash thoroughly. Keep away from children. Must not be used near foodstuffs, pets or livestock. In handling, hands and arms should be protected with neoprene rubber gloves. Wash hands and arms with soap and warm water frequently. Do not contaminate feed and foodstuffs.

This product is toxic to fish and wildlife. Animals and birds feeding in treated areas may be killed.

Do not contaminate water by cleaning equipment, or disposal of waste and containers.

Do not reuse empty drums. Return to drum reconditioner or destroy by perforating or crushing. Bury in a safe place.

Manufactured Expressly For

POLE TREATING COMPANY

Jenkintown, Penna.

EPA Reg. No. 6314-1

3-27-73

DIRECTIONS FOR USE

Stir well until entire contents have the same consistency. Before treating poles, all decayed wood should be removed. By means of a brush, trowel or other suitable device, apply a coating approximately 1/2-inch thick and over an area 18 nches to 24 inches wide. Usually not over 2 to 6 inches of the treatment extends above the ground line. When treatment is applied below ground line, that portion should be wrapped with suitable plastic coated paper. Covering all of the treatment with such paper is a recommended practice.

DANGER

The role of the work of the work of walls and the content of the c

This product is toxic to fish and wildlife. Animals and birds feeding in treated areas may be killed.

Denote our tarminate exactor in a real manerometric or a space of the vortex tarmers

Dispositiouse empty aronni. Retain in a line recondition in a restrict a proforation of creshing. Bury in a laster blace

Manufactured Expressly For

POLE TREATING COMPANY

Jenkintown, Penna.

EPA Reg No. 6314-1

3-27-73