POLEX is a ready-to-use penetrating preservative coating, designed for the groundline treatment of standing poles and for the treatment of the groundline area of poles in the yard that will be relocated or that have been in storage for prolonged periods. POLEX is also useful for the treatment of piling cutoffs.

Standing Poles: Use POLEX only on poles-in-line found by qualified inspector to be satisfactory for continued service. Dig a trench around the pole to the depth determined by the inspector to be necessary for the application of the preservative treatment. This may vary from 12 inches in wet areas to 18 inches or more in arid regions. Scrape away dirt and decayed wood from pole surface. Apply POLEX as a coating 1/8 to 1/4 inch in thickness, extending from the bottom of the trench to a predetermined height — from 2 inches to 12 inches above ground line to suit local conditions. Application may be by brush, paddle, scoop or mechanical applicator. Wrap the treated section with plastic coated kraft paper, stapling the paper to the pole. Alternately, POLEX may be applied to a suitable wrapping material, and this wrapper may then be stapled to the pole before backfilling the trenched area.

Piling Cut-Offs: Treat the cut-end with a coating 1/4 inch to 1/2 inch thick.

USDA Reg. No. 6314-2





Contains Penta, Creosote, and Sodium Borate. DANGER: (18 point) Keep Out of Reach of Children (12 point) See side panel for other warnings. **ACTIVE INGREDIENTS:**

Pentachlorophenol* Other Chlorophenols and Relate Coal Tar Creosote Aromatic Petroleum Hydrocarb Sodium Tetraborate (Anhydrou INERT INGREDIENTS:

10.8% Pentachlorophenol as defined in Federal Spec. TT-570 10,42%

MANUFACTURED EXPRESSLY FOR

FTED



TRADE MARK

PRESERVATIVE PASTE ---- T-B

	8.96%	811%
ed Compounds*	1.04%	1.8%
		15 %
bon	53.9.3%	
ıs Basis)		15%
	6.07%	/14 %
	•	

100 %



505 YORK ROAD . JENKINTOWN, PA.

ACCEPTED WITH COMMENTS

DISON PLAISTER HABISTER HABIST THE FEEL AT INCOME. DIRECTIONS FOR

(Continued)

Yard Poles: Poles that have been held in storage for a prolonged period or used poles to be relocated, may be treated in decay vulnerable zones in a manner similar to that described for standing poles, taking care to remove dirt and decayed wood before applying treatment.

WARNING

May be fatal if swallowed. In case of swallowing take an emetic to induce vomiting -CALL A PHYSICIAN. Do not breathe vapors or spray mist. Do not get in eyes, on skin or on clothing. Harmful if absorbed through skin. Causes skin irritation. Do not get on skin. In case of contact wash immediately with soap and water. Keep away from children, pets or livestock. Must not be used near foodstuffs. In handling, hands and arms should be protected with neoprene rubber gloves. Wash hands and arms with soap and warm water, frequently.

nor the saller makes any representation or warranty, express or implied,

This material is toxic to fish.

Do not contaminate waters by cleaning of equipment or disposal of waste.

Do not reuse container. Destroy by burying with waste.

 \sim

V



ACCEPTED WITH COMMENTS