

8030-282-0971

Oil-Soluble Wood Preservative Solution for Ship and Boat Use

MIL-W-18142B Amendment 3 Type A

Copper Naphthenate

One Gallon Can Batch _____

Date of Manufacture _____

CORONADO PAINT COMPANY, INC.

EDGEWATER, FLORIDA 32032

Federal Contract No. _____

Net Weight 6.8 lbs. SHELF LIFE 24 months

CAUTION! KEEP OUT OF THE REACH OF CHILDREN.
HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.
Read Cautions Elsewhere on Label CAREFULLY.
Do Not Reuse Container. Destroy When Empty.

ACTIVE INGREDIENT:

★ COPPER NAPHTHENATE** 22.0%

INERT INGREDIENTS:

MINERAL SPIRITS 78.0%

FLASH POINT 100°F (38°C)

**Contains 2.2% Copper as Metallic

EPA Reg. No. 6557-2

ACCEPTED

March 19, 1974

UNDER THE FEDERAL INSECTICIDE,
FUNGICIDE AND RODENTICIDE ACT
ECONOMIC POISON REGISTER
EPA REG. NO. 6557-2

CAUTION: FIRE HAZARD
have a flash point as low as 100°F
or other source of fire should be prevented
after 24 hours of drying, under conditions
vapors. Treating should be done in well-ventilated
vatives should be stored out of doors
from a fire hazard standpoint.

IRRITATING EFFECTS: Although
less irritating. Adequate ventilation
use of neoprene-coated gloves, and
helpful. Workmen should be instructed in
servative, and also to wash well with water
brushing or dipping, adequate ventilation
the solvent vapor.

FLAMMABLE: AVOID FIRE
HARMFUL IF SWALLOWED. AVOID
AVOID PROLONGED INHALATION
WELL VENTILATED ROOM. USE
RECOMMENDED. WASH WELL WITH
THIS MATERIAL.

This product is toxic to fish. Keep away from
cleaning of equipment or disposal.

INTENDED USE: This material is
compatible with subsequent gluing
that wood preservatives be allowed to
time is 24 hours for brush application
allowed to dry, the migration of unreacted
the satisfactory performance of gluing
to decay and should receive thorough cleaning
previously treated require retreatment
be covered when not in use to prevent