

CONTENTS ONE U. S. GALLON

**DIRECTIONS FOR USE**

**IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.**

**WATER DISINFECTION FOR FARM, INSTITUTION, CAMPS AND HOME WATER SUPPLIES** To disinfect water from unprotected supplies, such as wells, springs, and lakes, add 1/4 oz. Climaco SX-3 to each 100 gallons of water or 10 drops to each gallon and let it stand for 15 to 30 minutes. This is a strength of about 1 PPM available chlorine.

**AUTOMATIC CHLORINATORS** The use of Climaco SX-3 in the new automatic water supply chlorinators will insure non-clogging trouble free operation and absolutely uniform disinfection.

**FARM DAIRY UTENSILS** Just before using, rinse all utensils including can covers with a mixture of 1 oz. Climaco SX-3 to each 2 gallons of water. This solution contains 200 PPM available chlorine.

**MILK PLANT EQUIPMENT — FLOW METHOD** Mix 1 oz. Climaco SX-3 to each 4 gallons of water. This solution contains 100 PPM available chlorine. Pump the solution from weigh vat through to filler, draining solution through valves. A starting concentration of 100 PPM available chlorine can be used if testing facilities are available. test solution frequently with a chlorine test kit to prevent the concentration from falling below 50 PPM. If no test kit is available a starting concentration of 200 PPM is recommended. **SPRAY METHOD** Spray all surfaces with a mixture of 2 ozs. Climaco SX-3 to each 4 gallons of water. Solution contains 200 PPM available chlorine.

**CLEANED-IN-PLACE MILK LINES** Mix 1 oz. Climaco SX-3 to each 4 gallons of water, solution is 100 PPM available chlorine. Circulate for at least 5 minutes through properly cleaned lines before use. Use enough solution to completely fill all pipe lines in the system.

**climaco**

ACCEPTED  
6545-2

INDUSTRIAL-CHEMICALS

**SX-3**

**LIQUID-BACTERICIDE**

**DISINFECTANT and SANITIZER**

ACTIVE INGREDIENTS: SODIUM HYPOCHLORITE 5.25%  
INERT INGREDIENTS: 94.75%

**CAUTION**

**FIRST AID • EXTERNAL** Flush with water, then wash with vinegar. **EYES** Flush with water, call physician. **INTERNAL** Drink multiple glasses of water, milk or tea, grape-fruit juice, follow with emetic tablets, if not, mustard in a tumbler of warm water, call physician.

**KEEP OUT OF REACH OF CHILDREN**

SEE ADDITIONAL PRECAUTIONS ON BACK PANEL

G  
in  
fo  
R  
  
D  
P  
C  
a  
1  
es  
Ev  
of  
co  
ti  
  
A  
cl  
w  
Fo  
W  
w  
Fo  
ta  
15

ONE U. S. GALLON

# CLIMACO

INDUSTRIAL-CHEMICALS

# SX-3 BACTERICIDE

DISINFECTANT and SANITIZER

SODIUM HYPOCHLORITE 5.25%  
Available in 5 and 94.75%.

**EXTERNAL** — Flood with water, then wash with  
Flood with water. Call physician. **INTERNAL**  
Use raw egg-white, milk or fine gruel, follow with  
1 tsp. of mustard in a tumbler of warm water.

**KEEP OUT OF REACH OF CHILDREN**

PRECAUTIONS ON BACK PANEL

### RESTAURANTS AND TAVERNS

**GLASSES, DISHES AND BEER MUGS** — Wash, then immerse in a mixture of 1 oz. Climaco SX-3 to each 2 gallons of water for 2 minutes. Solution contains 200 PPM available chlorine. Remove from the solution and drain dry.

### SWIMMING POOLS

**DISINFECTION, ALGAE CONTROL** — For newly filled private pools without chlorinating device — add 10 ozs. (1 1/4 cups) Climaco SX-3 per each 10,000 gallons of water to provide a 0.4 parts per million and continue adding increments of 1 oz. until a chlorine residual of 0.6 to 1.0 PPM has been established as determined by the use of a chlorine test kit. Every 1-2 weeks, a super chlorination dosage of 10 fluid ozs. of Climaco SX-3 per 1,000 gallons should be applied to control growth of algae. Maintain this chlorine level at all times.

### FOR LAUNDERING, BLEACHING AND SANITIZING WHITE AND COLORFAST COTTON AND LINEN

Add 1 cup Climaco SX-3 with detergent before immersing clothes. Front Loading Machines . . . add Climaco SX-3 to water, pour in at wash cycle.

For Removing Stains . . . Remove starch by soaking in cold water. Add 2 tablespoons Climaco SX-3 to each quart of water. Soak 10-15 minutes. Rinse. Repeat if necessary.

For brightening Nylon, Rayon, Dacron, Orlon, etc.: Add 2 tablespoons Climaco SX-3 to one gallon warm water. Soak 15 minutes. Rinse. Repeat if necessary.

### IMPORTANT

All utensils or equipment must be clean in order for this bactericide to be completely effective.

### CAUTION

**KEEP OUT OF REACH OF CHILDREN**

**MAY BE HARMFUL IF SWALLOWED. SKIN AND EYE CONTACT MAY CAUSE SEVERE IRRITATION. AVOID CONTACT WITH SKIN AND EYES. IN CASE OF CONTACT FLUSH WITH PLENTY OF WATER. DO NOT USE AMMONIA OR BOWL CLEANERS WITH THIS PRODUCT TO DO SO WILL RELEASE HAZARDOUS GASES.**

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

**CONTAINER DISPOSAL — DO NOT REUSE EMPTY CONTAINER. RINSE CONTAINER THOROUGHLY WITH WATER AND DISCARD IN SAFE PLACE.**

**KEEP UPRIGHT IN COOL PLACE — TIGHTLY CAPPED**

**CLIMACO CORPORATION  
CANTON, OHIO 44707**

EPA Reg. No. 6545-2

EPA Est. No. 1155-IL-1