

coronado paint * coronado paint *

Super Kote



ACCEPTED
JUL 13 1981
Under the Federal Insecticide, Fungicide, and Rodenticide Act, this product is registered under EPA Reg. No. _____

RESERVATIVE SOLUTION

111-193 COPPER NAPHTHENATE

32

WARNING! KEEP OUT OF THE REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN.

Read Precautionary Statements Elsewhere on Label CAREFULLY

STORAGE AND DISPOSAL: Do Not Reuse Empty Container. Destroy When Empty.

coronado paint x coronado paint x coronado

Kote

**LUBLE
SERVATIVE
TION**

NAPHTHENATE

32
 ACH OF CHILDREN. HARMFUL OR FATAL
 ABSORBED THROUGH SKIN.
 ents Elsewhere on Label CAREFULLY
 Reuse Empty Container. Destroy When Empty.

AT THE POINT OF USE...
 INERT INGREDIENTS...
 201
 1960

NET WEIGHT 6.8 LBS./GAL.

PRECAUTIONARY STATEMENTS - Hazards to Humans and

HARMFUL IF SWALLOWED. AVOID SKIN CONTACT OR IN Prolonged Inhalation of Fumes. Work Area Should be Well Ventilated. Use of Goggles and Protective Clothing Recommended. Wash Well with Soap and Water After Using.
IRRITATING EFFECTS: Although workmen vary in sensitivity to the solvent, it is irritating. Adequate ventilation and other protective measures should be used. Wear neoprene coated gloves, aprons coated with butyral resin, and protective clothing. Workmen should be instructed to avoid the use of clothing soiled with the solvent. Wash well with soap and water after contact with the solution. Adequate ventilation should be maintained to reduce the concentration of solvent vapors.
FLAMMABLE - AVOID FIRE HAZARD.
STATEMENT OF PRACTICAL TREATMENT: If swallowed, do not induce vomiting. Get medical attention. In case of eye contact, flush immediately with water and get medical attention.

PHYSICAL OR CHEMICAL HAZARD:
WARNING FIRE HAZARD: The solvent or thinner used in this product has a flash point as low as 100 degrees F. Care should be taken to prevent a source of fire should be permitted near the treating operation or during drying under conditions of adequate ventilation to insure re-ventilation should be done out of doors or in an adequately ventilated room. Do not use or store near heat or open flame.

ENVIRONMENTAL HAZARD:
 This product is toxic to fish. Keep out of lakes, streams or ponds. Clean up spillage. Cleaning of equipment or disposal of wastes. Apply this product only to wood.

DIRECTIONS FOR USE: This material is intended for use in preparation of wood preservatives. It is compatible with subsequent gluing, caulking and painting operations. Wood preservatives be allowed to dry before such operations. Allow to dry for 24 hours for brush application and 72 hours for a 3-minute spray application. To dry, the migration of unevaporated solvent will discolor paint. Factory performance of glues and caulks. End grain surfaces are especially susceptible. Should receive thorough treatment. Cut, bored, or sanded surfaces require retreatment if protection is to be assured. Vats of preservative should be covered to prevent solvent evaporation. It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FLASH POINT 100 degrees F (38 degrees C)

33


coronado paint co.
 IN EDGEWATER, FLORIDA, U.S.A.

Coronado paint

PRECAUTIONARY STATEMENTS - Hazards to Humans and Domestic Animals - WARNING

HARMFUL IF SWALLOWED. AVOID SKIN CONTACT OR INTRODUCTION INTO EYES. AVOID PROLONGED INHALATION OF FUMES. WORK AREA SHOULD BE OUTDOORS OR WELL VENTILATED ROOM. USE OF GOGGLES AND PROTECTIVE CLOTHING IS RECOMMENDED. WASH WELL WITH SOAP AND WATER AFTER USING OR HANDLING THIS MATERIAL. IRRITATING EFFECTS. Although workmen vary in sensitivity, wood preservatives are more or less irritating. Adequate ventilation and other protective measures should be provided. The use of neoprene coated gloves, aprons coated with butyral resin, and protective ointments are helpful. Workmen should be instructed to avoid the use of clothing soiled with wood preservative, and also to wash well with soap and water after contact with the solution. When brushing or dipping, adequate ventilation should be maintained to reduce the concentration of the solvent vapor.

FLAMMABLE - AVOID FIRE HAZARD

STATEMENT OF PRACTICAL TREATMENT: If swallowed, do not induce vomiting. Get immediate medical attention. In case of eye contact, flush immediately with plenty of water for 15 minutes and get medical attention.

PHYSICAL OR CHEMICAL HAZARDS

WARNING - FIRE HAZARD: The solvent or thinner used in this wood preservative may have a flash point as low as 100 degrees F. Care should be taken to prevent fire. No smoking, welding, or other source of fire should be permitted near the treating operation or treated material until after 24 hours of drying under conditions of adequate ventilation to insure removal of flammable vapors. Treating should be done out of doors or in an adequately ventilated room. The preservatives should be stored out of doors or in a "paint" room where adequate precautions are taken from a fire hazard standpoint. Do not use or store near heat or open flame.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

DIRECTIONS FOR USE: This material is intended for use in preventing the decay of wood, and to be compatible with subsequent gluing, caulking and painting operations. However, it is necessary that wood preservatives be allowed to dry before such operations are attempted. The usual drying time is 24 hours for brush application and 72 hours for a 3-minute dip. If the preservative is not allowed to dry, the migration of unevaporated solvent will discolor painted surfaces and prevent the satisfactory performance of glues and caulks. End grain surfaces are particularly susceptible to decay and should receive thorough treatment. Cut, bored, or sanded surfaces which have been previously treated require retreatment if protection is to be assured. Vats of preservative should be covered when not in use to prevent solvent evaporation. It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

FLASH POINT 100 degrees F (38 degrees C)

EPA Reg. No. 6557-2

Net Weight



coronado paint company

IN EDGEWATER, FLORIDA, U.S.A.

33

34

NET WEIGHT 6.8 LBS./GAL.