 <p>U.S. ENVIRONMENTAL PROTECTION AGENCY Office of Pesticide Programs Registration Division (H7505C) 401 "M" St., S.W. Washington, D.C. 20460</p> <p>NOTICE OF PESTICIDE: <u> X </u> Registration <u> </u> Reregistration</p> <p>(under FIFRA, as amended)</p>	<p>EPA Reg. Number: 6557-17</p>	<p>Date of Issuance: AUG - 4 1999</p>
	<p>Term of Issuance: Until Reregistration</p>	
	<p>Name of Pesticide Product: Coronado Exterior Preservative Wood Stain</p>	
<p>Name and Address of Registrant (include ZIP Code):</p> <p>Coronado Paint Company 308 Old County Road Edgewater, FL 32132</p>		
<p>Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.</p>		
<p>On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistration under the Federal Insecticide, Fungicide and Rodenticide Act.</p> <p>Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA sec. 3(c) (7) (A) provided that you:</p> <ol style="list-style-type: none"> 1. Submit and/or cite all data or other material required for registration/reregistration of your product under FIFRA sec. 3(c) (5) or FIFRA sec. 4 when the Agency requires all registrants of similar products to submit such data. 2. Make the labeling changes listed below before you release the product for shipment: 		
<p>Signature of Approving Official: Adam Heyward, Product Manager (34) Regulatory Management Branch II Antimicrobials Division (7510W)</p>	<p>Date: AUG - 4 1999</p>	

a. Add the phrase, "EPA Registration No. 6557-17".

b. Add the the following statement the under the heading HAZARDS TO HUMANS AND DOMESTIC ANIMALS:

Harmful if inhaled. Avoid breathing spray mist, vapor, or dust. While spraying, sanding, or blasting, wear a mask or pesticide respirator approved by the National Institute for Occupational Safety and Health. Remove contaminated clothing and wash clothing before reuse.

c. Add the following statement under the FIRST AID:

IF INHALED: Remove victim to fresh air. If not breathing, give artificial respiration, preferable mouth-to-mouth, Get medical attention.


d. Delete the statement "WATER REPELLENT EXCEEDS FEDERAL SPEC. TT-W-572 B, 3.7" or you must provide a statement from a Federal Agency certifying that this product exceeds Federal SPEC. TT-W-572 B, 3.7.

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Adam Heyward
Product Manager 34
Regulatory Management Branch II
Antimicrobials Division (7510W)

Enclosure

FRONT PANEL

CORONADO

(LOGO)

CORONADO

NORDIK
EXTERIOR PRESERVATIVE
WOOD STAIN

92-1927 Clear (Tint Base)

SIDE PANEL

WATER REPELLENT
EXCEEDS FEDERAL SPEC.
TT-W-572 B, 3.7

EPA Reg. No. _____
EPA Est. No. 06557-FL-01

Ingredient Statement

Active Ingredient:

Folpet, N-(Trichloromethylthio) Phthalimide	.75%
Distannozane, hexabutyl, [Bis (tributyltin) Oxide]	.81%
Inert Ingredients	98.44%
	100.00%

Contains Petroleum Distillate

Weight per gallon 7.08 ± 0.20 lbs.

KEEP OUT OF REACH OF CHILDREN.

CAUTION!
COMBUSTIBLE (FLASH POINT 104° F)
SEE BACK PANEL FOR
ADDITIONAL PRECAUTIONARY STATEMENTS.

ONE GALLON
3.785 LITERS

ACCEPTED
with COMMENTS
in EPA Letter Dated:
AUG - 4 1999

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
this product is hereby
registered under EPA Reg. No. **6557-17**

406

BACK PANEL

NORDIK STAIN BASE

Penetrating Wood Preservative

Repels Moisture - Retards Dry Rot - Reduces Warping

Penetrates Deeply - Natural Appearance

Directions for use.

NOTE: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

PRODUCT DESCRIPTION:

Nordic Exterior Preservative Stain Base may be used either as a clear wood preservative or when tinted, as a semi-transparent stain that allows natural wood grain and texture to show through beautifully. Nordik Preservative protects the natural wood fibers and repels damaging moisture. When tinted into a stain, Nordik screens out harmful ultra-violet light, which can damage wood integrity and cause graying.

WHERE TO APPLY:

Use for exterior applications, only. Can be applied to new or unsealed wood surfaces, such as siding, shakes, shingles, decks or fencing. Nordik Preservative is not intended for below grade use or on structural members. Do not use on abraded plywood. Smooth planed clapboard or siding must be sanded thoroughly to break the "mill glaze" to allow proper adhesion. Avoid contact with skin and food products.

SURFACE PREPARATION:

Surface to be coated must be clean and dry. All dirt, dust, mildew or any other contaminant must be removed. If mildew is present, remove it by washing with a solution of one part liquid bleach and three parts water followed by a thorough clean water rinse. Allow surface to dry. Do not prime. Nordik Preservative Stain is self-priming. Do not apply to surfaces that were previously painted, as the stain cannot penetrate.

APPLICATION:

Mix thoroughly before and during application. Nordik Preservative Stain may be applied by brush, roller, spray, dipping or pad at up to 250 square feet per gallon. Surface porosity and texture will dictate actual rate. The final color will vary depending on the type of wood, its grain, color and texture. Stain a test panel to determine actual finished appearance. Apply stain liberally; the more stain absorbed into the wood, the greater the protection. Always maintain a wet edge during application, to avoid lap marks. Prior to staining, ensure having enough stain boxed or mixed in one container

to complete an entire section. Thinning is normally not recommended. If needed, use mineral spirits. Stain when temperatures are between 50° F and 100° F. Do not apply if
BACK PANEL-Page 2

rain is threatening. Do not apply in direct, hot sunlight. This product may injure plants if spilled or dripped.

SPREAD RATE:

Up to 250 square feet per gallon, per coat, depending on wood texture and porosity.

DRY TIME

Dries to touch in 2 to 4 hours. May be recoated in 8 to 12 hours. Allow 24 hours before using the surface for walking, such as on decks and patios.

CLEAN UP:

Clean application tools with mineral spirits.

MILDEW:

Mildew is a natural phenomenon over which we have no control and although every effort is made to make this coating mildew resistant we cannot assume responsibility for the formation of this fungus on the paint film.

LIMITED WARRANTY:

We guarantee your satisfaction with this product when applied according to label instructions. If not satisfied with performance, return the unused portion with your receipt to the place of purchase. You will either receive replacement material or a refund of the original purchase price. This limited warranty does not include the cost of labor. This warranty gives you specific legal rights, and you may also have other rights which vary from state to state.

CAUTION!

Precautionary statements - Hazards to humans and domestic animals.

Caution: Keep out of reach of children. Causes moderate eye irritation. Avoid breathing vapor. Harmful if adsorbed through the skin or swallowed. Use only in well ventilated areas. Do not use or store near heat or open flame. Avoid contact with eyes, skin or clothing! Wear rubber gloves and protective clothing when applying or handling freshly treated lumber. Wash thoroughly with soap and water after handling. Treated wood should not be used where it can come into contact with food, feed, livestock, or potable water.

FIRST AID: If on skin, remove excess with clean dry cloths and then wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse. **IF IN EYES:** Hold eyelids open and flush with plenty of water. Get medical attention if irritation persist. If swallowed, do not induce vomiting. Drink promptly a large quantity

of milk, egg whites, or gelatin solution. If these are not available, drink large quantities of water. Call a physician.

BACK PANEL - Page 3

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL AND CHEMICAL HAZARDS: Avoid storage near feed or food products. Do not use or store inside the home. Do not use or store near heat or open flame.

This product contains a maximum of 4.97 pounds VOC/VOS per gallon of coating.

STORAGE AND DISPOSAL INSTRUCTIONS:

Do not reuse empty container. Wrap empty container and put in trash collection. Store in well ventilated area at temperatures not in excess of 90° F

Manufactured by

CORONADO PAINT COMPANY

308 Old County Road
Edgewater, FL 32132



7451 FM 3009
Schertz, TX 78154