

DIRECTIONS FOR USE

**SAP STAIN AND MOLD CONTROL
IN LUMBER**

For lumber 2 inches or less in thickness immerse completely in a solution of 5 pounds of SONTOX-S in 100 U.S. gallons of water. For thicker lumber use a solution of 10 pounds of SONTOX-S in 100 U.S. gallons of water. Protect from rain until the surface is dry and stack according to best drying practice. Lumber should be treated as soon as possible after sawing. Spraying can also be used for application.

**SAP STAIN AND MOLD CONTROL IN POLES,
POSTS, AND TIMBERS**

Dissolve 10 pounds of SONTOX-S in 100 gallons of water and dip or spray in solution until all surfaces are wetted.

E.P.A. REGISTRATION NO. 6651-15

**CONTROLS SAP STAIN AND MOLD
IN LUMBER, POLES, AND LOGS**

**WARNING
KEEP OUT OF REACH
OF CHILDREN**

Causes skin irritation. Harmful if swallowed. Do not breathe dust or spray mist. Do not get in eyes, on skin or clothing. Wash thoroughly with ample quantities of water after skin contact. Do not take internally. In case of accidental swallowing induce vomiting by administering warm salt water or emetic. Do not contaminate feed or foodstuffs. Do not use on products that will be used in contact with food, feed, or contacted by children.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not re-use empty drums. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

ACTIVE INGREDIENTS:

Sodium Pentachlorophenate	79%
Sodium salts of other chlorophenols	11%
INERT INGREDIENTS	10%
Total	100%

DIRECTIONS FOR USE

SAP STAIN AND MOLD CONTROL IN LOGS

Spray the ends and barkless areas of the freshly cut logs with a solution of 10 pounds of SONTOX-S in 100 gallons of water. Warm water will dissolve SONTOX-S faster.

NOTE

BUYER ASSUMES ALL RISKS OF USE, STORAGE OR HANDLING IF THIS MATERIAL NOT IN STRICT ACCORDANCE WITH DIRECTIONS GIVEN HEREWITH.

NET WEIGHT _____ LBS.

April 5, 1973

A PRODUCT OF

SONFORD PRODUCTS CORPORATION



DIRECTIONS FOR USE

**SAP STAIN AND MOLD CONTROL
IN LUMBER**

For lumber 2 inches or less in thickness immerse completely in a solution of 5 pounds of SONTOX-S in 100 U.S. gallons of water. For thicker lumber use a solution of 10 pounds of SONTOX-S in 100 U.S. gallons of water. Protect from rain until the surface is dry and stack according to best drying practice. Lumber should be treated as soon as possible after sawing. Spraying can also be used for application.

**SAP STAIN AND MOLD CONTROL IN POLES,
POSTS, AND TIMBERS**

Dissolve 10 pounds of SONTOX-S in 100 gallons of water and dip or spray in solution until all surfaces are wetted.

E.P.A. REGISTRATION NO. 6651-15

**CONTROLS SAP STAIN AND MOLD
IN LUMBER, POLES, AND LOGS**

**WARNING
KEEP OUT OF REACH
OF CHILDREN**

Causes skin irritation. Harmful if swallowed. Do not breathe dust or spray mist. Do not get in eyes, on skin or clothing. Wash thoroughly with ample quantities of water after skin contact. Do not take internally. In case of accidental swallowing induce vomiting by administering warm salt water or emetic. Do not contaminate feed or foodstuffs. Do not use on products that will be used in contact with food, feed, or contacted by children.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not re-use empty drums. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

ACTIVE INGREDIENTS:

Sodium Pentachlorophenate	79%
Sodium salts of other chlorophenols	11%
INERT INGREDIENTS	10%

Total	100%
-------	------

DIRECTIONS FOR USE

SAP STAIN AND MOLD CONTROL IN LOGS

Spray the ends and barkless areas of the freshly cut logs with a solution of 10 pounds of SONTOX-S in 100 gallons of water. Warm water will dissolve SONTOX-S faster.

NOTE

BUYER ASSUMES ALL RISKS OF USE, STORAGE OR HANDLING IF THIS MATERIAL NOT IN STRICT ACCORDANCE WITH DIRECTIONS GIVEN HEREWITH.

NET WEIGHT _____ LBS.

A PRODUCT OF

SONFORD PRODUCTS CORPORATION

SONFORD