

DIRECTIONS

LUMBER: For lumber 2 inches or less in thickness, dissolve 10 lbs of SP-60 in 100 U. S. gallons of water. The freshly cut lumber should then be dipped or sprayed in this solution until complete surface wetting is accomplished.

POLES, POSTS & TIMBERS. Dissolve 20 lbs. of SP-60 in 100 gallons of water and dip or spray in solution until all surfaces are wetted.

It is desirable that the logs be bright and free from infection at the time they are converted into lumber. For best protection during warm weather lumber should be dipped the day it is sawed, or at least, the following day. SP-60 should be thoroughly dissolved in a mixing tank of known capacity, such as a barrel, prior to being run into the dipping vat. The dipping vat should be protected from the rain to prevent dilution of the treating solution.

Treated lumber should not be exposed to heavy rains immediately after dipping. Lumber piles should be as narrow as practical, properly elevated, well spaced, and adequately roofed.

CONTROLS SAP STAIN AND MOLD IN FRESHLY CUT SOFTWOOD AND HARDWOOD LUMBER, LOGS, POLES, POSTS AND TIMBERS

ACTIVE INGREDIENTS:	
Sodium Pentachlorophenate	47.0%*
Sodium Salts of other chlorinated phenols	7.0%*
Sodium tetraborate decahydrate	38.0%
INERT INGREDIENTS	
	8.0%
Total	100.00%

*Equivalent to 60% technical sodium pentachlorophenate

WARNING KEEP OUT OF REACH OF CHILDREN

Causes skin irritation. Harmful or fatal if swallowed. Do not breathe dust. Do not get in eyes, on skin or clothing. Wash thoroughly after handling. Do not take internally. In case of swallowing induce vomiting by administering warm salt water or emetic. Do not contaminate feed or foodstuffs. Do not use on products that will be used in contact with food or feed, or contacted by children.

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

Wear rubber gloves and protective clothing when handling the freshly treated lumber.

LOGS. Spray the ends and barkless areas of the freshly cut logs with a solution of 20 lbs. of SP-60 in 100 gallons of water.

NOTE

BUYER ASSUMES ALL RISKS OF USE, STORAGE OR HANDLING OF THIS MATERIAL NOT IN STRICT ACCORDANCE WITH DIRECTIONS GIVEN HEREWITH.

E.P.A. Registration No. 6651-20

Net WEIGHT _____ LBS.

A PRODUCT OF

SONFORD PRODUCTS CORPORATION

SONFORD

DIRECTIONS

LUMBER: For lumber 2 inches or less in thickness, dissolve 10 lbs of SP-60 in 100 U. S. gallons of water. The freshly cut lumber should then be dipped or sprayed in this solution until complete surface wetting is accomplished.

POLES, POSTS & TIMBERS. Dissolve 20 lbs. of SP-60 in 100 gallons of water and dip or spray in solution until all surfaces are wetted.

It is desirable that the logs be bright and free from infection at the time they are converted into lumber. For best protection during warm weather lumber should be dipped the day it is sawed, or at least, the following day. SP-60 should be thoroughly dissolved in a mixing tank of known capacity, such as a barrel, prior to being run into the dipping vat. The dipping vat should be protected from the rain to prevent dilution of the treating solution.

The wet lumber should not be exposed to heavy rains immediately after dipping. Lumber piles should be as narrow as practical, properly elevated, well spaced, and adequately roofed.

CONTROLS SAP STAIN AND MOLD IN FRESHLY CUT SOFTWOOD AND HARDWOOD LUMBER, LOGS, POLES, POSTS AND TIMBERS

ACTIVE INGREDIENTS:

Sodium Pentachlorophenate	47.00%
Sodium Salts of other chlorinated phenols	7.00%
Sodium tetraborate decahydrate	38.00%
INERT INGREDIENTS	8.00%

Total 100.00%

Equivalent to 60% technical sodium pentachlorophenate

WARNING KEEP OUT OF REACH OF CHILDREN

Causes skin irritation. Harmful or fatal if swallowed. Do not breathe dust. Do not get in eyes, on skin or clothing. Wash thoroughly after handling. Do not take internally. In case of swallowing induce vomiting by administering warm salt water or emetic. Do not contaminate soil or foodstuffs. Do not use on products that will be used in contact with food or feed, or contacted with them.

This product is toxic to fish and wildlife. Keep out of lakes, streams, rivers. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

Do not reuse empty drums. Return to drum reconditioner or destroyer by crushing or crushing and burying in a safe place.

Wear proper gloves and protective clothing when handling the freshly treated lumber.

LOGS. Spray the ends and barkless areas of the freshly cut logs with a solution of 20 lbs. of SP-60 in 100 gallons of water.

NOTE

BUYER ASSUMES ALL RISKS OF USE, STORAGE OR HANDLING OF THIS MATERIAL NOT IN STRICT ACCORDANCE WITH DIRECTIONS GIVEN HEREWITH.

E.P.A. Registration No. 6651-20

Net WEIGHT _____ LBS.

A PRODUCT OF

SONFORD PRODUCTS CORPORATION

SONFORD