

ACTIVE INGREDIENT: 2-(thiocyanomethylthio)benzothiazole INERT INGREDIENTS 70%

STA-BRITE LIQUID CONCENTRATE is intended for use as a control of "Sap Stain and Mold" in freshly cut softwood and hardwood lumber and timbers.

DIRECTIONS

LUMBER. For lumber 2 inches or less in thickness, disperse 2.0 to 3.0 lb. (2 to 3 pints) of **STA-BRITE LIQUID CONCENTRATE** in 100 U. 5. gallons of water. The freshly cut lumber should then be dipped or sprayed in this dispersion until complete surface wetting is accomplished.

TIMBERS. For timbers and lumber over 2 inches in thickness, disperse 4.0 to 6.0 lb. (4 to 6 pints) of **STA-BRITE LIQUID CONCENTRATE** in 100 U. S. gallons of water and dip or spray in dispersion until all surfaces are wetted.

GENERAL. It is desirable that the logs be bright and free from infection at the time they are converted into lumber. For best protection during warm weather lumber should be dipped the day it is sawed, or at least, the following day. **STA-BRITE LIQUID CON-CENTRATE** should be thoroughly disperred in water in a mixing tank of known capacity, such as a barrel, prior to being run into the dipping vat. The dipping vat should be protected from the rain to prevent dilution of the treating dispersion.

Treated lumber and timbers should not be exposed to heavy rains immediately after dipping. Lumber piles should be as narrow as practical, properly elevated, well spaced, and adequately roofed.

- WARNING - KEEP OUT OF REACH OF CHILDREN

Harmful if swallowed. If swallowed, call c physician immediately. Give patient doses of powered charcoal immediately or all he can swallow of raw egg whites, milk, gruel, or flour and water. Then induce vomiting with salt, soap, or mustard in warm water. May be harmful if absorbed through the skin. Workmen handling the product should wear rubber gloves and goggles and should avoid contact of the product with clothing or skin. After exposure, wash promptly and thoroughly with

•



ACTIVE INGREDIENT:

STA-BRITE LIQUID CONCENTRATE is intended for use as a control of "Sap Stain and Mold" in freshly cut softwood and hardwood lumber and timbers.

DIRECTIONS

LUMBER. For lumber 2 inches or less in thickness, disperse 2.0 to 3.0 lb. (2 to 3 pints) of STA-BRITE LIQUID CONCENTRATE in 100 U.S. gallons of water. The freshly cut lumber should then be dipped or sprayed in this dispersion until complete surface wetting is accomplished.

TIMBERS. For timbers and lumber over 2 inches in thickness, disperse 4.0 to 6.0 lb. (4 to 6 pints) of STA-BRITE LIQUID CONCENTRATE in 100 U.S. gallons of water and dip or spray in dispersion until all surfaces are wetted.

GENERAL. It is desirable that the logs be bright and free from infection at the time they are converted into lumber. For best protection during warm weather lumber should be dipped the day it is sawed, or at least, the following day. STA-BRITE LIQUID CON-**CENTRATE** should be thoroughly dispersed in water in a mixing tank of known capacity, such as a barrel, prior to being run into the dipping vat. The dipping vat should be protected from the rain to prevent dilution of the treating dispersion.

Treated lumber and timbers should not be exposed to heavy rains immediately after dipping. Lumber piles should be as narrow as practical, properly elevated, well spaced, and adequately roofed.

- WARNING -**KEEP OUT OF REACH OF CHILDREN**

Harmful if swallowed. If swallowed, call a physician immediately. Give patient doses of powered charcoal immediately or all he can swallow of raw egg whites, milk, gruel, or flour and water. They induce vomiting with salt, soap, or mustard in warm water. May be harmful if absorbed through the skin. Workmen handling the product should wear rubber gloves and goggles and should avoid contact of the product with clothing or skin. After exposure, wash promptly and thoroughly with an abrasive soap and cool water and finally with glycerin. In case of persistent irritation of the skin, obtain medical attention. If the product gets into the eyes, it causes eye damage; therefore, flood eyes immediately and thoroughly with cool water for 15 to 30 minutes. See a physician if any irritation persists. Keep the drum closed when not in use.

This product is toxic to fish. Keep out of lakes, streams, or ponds. Do not contaminate water by cleaning of equipment, or disposal of wastes, and apply this product only as specified on this label.

Do not reuse container. Destroy when empty or return to drum reconditioner.

BUYER ASSUMES ALL RISKS OF 'JSE, STORAGE OR HANDLING IT THIS MA TERIAL IS NOT USED IN STRICT ACCORDANCE WITH DIRECTIONS GIVEN HERE-WITH.

A Product of SONFORD PRODUCTS CORPORATION SOUTHERN DIVISION P. O. Box 5570 Jackson, Mississippi 39208

E.P.A. Reg. No. 6651-27

E.P.A. Est. No. 6651-MS-1