

1284

11.3

6651-33

For sale to and use only by certified applicators or by persons under their direct supervision and only for those uses covered by the certified applicator's certification.

The U.S. EPA has determined that pentachlorophenol can produce defects in the offspring of laboratory animals. Exposure to pentachlorophenol during pregnancy should be avoided.

PENTA-TOX DP

A 5% PENTACHLOROPHENOL SOLUTION
FOR WOOD PRESERVATION
AND WATER REPELLENT INGREDIENTS
FOR DIMENSION PROTECTION*

ACCEPTED
JUL 17 1985
Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, for the pesticide registered under EPA Reg. No. 6651-33

ACTIVE INGREDIENTS:	
Pentachlorophenol	4.5%*
Other Chlorophenols and related compounds	53%
INERT INGREDIENTS:	94.97%

*Equiv. to 5.3% Technical Pentachlorophenol

Keep Out of Reach of Children

(12 pt)

DANGER

(18 pt)

Statement of Practical Treatment

For Eyes: In case of contact with eyes, flush with plenty of water for at least 15 minutes. Call a physician.

For Skin: Wash exposed areas of skin with soap and water after handling or using.

If Swallowed: Do not induce vomiting. Call a physician immediately.

Note: Remove and wash contaminated clothing before reuse or discard in accordance with instructions for pesticide container disposal.

See Side Panel for Additional Precautionary Statements

EPA Reg. No. 6651-33

EPA Est. No. 6651-19-1

NET CONTENTS

Sonford Products Corp.
Jackson, MS

AVAILABLE COPY

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS

DANGER

(18 pt)

Corrosive. Causes eye damage and skin irritation. Do not get in eyes, on skin or on clothing. Harmful or fatal if swallowed.

Applicators must wear gloves impervious to this wood treatment formulation in all situations where dermal contact is expected. (For example, during the actual application process and when handling freshly treated wood)

Spray applicators must wear protective clothing (including overalls, jackets, gloves and boots) impervious to this wood treatment formulation, and a respirator, head covering and goggles when spraying.

Applicators who apply pentachlorophenol by other application methods (e.g., brush-on) must wear disposable coveralls or other suitable impermeable protective clothing. Launder non-disposable protective clothing separately from other clothing.

Applicators must not eat, drink, or use tobacco products during those parts of the application process that may expose them to this wood treatment formulation.

Avoid inhaling vapors. If inhalation of vapors cannot be avoided, applicators must wear a properly fitting, well-maintained half-mask canister or cartridge respirator which is MSHA/NIOSH approved for organic vapors and acid gases.

Wash thoroughly after skin contact, and before eating, drinking, use of tobacco products, or using restrooms.

ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not use this product to treat wood intended to be used where it may come into direct or indirect contact with public drinking water, or drinking water for domestic animals or livestock, except for those uses involving incidental contact such as docks and bridges.

PHYSICAL AND CHEMICAL HAZARDS

Contains petroleum distillate. Do not use, pour, spill or store near heat and open flame.

Notes on Handling: Because this product contains petroleum distillate, proper precaution should be taken to insure adequate ventilation. It should not be applied in the presence of open flames. Smoking during application should not be permitted in the area.

BEST AVAILABLE COPY

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

STORAGE AND DISPOSAL

(14 pt)

Securely wrap original pesticide container in several layers of newspaper and discard in trash. Do not reuse empty containers. Protective clothing must be changed when it shows signs of contamination. Dispose of worn-out protective clothing and work-shoes in any general landfill, in the trash, or in any other manner approved for pesticide disposal.

Wood which has been treated with this product should be disposed of by burial or ordinary trash collection. Do not burn treated wood in an outdoor fire or in stoves or fireplaces because toxic chemicals may be produced as part of the smoke and ashes.

Do not apply where there may be direct contact with domestic animals or livestock, and where there may be contamination of food, feed, or drinking and irrigation water.

Do not apply in interiors. Do not apply to wood intended for use in interiors except for those support structures which are in contact with soil in barns, stables, and similar sites and which are subject to decay or insect infestation, and millwork which has outdoor surfaces (e.g., door frames, windows and patio frames). Interior surfaces of the treated wood should be sealed with two coats of an appropriate sealer.

Do not use this product to treat wood intended to be used for cutting-boards or counter-tops.

Do not use this product to treat wood intended for construction of those portions of beehives which may come into contact with the honey.

Wood to be treated with this product should be cut to size before treatment. If it is necessary to saw or machine wood after treatment, wear goggles to protect the eyes from flying particles and a dust mask to avoid inhaling sawdust from the treated wood. If oily preservatives or sawdust accumulate on clothes, launder before reuse. Wash work clothing separately from other household laundry. Contact with treated surfaces should be avoided even after the preservative has dried.

This product should not be used to treat wood which will be in frequent or prolonged contact with skin, unless the wood will be treated with an effective sealer.

Note to User: As used on this label, the term "respirators" means properly fitting, well-maintained half-mask canisters or cartridge respirators which are MSHA/NIOSH-approved for organic vapors and acid gases. Examples of acceptable materials for protective clothing (e.g., overalls, jackets, head covering, boots, disposable coveralls, and gloves) required during application and handling of pentachlorophenol are polyvinylacetate (PVA), polyvinylchloride (PVC), neoprene, NBR (Buna-N), and nitrile. Urethane, shellac, latex epoxy enamel and varnish are acceptable sealers for pentachlorophenol-treated wood.

BEST AVAILABLE COPY

PENTA-TOX DP

protects wood against Powder-Post Beetles and Termites. Stops Rot, Stain and Decay. Checks Swelling, Shrinking, Warping, and Checking.

DIRECTIONS

For best results immerse wood to be treated in Penta-Tox DP for 3 minutes or longer. If dipping is not possible, apply 2 liberal brush or spray applications. Allow 1 hour between applications. Make certain all surfaces are treated. If treated wood is sawed or planed, re-treat newly exposed surfaces. Allow a minimum of 24 hours or longer after applying Penta-Tox DP.

Less paint is required over wood treated with Penta-Tox DP.

RECOMMENDED FOR USE ON:

All Unpainted Wood such as Joists, Sills, Plates, Door Casings, Doors, Window Frames, Windows, Stairs, Porches, Sub-Flooring, Interior Trim, Furring Strips, Wall Paneling, Arbors, Fence Rails, Fence Pickets, Seed Boxes, Cold Frames and Beverage Cases. Avoid spraying on plants not to be destroyed.

BEST AVAILABLE COPY