



SUBTERRANEAN TERMITES

Directions for Professional Use

Use 1 gallon of BHC E-11 in a .8% emulsion (add 1 gallon of BHC E-11 to 14 gallons of water) as follows.

PRECONSTRUCTION TREATMENT

Slab-on-Ground Construction

(1) Apply an over-all treatment under entire surface of floor slab. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is gravel or other coarse absorbent material, apply at the rate of 1½ gallons per 10 square feet.

(2) Under slab-on-ground porch floors and entrance platforms, apply an over-all treatment at the rate of 1 gallon per 10 square feet.

(3) Along both side of foundation wall, along interior foundation walls, and around plumbing dig a narrow trench to a depth of 1 foot, but not below the top of the footing. Apply at the rate of 2 gallons per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least **1 gallon per 5 linear feet** of wall. Apply the emulsion so as to reach the footing.

Buildings with Crawl Spaces

(1) Dig a narrow trench to the top of the footing along the **inside** of foundation walls, around piers, sewer pipes and conduits. Apply 2 gallons of emulsion per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(2) Dig a narrow trench to the top of the footing along the **outside** of the foundation wall. Apply 2 gallons of emulsion per 5 linear feet of trench per each foot of depth. A trench 3 feet deep would require 6 gallons per 5 linear feet. The chemical should be mixed with the soil as it is being replaced in the trench.

(3) Under attached porches, entrance platforms, utility entrances, and similar situations where slab or fill is at the same grade level, apply 1 gallon per 10 square feet of soil surface.

(4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

Buildings with Basements

(1) Apply an over-all treatment under the basement flooring, as well as under attached porches, entrance platforms, utility entrances, and similar situations where slab or fill is at the grade level. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.

(2) Dig a narrow trench to the top of the footing along the inside of foundation walls, around piers, sewer pipes and conduits. Apply 2 gallons of emulsion per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

(3) Along the outside of foundation walls, dig a narrow trench, such trench to be dug no deeper than the top of the footings. If the trench is less than 12 inches in depth to the top of the footings, apply **1 gallon per 5 linear feet**. Replace the soil and apply another **1 gallon per 5 linear feet** to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 12 inches in depth to the top of the footings, apply **2 gallons per 5 linear feet**. Replace the soil and apply another **2 gallons per 5 linear feet** to the back fill. Cover the back fill with a thin layer of soil. A trench of 30 inches deep is a maximum depth required alongside foundations where the top of the footing is greater than 40 inches deep. In the case of trenching to a 40 inch depth, make the trench 12 to 15 inches deep and rod to footing, spacing the holes about 1 foot apart.

(4) Treat all voids in hollow masonry units of the foundation at the rate of **1 gallon per 5 linear feet** of wall. Apply the emulsion so as to reach the footing.



BHC E-11

An Emulsifiable Concentrate Containing
1.0 lb. of Gamma Isomer per Gallon

ACTIVE INGREDIENTS:

Gamma Isomer of Benzene Hexachloride	11.9%
Other Isomers of Benzene Hexachloride	15.4%

INERT INGREDIENTS:	72.7%
--------------------------	-------

TOTAL	100.0%
-------------	--------

WARNING: KEEP OUT OF REACH OF CHILDREN

SEE SIDE PANEL FOR OTHER CAUTIONS

E.P.A. Registration Number 6720-161

E.P.A. Est. 6720-FL-1



MANUFACTURED BY
Southern MILL CREEK PRODUCTS COMPANY, Inc.
TAMPA, FLORIDA

11
aining
illon

..... 11.9%
..... 15.4%
..... 72.7%
..... 100.0%

I OF CHILDREN
ONS

E.P.A. Est. 6720-FL-1

OMPANY, Inc.

WARNING

This product is toxic to fish, birds and other wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

DO NOT reuse container

Destroy when empty

DO NOT USE, POUR, SPILL OR STORE NEAR HEAT OR OPEN FLAME.

WARNING

May be fatal if swallowed. Avoid contact with eyes. In case of contact with eyes flush with water and get medical attention.

May be absorbed through skin. Do not breathe spray mist. Avoid skin contact. In case of contact wash immediately with soap and water. Avoid contamination of feed and foodstuffs. DO NOT use on household pets or humans.

NOTICE: Seller's guaranty shall be limited to the terms of the label and subject thereto. The buyer assumes any risk to persons or property arising out of use or handling, and accepts the product on these conditions.