



LINDANE 1E

An Emulsifiable Concentrate Con
1 lb. of Lindane per Gallon

ACTIVE INGREDIENTS:

Lindane (Gamma Isomer of Benzene Hexachloride)	12.87%
Xylene Range Aromatic Solvent	82.45%
INERT INGREDIENTS:	4.68%
TOTAL	100.0%

CAUTION: KEEP OUT OF REACH OF CHILDREN

SEE SIDE PANEL FOR OTHER CAUTIONS

E.P.A. Registration Number 6720-161

E.P.A. Est. 6720 P-1

SUBTERRANEAN Directions for Professional Use

Use 1 gallon of Lindane 1E in a 8% emulsion (add 1 gallon of Lindane 1E to 14 gallons of water) as follows

PRECONSTRUCTION TREATMENT

Slab-on-Ground Construction

- (1) Apply an over-all treatment under entire surface of floor slab. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is gravel or other coarse absorbent material, apply at the rate of 1 gallon per 10 square feet.
- (2) Under slab-on-ground floors and entrance platforms, apply an over-all treatment at the rate of 1 gallon per 10 square feet.
- (3) Along down side of foundation wall, along interior foundation walls and around plumbing dig a narrow trench to a depth of 1 foot but not below the top of the footing. Apply at the rate of 2 gallons per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

Buildings with Crawl Spaces

- (1) Dig a narrow trench to the top of the footing along the inside of foundation walls, around piers sewer pipes and conduits. Apply 2 gallons of emulsion per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.
- (2) Dig a narrow trench to the top of the footing along the outside of the foundation wall. Apply 2 gallons of emulsion per 5 linear feet of trench per each foot of depth. A trench 3 feet deep would require 6 gallons per 5 linear feet. The chemical should be mixed with the soil as it is being replaced in the trench.
- (3) Under attached porches, entrance platforms, utility entrances, and similar situation where slab or fill is at the same grade level apply 1 gallon per 10 square feet of soil surface.

CAUTION

May be harmful if swallowed. Avoid contact with eyes. In case of contact with eyes flush with water and get medical attention.

May be absorbed through skin. Do not breathe spray mist. Avoid skin contact. In case of contact wash immediately with soap and water. Avoid contamination of feed and food-stuffs. DO NOT use on household pets or humans.

This product is toxic to fish, birds and other wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

NOTICE: Seller's guaranty shall be limited to the terms of the label and subject thereto. The buyer assumes any risk to persons or property arising out of use or handling, and accepts the product on these conditions.

NOTIFICATION TO PRINTER

Please Reference the Front Panel of This EPA Labeling. EPA no longer classifies the Solvent in this product as an Active Ingredient therefore entirely remove the Solvent Name from the Ingredient Statement. Adjust the figures to add the percentage which is now shown for the solvent TO the total percentage of the INERT INGREDIENT. Proof ASAP.

NOV 15 1989

Not Reviewed. Registrant claims to be in accordance with registration of Pesticide Product Guidance for Phase 2 response, Page 2.12, Active to Inert Change in Status.

- (4) Treat all voids in hollow masonry units of the foundation at the rate of at least 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

Buildings with Basements

- (1) Apply an over-all treatment under the basement flooring, as well as under attached porches, entrance platforms, utility entrances, and similar situation where slab fill is at the grade level. Apply at the rate of 1 gallon per 10 square feet, except that if fill under slab is of washed gravel, cinders, or similar coarse material, increase the dosage by at least one-half. Where crawl spaces exist, treat as described in part (2) below.

- (2) Dig a narrow trench to the top of the footing along the inside of foundation walls, around piers sewer pipes and conduits. Apply 2 gallons of emulsion per 5 linear feet of trench. The chemical should be mixed with the soil as it is being replaced in the trench.

- (3) Along the outside of foundation walls, dig a narrow trench, such trench to be dug no deeper than the top of the footings. If the trench is less than 15 inches in depth to the top of the footings, apply 1 gallon per 5 linear feet. Replace the soil and apply another 1 gallon per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. If the trench is more than 15 inches in depth to the top of the footings, apply 2 gallons per 5 linear feet. Replace the soil and apply another 2 gallons per 5 linear feet to the back fill. Cover the back fill with a thin layer of soil. A trench of 30 inches deep is a maximum depth required alongside foundations where the top of the footing is greater than 30 inches deep. In lieu of trenching to a 30" depth, make the trench 12 to 15" deep and rod to footing, spacing the holes about 1 foot apart.

- (4) Treat all voids in hollow masonry units of the foundation at the rate of 1 gallon per 5 linear feet of wall. Apply the emulsion so as to reach the footing.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited.

Pesticide, spray mixture, or rinseate that cannot be used or chemically reprocessed should be disposed of in a landfill approved for pesticides or buried in a safe place away from water supplies.

Triple rinse container and offer for recycling, reconditioning or disposal in approved landfills or burn in a safe place.

Consult federal, state or local disposal authorities for approved alternative procedures.

DO NOT USE POUR SPILL OR STORE NEAR HEAT OR OPEN FLAME.