U.S.D.A. Reg. No. 6811-x

• CLEANS • DEODORIZES • DISINFECTS

DIRECTIONS FOR USE

## GENERAL BEGBORIZING AND DISINFECTING

When diluted at the rate of 1:80 this solution shows disinfectant activity against surfaces conteminated with dried films of tubercle bacilli in erganic matter. For general deodorizing and disinfecting use 4 az. per gallon of water and scrub surfaces and allow to stand a few minutes and rines off.

GENGRAL DISINFECTING OF BATHROOMS, Etc. Use 4 to 5 ounces per gollon of water and scrub surtace, allowing to remain a few minutes and rinse off.

EARGER SHOP AND ESAUTY PARLOR EQUIPMENT: Clean thoroughly, then seek combs, brushes, razors, etc., or 10 mins. in a solution of 4 oz. per gallon of water.

NET CONTENTS: \_\_\_\_ GALS.

PINE OIL

DISINFECTANT

Water

(see side panel for further instructions)

• CLEANS • DEODORIZI

#### DIRECTIONS FO

FLOORS, WALLS, WOODWOR per 3 gallons of water. After cleaned put this solution on to stand a few minutes. Pick after to dry.

# SOAP SCUM REMOVAL

a solution of 3 to 4 az. per allow to dry. Works on Clath, ar any surface where meld as abserved that a water solution surface.

CAUTION: Marmful if sw physician immediately. mear heat keep away from Avoid contamination of 1

5112 MERCANTILE ROW

RESEARCH PRODUCTS co

DALLAS TEXA

Cameraman's Note Poor Copy ACCEPTED WITH COMMENTS

Ţ,

CAUTION:

eg. No. 6811-x

DEODORIZES • DISINFECTS

CTIONS FOR USE

## RIZING AND DISINFECTING

uted at the rate of 1:80 this clast activity against surfaces and films of tubercle bacilli in peneral deodorizing and diser gallon of water and scrub a stand a few minutes and

IG OF BATHROOMS, Esc. Use allon of water and scrub surin a few minutes and rinse off. BEAUTY PARLOR EQUIPMENT:

seak combs, brushes, razors, solution of 4 az. per gallen

\_\_\_GALS.

# TOINE OIL

DISINFE CTANT

Typhosa PHENOL COEF. 5 A.O.A.C. Method against S.

Steam distilled pine oil

MACTIVE WEREDIENT ..... 19%

CAUTION:

(see side panel for further instructions)

#### • CLEANS • DEODORIZES • DISIMPECTS

### DIRECTIONS FOR USE

FLOORS, WALLS, WOODWORK, etc.: Use 4 oz. per 3 gailons of water. After the floor has been cleaned put this solution on the floor and allow to stand a few minutes. Pick up the cases and allow to dry.

SGAP SCLM REMOVAL. Map down area with a solution of 3 to 4 oz. per gallen of water and allow to dry. Works on Clath, Shower Stalls, Walls, or any surface where mold accurs. Care should be abserved that a water salution will not have the surface.

CAUTION: Marmful if swallowed. Call physician immediately. Do not store near heat keep away from open flame. Avoid contamination of Food.

RESEARCH PRODUCTS co.

Water

DALLAS TEXAS 247

2 MERCANTILE ROW