

B-W Co.

Creosote-Petroleum Solution

CAUTION! COMBUSTIBLE!
KEEP AWAY FROM HEAT AND OPEN FLAME
Keep Closed When Not in Use

Active Ingredients	
Coal-Tar Creosote	48.5%
Petroleum Oil	51.5%
Total	100.0%

*This Creosote conforms to the specifications of the American Wood Preservers Association for Grade 1 Coal-Tar Creosote.

ACCEPTED
Apr 5 1971
 UNDER THE FEDERAL INSECTICIDE
 FUNGICIDE AND RODENTICIDE ACT
 FOR ECONOMIC POISON REGISTERED
 UNDER NO. *6823-1*

Comments

DIRECTIONS: Stir contents and use full strength. Apply several coats with brush or rag mop to all surfaces of Creosote-Petroleum Solution pressure treated lumber that has been exposed by cutting, notching or dapping.

USE WITH CAUTION STRICTLY IN ACCORDANCE WITH DIRECTIONS

Sold only for protection of Lumber against termites and decay-producing fungi.



ANTIDOTE: (internal)

Call a physician immediately. Emetic of mustard white of egg beaten up with water, olive oil, Magnesia. Stimulate with teaspoon of Spirits of Aromatic Ammonia in water or strong coffee.

POISON

Keep patient in horizontal position. Apply heat to extremities.

WARNING: Do not get in eyes, on skin, on clothing or in food or feed stuff. In case of accident, wash thoroughly with soap and copious quantities of water. For eyes: Flush with water for 15 minutes. Get medical attention immediately! Do not spray near open flame or hot objects. Wear protective clothing (synthetic rubber apron and gloves) when applying Pentachlorophenol solutions. When working indoors, goggles and a respirator are necessary for spraying. Do not breathe mist.

ACCEPTED WITH COMMENTS

Keep Out of Reach of Children

Destroy all empty containers

Do not sell except in original labeled containers

Baxter-Wyckoff Co.

560 White-Henry-Stuart Building
Seattle, Washington 98101

NET CONTENTS

..... GALLON

U.S.D.A. Reg. No. 6823-1



B-W Co.

Creosote-Petroleum Solution

CAUTION! COMBUSTIBLE!

KEEP AWAY FROM HEAT AND OPEN FLAME

Keep Closed When Not in Use

Active Ingredients

Coal-Tar Creosote
Petroleum Oil
Total

48.5%
51.5%
100.0%

*This Creosote conforms to the specifications of the American Wood Preservers Association for Grade 1 Coal-Tar Creosote.

ACCEPTED
cup
UNDER THE FEDERAL INSECTICIDE
AND FUNGICIDE ACT
FOR ECONOMIC PEST CONTROL ACT
REGISTERED UNDER NO.

DIRECTIONS: Stir contents and use full strength. Apply several coats with brush or rag mop to all surfaces of Creosote-Petroleum Solution pressure treated lumber that has been exposed by cutting, notching or dapping.

USE WITH CAUTION STRICTLY IN ACCORDANCE WITH DIRECTIONS

Sold only for protection of Lumber against termites and decay-producing fungi.



Faint, illegible text, possibly a registration or approval stamp.

WARNING: Do not get in eyes, on skin, on clothing or in food or feed stuff. In case of accident, wash thoroughly with soap and copious quantities of water. For eyes: Flush with water for 15 minutes. Get medical attention immediately! Do not spray near open flame or hot objects. Wear protective clothing (synthetic rubber apron and gloves) when applying Pentachlorophenol solutions. When working indoors, goggles and a respirator are necessary for spraying. Do not breathe mist.

ACCEPTED WITH COMMENTS

Keep Out of Reach of Children

Destroy all empty containers

Do not sell except in original labeled containers

Baxter-Wyckoff Co.

560 White-Henry-Stuart Building
Seattle, Washington 98101

NET CONTENTS

GALLON

U S D A. Reg. No. 6823 1

