

WARNING

Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Avoid contamination of food.

FIRST AID

In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes call a physician immediately. Remove and wash contaminated clothing before reuse.

If swallowed give patient doses of powdered charcoal immediately or all he can swallow of raw egg white, milk, gruel or flour and water. Then induce vomiting with salt, soap or mustard in warm water. Call physician immediately.

STORAGE AND HANDLING: Keep from freezing, store at normal room temperature. Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place. This product is toxic to fish. Treated effluent should not be discarded where it will drain into lakes, streams, ponds or treated water. Apply only as specified on this label.

FREMONT 9928 MICROBIOCIDES

Water Treatment Microbiocide
for Building and Industrial
Cooling Towers

Active Ingredients 11.66%

Disodium cyanodithioimidocarbonate 4.90%
Potassium N-methyldithiocarbamate 6.76%

Inert Ingredients 88.34%
100.00%

EPA Establishment No. 7053-MN-1

EPA Registration No. 7053-19

NET WEIGHT

NET VOLUME

FREMONT INDUSTRIES, INC.
Box 67, Shakopee, Minnesota 55379

WARNING

KEEP OUT OF REACH OF CHILDREN. SEE LEFT PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS. SEE RIGHT PANEL FOR USE OR APPLICATION DIRECTIONS.

Fremont 9928 Microbiocides
and fungi in recirculating water.
Before treatment, the system should be cleaned to remove algae and sludge. Add 1 fluid ounce of Fremont 9928 Microbiocides per 1000 gallons of water. Repeat applications at 1000 gallons of water at the required frequency and the severity of the problem. Dilute the appropriate amount of water before use.

C

FREMONT 9928 MICROBIOCIDES

Water Treatment Microbiocide
for Building and Industrial
Cooling Towers

Active Ingredients 11.66%

Disodium cyanodithioimidocarbonate 4.90%
Potassium N-methyldithiocarbamate 6.76%

Inert Ingredients 88.34%
100.00%

EPA Establishment No. 7053-MN-1

EPA Registration No. 7053-19

NET WEIGHT

NET VOLUME

FREMONT INDUSTRIES, INC.
Box 67, Shakopee, Minnesota 55379

WARNING

KEEP OUT OF REACH OF CHILDREN. SEE LEFT
PANEL FOR ADDITIONAL PRECAUTIONARY
STATEMENTS. SEE RIGHT PANEL FOR USE OR
APPLICATION DIRECTIONS.

DIRECTIONS

Fremont 9928 Microbiocide is used to inhibit the growth of algae, bacteria and fungi in recirculating commercial and industrial cooling water systems. Before treatment with Fremont 9928 Microbiocide systems must be cleaned to remove algae growth, microbiological slime and other deposits. Then the system should be treated with an initial slug addition of 5.1 to 10.2 fluid ounces of Fremont 9928 Microbiocide per 1000 gallons of water in the system. Repeat the initial dosage until control is evident. Subsequent slug additions of 1.7 to 10.2 fluid ounces of Fremont 9928 Microbiocide per 1000 gallons of water should be made every 1 to 5 days or as needed. The required frequency of treatment depends on the relative amount of bleedoff and the severity of the microbiological problem. Slug additions of Fremont 9928 Microbiocide should be made to the sump of water cooling towers. Dilute the appropriate amount of Fremont 9928 Microbiocide in 1 to 2 gallons of water before adding to the sump of the tower.

