

BEST AVAILABLE COPY

FOR SPARKLING POOLS

SLOW DISSOLVING CHLORINATING STICKS

ACTIVE INGREDIENT:

Trichloro-s-triazinetrione* 99.0%

INERT INGREDIENT.....1.0%

*Provides 89% Available Chlorine

KEEP OUT OF REACH OF CHILDREN

DANGER

SEE FIRST AID TREATMENT AND OTHER
PRECAUTIONS ON SIDE PANEL
BEFORE OPENING CONTAINER

NET WEIGHT 2 1/4 LBS. (40 OZ.)

BEST AVAILABLE COPY

1. Read and follow all directions on the label for use of this product in a manner consistent with its labeling.

2. Adjust water pH to 7.2 - 7.6 as determined by a test kit. For pools with copper plumbing best pH range is 7.5 - 7.8.

3. If the pool has not been previously stabilized, add Conditioner and Stabilizer (cyanuric acid) following the directions for use on the label for that product.

4. Set water circulation in the area of pool that is adjusted by return flow from filter. If residual chlorine is high, chlor water should be moved further from the application area which will slow the dissolving action of the sticks.

5. In new pools, follow steps 1 through 3 then add 2 sticks per 100 gallons of pool water to establish a chlorine residual of 1.0 to 1.5 p.p.m. as determined by a test kit. Repeat treatments as needed to maintain a residual of 1.0 to 1.5 p.p.m. at all times. For older pools, add 1 stick per 100 gallons of pool water as needed to maintain chlorine residual of 1.0 to 1.5 p.p.m. at all times. Residual chlorine should be determined by a test kit. For pools with stabilizer, follow steps 1 and 3 then add 1 stick per 100 gallons of pool water as needed to maintain a chlorine residual of 1.0 to 1.5 p.p.m. at all times as determined by a test kit.

Please note: the pH of Slow Dissolving Sticks is on the acid side and will tend to reduce the pH and alkalinity of the pool water. Proper pH should be maintained at pH 7.2 - 7.6 as determined by a test kit by periodic additions of sodium carbonate or sodium bicarbonate.

WARNING: IRRITANT. Keep product dry in tightly closed containers when not in use. Store in a cool, dry, well-ventilated area away from heat or open flame. In case of emergency, call state poison center in open area if possible, and flood with large amounts of water. If container is empty, container. Rinse empty container thoroughly with water to remove all material before reusing. Do not wash container or dispose in approved landfills. See label for disposal instructions.

E.P.A. Reg. No. 7124-14
E.P.A. Est. No. 7124-14

7124-14

Manufactured by ALCOA LEEDS INC.
So. Kearny, N.J. 07032