

SE

BEST AVAILABLE COPY

FOR INFORMATION

Shoock

- Pools with a green film due to algae
- Pools with a black film on floor and sides
- Pools with a strong water from the walls season
- Pools with a film that are green or brown due to a film of organic particles
- Pools with a strong odor
- Pools with a strong odor
- Pools with a strong odor

CLIENT

*F. Available Chlorine

KEEP OFF REFRIGERATOR AND KEEP OUT OF REACH OF CHILDREN
DANGER!
 SEE FIRST AID STATEMENT AND OTHER
 PRECAUTIONS ON SIDE PANELS
 BEFORE OPENING CONTAINER
 Net Weight 4 lbs. (64 oz.)

[illegible]

DANIEL NUSSENFELDER

It is a violation of federal law to use this product in a manner inconsistent with the label. The purpose of this product is to provide a shock treatment to ponds that are threatened or infested due to the presence of algae. Use of this product in the absence of neglect, or the presence of manganese, a condition of manganese 2 lbs of this product will treat 11 ppm of chlorine to 15,000 gal of water which should correct the calcium problem. A second treatment may be necessary if you were not forced to initial dose.

1. Remove as much as possible any floating suspended and/or sunken matter that may be present by use of a hand skimmer, net, or vacuuming the pool.
2. Adjust pool water pH to 7.2-7.6
3. Start filter and add Shock and Superchlorinate 8,000 gallons of pool water. Add Shock and Superchlorinate through skimmer noting special precautions on package panel. This product will bleach the vinyl linings of vinyl lined pools and bleach the paint on metal pools if it is added directly to the pool. Allow filter to run continuously being careful to empty skimmer basket in front of pump if suction is employed. As so there may be a tendency for the filter to clog due to the accumulation of dead algae. Backwash filter if this occurs. Repeat dosage of the same amount if necessary. If there is no improvement after two third day, consult your dealer or the manufacturer of this product for further advice. Do not over chlorinate. Chlorine dose as follows: 1.0 resins - 1.0 oz. per 10,000 g.p.m. Bathing should not be allowed in the pool until the chlorine residual is less than 1.0 ppm.

STORAGE AND CLASSIFICATION

[illegible]

1. General Information
 2. Personal Information
 3. Employment History
 4. Education
 5. References
 6. Notes
 7. Signature
 8. Date
 9. Signature
 10. Date
 11. Signature
 12. Date
 13. Signature
 14. Date
 15. Signature
 16. Date
 17. Signature
 18. Date
 19. Signature
 20. Date
 21. Signature
 22. Date
 23. Signature
 24. Date
 25. Signature
 26. Date
 27. Signature
 28. Date
 29. Signature
 30. Date
 31. Signature
 32. Date
 33. Signature
 34. Date
 35. Signature
 36. Date
 37. Signature
 38. Date
 39. Signature
 40. Date
 41. Signature
 42. Date
 43. Signature
 44. Date
 45. Signature
 46. Date
 47. Signature
 48. Date
 49. Signature
 50. Date
 51. Signature
 52. Date
 53. Signature
 54. Date
 55. Signature
 56. Date
 57. Signature
 58. Date
 59. Signature
 60. Date
 61. Signature
 62. Date
 63. Signature
 64. Date
 65. Signature
 66. Date
 67. Signature
 68. Date
 69. Signature
 70. Date
 71. Signature
 72. Date
 73. Signature
 74. Date
 75. Signature
 76. Date
 77. Signature
 78. Date
 79. Signature
 80. Date
 81. Signature
 82. Date
 83. Signature
 84. Date
 85. Signature
 86. Date
 87. Signature
 88. Date
 89. Signature
 90. Date
 91. Signature
 92. Date
 93. Signature
 94. Date
 95. Signature
 96. Date
 97. Signature
 98. Date
 99. Signature
 100. Date

STINGING FIRST AID: If a bee stings you, wash the area with soap and water. If the sting is on a sensitive area, such as the face, use a cold compress to reduce swelling. If you are allergic to bee stings, seek medical attention immediately.

Chemical Hazards. The use of hazardous materials, chemicals, or substances in the laboratory is prohibited. The use of any chemical reagent or substance in the laboratory is prohibited.

and the pesticide is some por-
tion of the water. For
this reason, the water
must be changed
frequently.

SPECIAL ADVERTISING NOTICE: PLEASE READ

avoid breathing

2. **Plunger**—Use the plunger to apply the product in its undiluted state to the contaminated surfaces with the nozzle. The nozzle is designed to introduce the product into the cracks and crevices of the leaded solder.

3. V. on ad. ...
 4. ...
 5. ...
 6. ...

4. Use this procedure as a guide in
future. Do not leave advice
by yourself.

If it is possible to find
 great literature in the
 and it is not possible
 to find it in the
 new world. So, it is
 not possible to find it

EPA 402-1-15-AA
L.A. 81-1-10-1

536 A. DENIELLO, M. G. N. J. ORLANDI