

ACCEPTED

SEP 22 1993

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 7124-29

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Irritating to nose and throat. Avoid breathing dust. Remove and wash contaminated clothing before reuse.

PHYSICAL AND CHEMICAL HAZARDS: Danger: Strong oxidizing agent. Mix only into water. Contamination may start a chemical reaction with generation of heat, liberation of hazardous gases, and possible fire or explosion. Avoid any contact with flame or burning material, such as a lighted cigarette. Do not contaminate with moisture, garbage, dirt, organic matter, chemicals including other pool chemicals, pool chlorinating compounds, household products, cyanuric pool stabilizers, soap products, paint products, solvents, acids, vinegar, beverages, oils, dirty rags or any foreign matter. Do not use moist or damp utensils.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

SPECIAL PRECAUTIONS PLEASE READ BEFORE OPENING CONTAINER

PREVENTION OF PHYSICAL INJURY

1. This product emits a powerful chlorine gas. Do not open container indoors. Hold away from face when opening to avoid breathing fumes.
2. This product is dangerous when not used properly.

MISUSE MAY RESULT IN SERIOUS PERSONAL INJURY REQUIRING HOSPITALIZATION

RELATED COMPLICATIONS MAY LEAD TO DEATH

Do not mix with any other chemicals.
Mixing with other chemicals may cause a violent and instantaneous chemical reaction.

- Do not add water to this product.
- Do not add this product to water in a pool.
- Do not take advice from others.
- Do not experiment.
- Follow label instructions exactly.

PREVENTION OF PROPERTY DAMAGE: Contact between this product in its undissolved state and vinyl liners, painted surfaces or other property in or around the pool will result in permanent bleaching of the color. 9/10

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

Proper dosages of this product will control growth of algae and effectively kill many bacteria which may cause infection.

FOR USE AS A SHOCK TREATMENT

The purpose of this product is to provide a shock treatment to pools that are unacceptable for use due to the presence of bacteria or algae, or discolored because of neglect or the presence of minerals such as iron or manganese. One pound of this product will impart 3 ppm (parts per million) of available chlorine to 9,000 gallons of water. In some cases when the extent of organics present in the pool does not allow the water to respond to the initial dose, a second treatment may be necessary.

1. Remove as much as possible any floating, suspended and/or sunken matter that may be present by use of a hand skimmer, pool leaf rake or by vacuuming to waste.
2. Adjust pool water pH to 7.2-7.6.
3. Introduce this product at the rate of 1 lb. per 9,000 gallons of water.

HIT HARD

SHOCK TREATMENT

wuclo

Designed To Be Used In Pools As A Periodic Shock Treatment
In Regular Maintenance And In:

- Pools with visible algae on floor and sides
- Pools with green water due to algae
- Pools freshly filled that are green or brown due to mineral impurities
- Pools Starting up using water from previous season
- Pools with cloudy water
- Provides calcium hardness
- Fast acting helps raise pH

ACTIVE INGREDIENT

Calcium Hypochlorite 65.0

INERT INGREDIENT

35.0

*Provides Available Chlorine

STATEMENT OF PRACTICAL TREATMENT

FIRST AID

In case of contact with eyes, flush immediately with water for at least 15 minutes. In case of contact with skin, wash immediately with water. In case of inhalation, move to fresh air. In case of ingestion, do not induce vomiting. Seek medical attention immediately.

DANGER KEEP OUT OF REACH OF CHILDREN
SEE FIRST AID STATEMENT AND OTHER
PRECAUTIONS ON SIDE PANEL BEFORE OPENING CONTAINER

NET WT.
5 LBS.

SEE DIRECTIONS FOR APPLICATION BELOW:

Allow filter to run continuously being careful to empty strainer basket in front of pump if suction is impeded. Also, there may be a tendency for the filter to clog due to the accumulation of dead algae. Backwash filter if this occurs. Repeat dosage on the second day if necessary. If there is no improvement on the third day, consult your dealer or the manufacturer of this product for further advice. Do not resume regular chlorine dosages until chlorine residual falls to between 1 and 3 ppm. Bathers should not be allowed to enter the pool until chlorine residual falls to 2 ppm or less.

NOTE ON POOLS TREATED FOR ALGAE: If this product is used to shock or superchlorinate an algae infested pool, after treatment it is important to brush the walls and floor to expose algae that may be in cracks or wrinkles that might protect algae from high chlorine residuals.

FOR USE IN DAILY CHLORINATION

INITIAL DOSAGE: Add 1 ounce of this product for each 1,000 gallons of water. The initial chlorination dose should be repeated until a chlorine residual of 0.8 to 1.0 p.p.m. is obtained.

MAINTENANCE DOSAGE: Add one ounce per 5,000 gallons daily or as needed to maintain a residual of 0.8 p.p.m. to 1.0 p.p.m. of available chlorine as determined by the use of a chlorine test kit. Keep pH in range between 7.2-7.6.

One ounce of this product will add 1.0 p.p.m. available chlorine to 5,000 gallons of water. During hot sunlit days or when bathing load is heavy, test water frequently as available chlorine may dissipate rapidly. Maintain chlorine residual between 0.8 p.p.m. and 1.0 p.p.m. at all times.

Application should be made using one of the following methods:

SKIMMER: Use this method to avoid bleaching vinyl liner or paint. Empty skimmer of all chemicals and/or debris. Make sure that filter is on and that water is properly recirculating through skimmer. Remove any chemicals that may be in an in-line automatic chemical dispensing device. Pour product slowly into skimmer, making sure that the material is drawn into the system at the same rate. Do not allow this material to accumulate as gases generated may cause an explosion.

DOSE DIRECTLY INTO POOL: Broadcast dosage across surface of water. To prevent liner damage, use skimmer method above.

POOL GALLON CALCULATOR (all dimensions in feet)

Square or Rectangular
Length x Width x Average Depth x 7.5 = Gallons
Round or Oval
Length x Width x Average Depth x 5.9 = Gallons

STORAGE AND DISPOSAL

STORAGE: Keep product in dry tightly closed container when not in use. Store in a cool, dry, well-ventilated area away from heat or open flame.

DISPOSAL: Do not reuse empty container. Rinse empty container thoroughly with water to dissolve all material before discarding. Place in trash or dispose in approved landfill area.

EMERGENCY HANDLING: In case of contamination or decomposition, do not reuse container. If possible isolate container in open and well-ventilated area. Flood with large volumes of water. 11/10

EPA REG NO. 7124-29
EPA EST. NO. 7124-NJ-1

Manufactured by
ALDEN LEEDS, INC.
55 Jacobus Ave.
So. Kearny, NJ 07002

BEST AVAILABLE COPY