

VINYL POOL SHOCK

HELPS PREVENT BLEACHING AND DISCOLORATION
OF VINYL LINERS AND PAINTED SURFACES WHEN
USED AS A PERIODIC SHOCK TREATMENT IN REG-
ULAR MAINTENANCE AND IN:

- 1 Pools with green water due to algae
- 2 Pools with visible algae on floor and sides
- 3 Pools starting up using water from previous season
- 4 Pools freshly filled that are green or brown due to mineral impurities
- 5 Pools with cloudy water

ACTIVE INGREDIENT

Lithium Hypochlorite 29%
INERT INGREDIENT 71%
*Provides 35% Available Chlorine

KEEP OUT OF REACH OF CHILDREN
DANGER

PRACTICAL TREATMENT (First Aid) If swallowed, feed bread soaked in milk followed by olive oil. Call a physician immediately if on skin. Brush off excess chemical and flush skin with cold water for at least 15 minutes. If in eyes, flush with cold water for at least 15 minutes. Get medical attention.

SEE ADDITIONAL PRECAUTIONS
ON SIDE PANEL

NET WEIGHT 18.16 (0.72)

ACCEPTED
with COMMENTS
EPA REG NO. 7124-N

OCT 2 1984

7124-84

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING

The purpose of this product is to provide a shock treatment to pools that are unacceptable for use due to the presence of algae or discolored water because of neglect or iron or manganese.

TO AVOID POSSIBLE BLEACHING OR DISCOLORATION OF VINYL LINERS ADD ALL CHEMICALS THROUGH SKIMMER. NEVER DIRECT ONE CHEMICAL AT A TIME. NEVER TWO AT ONCE. AS A VIOLENT REACTION MAY OCCUR

1. Remove as much as possible any floating, suspended and/or sunken matter that may be present by use of a hand skimmer, net or vacuuming to waste.
2. Adjust pool water pH to 7.2 - 7.6.
3. Start filter and add VINYL POOL SHOCK at the rate of 1 lb (16 oz) per 7500 gallons of pool water. Dose by feeding VINYL POOL SHOCK through the pool skimmer. Be careful to empty strainer basket in front of pump if suction is impeded. Also there may be a tendency for the filter to clog due to the accumulation of dead algae. Back dosage on the second day if necessary. If there is no improvement on the third day consult your dealer or the manufacturer of this product for further advice. Do not rest.

residual reads between 1 and 3 ppm.

BATHERS SHOULD NOT BE ALLOWED TO ENTER THE POOL UNTIL THE CHLORINE RESIDUAL DROPS TO 3 PPM OR LESS

STORAGE AND DISPOSAL Keep this product dry in a tightly closed container when not in use. Store in a cool, dry, well-ventilated area away from heat or open flame. Do not store in a place where it is possible and flood area with large amounts of water to dissolve all materials before discarding this container. Place in trash collection or dispose in safe place.

EPA REG NO 7124 (NEW PRODUCT REGISTRATION #) EPA EST NO 7124-N J-1
manufactured by ALDEN LEEDS, INC. 55 Jacobus Avenue South Kearny, New Jersey 07032

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Highly corrosive. Causes skin and eye damage. May be fatal if swallowed. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves. Avoid breathing dust. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Do not discharge into lakes, streams, ponds or public waters unless in accordance with an NPDES permit from the Regional office of EPA.

PHYSICAL AND CHEMICAL HAZARDS STRONG OXIDIZING AGENT: Mix only with water. Use clean dry utensils. Do not add this product to any dispensing device containing remnants of any other product. Such use may cause a violent reaction leading to a fire or explosion. Moisture, organic matter or other chemicals may start a chemical reaction with generation of heat, liberation of hazardous gases and possible generation of fire and explosion.

SPECIAL PRECAUTIONS (PLEASE READ)

1. This product has a powerful chlorine odor. Hold away from face when opening to avoid breathing fumes.
2. Prolonged contact between this product in its undissolved state and vinyl liners or painted surfaces will result in bleaching of the vinyl or paint. Introduce this product through the prescribed feeder to avoid discoloration of liner or paint.
3. When adding this product to skimmer or feeder make sure there are no other chemicals present as a violent reaction may occur. It is always dangerous to mix chemicals.
4. Use this product as directed as per instructions on label. Do not take advice from others or experiment by yourself.
5. If this product is used to shock or superchlorinate a pool, after treatment it is important to brush walls and floor to expose algae that may be in cracks or wrinkles. Chlorine residual. Such protected algae will begin to reproduce again when high chlorine residual falls.
6. This product, because of its potent formulation, can be dangerous if not used properly. Do not mix with any other chemicals. This could result in a violent chemical reaction in a closed container. Do not add this product to a small amount of water in a pail. When adding this product to skimmer make sure pump is on and water is circulating. Do not allow build up of dry material in skimmer as gases generated may cause an explosion.

SIDE PANEL

FRONT PANEL

SIDE PANEL

8/84 ALDEN LEEDS, INC. 55 JACOBUS AVE., SO KEARNY, N.J. 07032 (201) 589-3544

FILE 9 VINYL SHOCK