

**PENTA
(Water
Repellent)**

Directions: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Protective clothing and jobber gloves should be worn when applying Penta or when handling heavily treated lumber. Penta can cause severe skin irritation. Apply only by brushing or soaking. Do not spray.

Stationary wood to be treated in Water Repellent Penta should be treated in 4 applications if possible. Apply 2 liberal coats by brush, allowing a minimum of one hour between applications. Allow a minimum of 24 hours drying time prior to painting. Treated wood for lumber to be used where severe conditions of exposure exist should be kept soaking period and heavier absorption is recommended. Because of the high viscosity in available clear formulations, some joints may dry more slowly on wood called soft-wood. Water Repellent Penta, because of its non-uniformly applicable AHS are possible will have to absorb or dry in 14 days. If wood industry surface must be kept soaked and kept covered in some joints of the wood.



**sunnyside
penta wood
preservative**
WATER REPELLENT
(PAINTABLE)

CONTROLS DECAY WARNING & CHECKING

ACTIVE INGREDIENTS	4.2%
INERT INGREDIENTS	95.8%
TOTAL	100%



**PENTA
(Water
Repellent)**

ACCEPTED
7135-2
DEC 8 1980
Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, this product is registered under EPA Reg. No.

PENTA WOOD PRESERVATIVE (Water Repellent) Sunnyside Water Repellent Penta offers positive protection to lumber and masonry from damage by moisture, decay, mold and mildew, termites, powder post beetles and other wood boring insects, and fungi that cause rot and blue stain. It greatly reduces swelling and shrinking, checking, warping, staining and discoloration, and is also a preservative against staining and discoloration of masonry. Water Repellent Penta is a clear, non-toxic, non-flammable liquid which does not contain any volatile organic compounds. It is frequently used as a preservative for wood and masonry. It is also used as a preservative for concrete and masonry. It is also used as a preservative for concrete and masonry. It is also used as a preservative for concrete and masonry.

WARNING: CONTAINS PENTACHLOROPHENOL AND PETROLEUM DISTILLATE. Keep away from heat and open flame. Avoid breathing vapor. Vapor can be harmful if inhaled. Avoid vapor accumulation by providing plenty of fresh air ventilation. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

FIRST AID: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention. For skin contact, wash thoroughly. If overcome by vapors, remove to fresh air and get medical attention.

ENVIRONMENTAL HAZARDS: This product is toxic to humans, fish and wildlife. Keep out of lakes, streams and ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label. Do not use treated wood inside dairy barns, silos or other structures where it may contact food, feed or livestock. Protect grass, leafy plants and vegetation from contact with Penta Wood Preservative (Water Repellent).

STORAGE AND DISPOSAL: Close container after each use. Do not transfer contents to unlabeled containers. Do not reuse empty container. Wrap container and put in trash collection.

Use only with adequate ventilation.
EPA Reg. No. 7135-2

WARNING!
KEEP OUT OF REACH OF CHILDREN
HAZARDOUS IF SWALLOWED OR ABSORBED THROUGH SKIN
COMBUSTIBLE SKIN AND EYE IRRITANT

SUNNYSIDE CORPORATION

