

30 242-643-75

REFINED
CREOSOTE
OIL



sunnyside

REFINED

creosote
oil

WOOD PRESERVATIVE
FUNGICIDE & INSECTICIDE
WOOD STAIN

ACTIVE INGREDIENTS 100%
Refined Creosote Oil 100%

EPA Reg. No. 7155-11
EPA Reg. No. 7155-4

depend on
the top quality
of sunnyside

CAUTION!
KEEP OUT OF REACH OF CHILDREN
HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN
COMBUSTIBLE SKIN AND EYE IRRITANT
See other warnings on back panel. Use only as directed.
ONE GALLON □ 3.785 LITERS

REFINED
CREOSOTE
OIL

DIRECTIONS

Wood Protection: Wood should be peeled, decay-free, dry and seasoned. Soak construction lumber in creosote for at least 3 minutes per inch of thickness. Fence posts are best treated by full length coverage; for butt treatment soak 24 hours and set with 12 inches of treated wood extending above ground level.

On existing structures creosote controls fungus rot and decay only. Apply liberally with brush or spray, allow to dry, then repeat treatment. When treated lumber is cut, apply 2 coats of creosote to the exposed, untreated wood. Never nail wallboard or other absorbent materials over treated wood unless absolutely dry.

Termite Control: Dig 12" wide trench around foundation walls, not lower than top of footing. Soil removed from trench should be thoroughly drenched with creosote at rate of 1 gallon per linear foot for trenches more than 15" deep, or 1/2 gallon per linear foot for trenches less than 15" deep. Treated soil should then be replaced in trench.

depend on
the top quality
of sunnyside

REFINED CREOSOTE (Sunnyside Creosote protects carpenter ants and powder siding, clapboard and shing light brown stain and protecting, checking, swelling and not for interior use and sh If further finishing is pla Sunnyside Penta Water Repel

CAUTION. CONTAINS COAL TAR do not induce vomiting. Cl Keep away from heat and op of vapor and contact with contact with skin or eyes, ous amounts of water. Get container after each use. bottles or other unlabeled empty container. Destroy ing. Bury or discard in a

This product is toxic to fl of lakes, streams and ponds by cleaning of equipment or this product only as specif

Do not use treated wood ins other structures where it n livestock.

Protect grass, leafy plants tact with creosote.

Use only with adequate vent

KEEP OUT OF REACH OF CHILDR

SUNNYSIDE PROD
CONSUMER PR
CHICAGO

CUST. Sunnyside Prod. DESIGN CREOSOTE OIL (1 GAL. F) NO PROOF
ENG. 1252-5 S.O. 242-643 SIZE 400x600x907 (E. 9-5622 20 40 B.P. 25-29 DATE 4/8/75) PROOF DATE 10



sunnyside

REFINED

creosote oil

WOOD PRESERVATIVE
FUNGICIDE & INSECTICIDE
WOOD STAIN

ACTIVE INGREDIENTS 100%
Refined Creosote Oil 100%

REFINED CREOSOTE OIL

DIRECTIONS

Wood Protection: Wood should be peeled, decay-free, dry and seasoned. Soak construction lumber in creosote for at least 3 minutes per inch of thickness. Fence posts are best treated by full length coverage; for butt treatment soak 24 hours and set with 12 inches of treated wood extending above ground level.

On existing structures creosote controls fungus rot and decay only. Apply liberally with brush or spray, allow to dry, then repeat treatment. When treated lumber is cut, apply 2 coats of creosote to the exposed, untreated wood. Never nail wallboard or other absorbent materials over treated wood unless absolutely dry.

Termite Control: Dig 12" wide trench around foundation walls, not lower than top of footing. Soil removed from trench should be thoroughly drenched with creosote at rate of 1 gallon per linear foot for trenches more than 15" deep, or 1/2 gallon per linear foot for trenches less than 15" deep. Treated soil should then be replaced in trench.

REFINED CREOSOTE OIL

Sunnyside Creosote protects against fungi, termites, carpenter ants and powder post beetles. When used on siding, clapboard and shingles, creosote produces a light brown stain and protects against decay, warping, checking, swelling and shrinking. Creosote is not for interior use and should not be painted over. If further finishing is planned after treatment, use Sunnyside Penta Water Repellent rather than Creosote.

CAUTION. CONTAINS COAL TAR CREOSOTE. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. Keep away from heat and open flame. Avoid breathing of vapor and contact with skin or eyes. In case of contact with skin or eyes, flush repeatedly with copious amounts of water. Get medical attention. Close container after each use. Do not transfer contents to bottles or other unlabeled containers. Do not reuse empty container. Destroy it by perforating or crushing. Buy or discard in a safe place.

This product is toxic to fish and wildlife. Keep out of lakes, streams and ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label.

Do not use treated wood inside dairy barns, silos or other structures where it may contact food, feed or livestock.

Protect grass, leafy plants and vegetation from contact with creosote.

Use only with adequate ventilation.

KEEP OUT OF REACH OF CHILDREN.

ACCEPTED

SEP 1975

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, this pesticide registered to
EPA Reg. No.

CAUTION!

KEEP OUT OF REACH OF CHILDREN
HARMFUL IF SWALLOWED OR ABSORBED THROUGH SKIN
COMBUSTIBLE. SKIN AND EYE IRRITANT
See other warnings on back panel. Use only as directed

ONE GALLON □ 3.785 LITERS

depend on
the top quality
of sunnyside

SUNNYSIDE PRODUCTS, INC.

CONSUMER PRODUCTS DIVISION
CHICAGO, ILLINOIS 60640



CUST. Sunnyside Prod. DESIGN CREOSOTE OIL (1 GAL. F.) NO. PROOFS
ENG. 1262-S S.O. 242-643 SIZE 40x26x907 C.E. 9-582A 2040 B.P. 24-5-24 DATE 4/5/75 PROOF DATE 10 00