

REFINED
CREOSOTE
OIL

Directions: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Protective clothing and rubber gloves should be worn when using Creosote. Creosote can quickly cause severe sun burns, particularly in the presence of sunlight.

Timber Care: Dig 12" trench around foundation walls, not lower than top of footing. Soil removed from trench should be thoroughly drenched with creosote at rate of 1 gallon per linear foot for trenches more than 15' deep, or 1/2 gallon per linear foot for trenches less than 15' deep. Sealed soil should then be replaced in trench.

ACCEPTED
DEC 8 1980
Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended for the pesticide registered under EPA Reg. No. 2135-4

WOOD PRESERVATIVE
FUNGICIDE & INSECTICIDE
WOOD STAIN

ACTIVE INGREDIENTS 100%
Refined Creosote Oil 100%


sunnyside
REFINED
creosote
oil

REFINED
CREOSOTE
OIL

Directions: It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Protective clothing and rubber gloves should be worn when applying creosote or when handling freshly treated lumber. Creosote can quickly cause severe skin burns, particularly in the presence of sunlight. Apply only by brushing or soaking. Do not spray.

Wood Preservation: Wood should be painted directly after dry and seasoned. Soak construction lumber in creosote for at least 3 minutes per inch of thickness. Fence posts are best treated by full length coverage. For full treatment soak 24 hours and set with 12 inches of treated wood extending above ground level. On existing structures creosote controls fungus rot and decay only. Apply liberally with brush, allow to dry then repeat treatment. When treated lumber is cut, apply 2 coats of creosote to the exposed untreated wood. Never use wallboard or other absorbent materials over treated wood unless absolutely dry.

Refined CREOSOTE OIL Sunnyside Creosote protects against long termites, carpenter ants and powder post beetles. When used on siding, clapboard and shingles, creosote produces a light brown stain and protects against decay, warping, checking, swelling and shattering. Creosote is not for interior use and should not be painted over. If further finishing is planned after treatment, use Sunnyside Perla Water Repellent rather than Creosote.

CAUTION. CONTAINS COAL TAR CREOSOTE. Keep away from heat and open flame. Avoid breathing vapor. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling.

FIRST AID: If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. In case of eye contact, flush thoroughly with water and get medical attention; for skin contact, wash thoroughly.

ENVIRONMENTAL HAZARDS: This product is toxic to humans, fish and wildlife. Keep out of lakes, streams and ponds. Do not contaminate water by cleaning of equipment or disposal of wastes. Apply this product only as specified on this label. Do not use treated wood inside dairy barns, silos or other structures where it may contact food, feed or livestock. Protect grass, leafy plants and vegetation from contact with creosote.

STORAGE AND DISPOSAL: Close container after each use. Do not transfer contents to unlabeled containers. Do not reuse empty container. Wrap container and put in trash collection.

Use only with adequate ventilation.
KEEP OUT OF REACH OF CHILDREN

EPA Est. 7126-B-1
EPA Reg. No. 7125-4

depend on
the top quality
of sunnyside

CAUTION!
KEEP OUT OF REACH OF CHILDREN. HARMFUL
IF SWALLOWED OR ABSORBED THROUGH SKIN.
COMBUSTIBLE. SKIN AND EYE IRRITANT.
See other warnings on back panel. Use only as directed.

32 FL. OZ. (1 QT.) ■ 9463 LITER

depend on
the top quality
of sunnyside

SUNNYSIDE CORPORATION
CONSUMER PRODUCTS DIVISION
WHEELING, ILLINOIS 60090