

# TRICLOSAN

## A BACTERIOSTAT FOR USE IN THE MANUFACTURE OF LATEX

**Active Ingredient:**  
**5-Chloro-2-(2, 4-dichlorophenoxy)**  
**phenol . . . . . 99%**  
**Inert Ingredients . . . 1%**

**DANGER:** Keep out of Reach of Children

NET WT 110 LBS

### PRIMARY STATEMENTS

For Industrial and Domestic Use  
Irritant, causes eye and skin irritation. Do not get in eyes or on clothing. Wear goggles and rubber gloves. In case of contact with plenty of water. In case of skin contact, wash with water.

001-3  
0-R11

ACCEPTED  
29 MAY 1961  
4001-3

7000  
1151

### DIRECTIONS FOR USE

Use as a bacteriostat in the manufacture of latex products in a rubber processing plant. Refer to Technical Bulletin for details and for additional information and processing instructions.

### STORAGE AND DISPOSAL

**Prohibitions**  
Do not contaminate water, food, or feed by storage or disposal. Open burning is prohibited. Do not reuse empty container.

**Pesticide disposal**  
Pesticide, spray mixture or residue that cannot be used or chemically reprocessed should be disposed of in a safe place away from water supplies.

**Container Disposal**  
Empty container should be disposed of in a safe place away from water supplies.

NET WT 110 LBS

ACCEPTED  
 71.52-37  
 JUN 1 1981  
 Under the Federal Insecticide,  
 Fungicide, and Rodenticide Act,  
 an analysis of the pesticide  
 required under  
 LFA 3-11.

**DIRECTIONS FOR USE**

It is a violation of federal law to use this product in a manner inconsistent with its labeling.

**DIRECTIONS FOR NEWLY FILLED POOLS.**

SEALCURE is added directly to the pool water at the rate of one pound per 8000 gallons to establish a residual chlorine value of 1.0-1.5 ppm. This dosage should be repeated until the test results for residual chlorine are in the range of 1.0-1.5 ppm. Sun Screen protection and Stabilization of chlorine in the pool is provided by stabilizer according to label instructions.

**REGULAR MAINTENANCE TREATMENT**

Adjust whatever proportioning mechanism that might be used to assure a constant treatment level of 1.0-2.0 ppm available chlorine in the pool water (normally 1-2 oz. of this product per 10,000 gallons daily). The chlorine level should be checked daily with the use of a suitable test kit. Due to the daily changes in weather, temperature, and bathing, the frequency and the amount of SLO-TAB 4 added will vary. Pool water pH must be adjusted and maintained regularly in the pH range of 7.2-7.6. For each pound of SLO-TAB 4, a half pound of SEABOARD PLUS is added for pH control.

**NET WT. 4 LBS.**

**SPARKLING WATER-SIMPLY & EASILY**

**SLO-TAB 4**

4 OZ TABLET

ACTIVE INGREDIENTS  
 INERT INGREDIENTS  
 TOTAL

**DANGER**

**KEEP OUT OF REACH OF CHILDREN  
DANGER**



**SEABOARD  
INDUSTRIES**  
 NEW JERSEY

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS  
DOMESTIC ANIMALS**

**DANGER** Highly corrosive. Causes eye damage. May be fatal if swallowed. Causes skin and eye irritation. Wear eye shield and rubber gloves when handling. Avoid breathing dust. Wash contaminated clothing before reuse.

**ENVIRONMENTAL HAZARDS** Toxic to fish. Do not discharge into ponds or public waters unless in accordance with NPDES Permit. For guidance contact office of EPA.

**PHYSICAL AND CHEMICAL HAZARDS**  
**OXIDIZING AGENT:** Strong Oxidizing Agent. Do not mix with water. Use clean utensils. Do not mix with any other product. Such use may cause a reaction leading to fire or explosion. Do not mix with moisture, organic matter, or acids. Do not start a chemical reaction, with liberation of hazardous gases, and fire and explosion. In case of decomposition, do not reseal container in open air or over fire. Flood with large volumes of water.

**STORAGE AND DISPOSAL:** Keep in tightly closed container when not in use. Store in a cool, dry, well ventilated area away from flame. In case of decomposition, do not breathe dust. If possible, and flood with large volumes of water. Dissolve all material before disposal. Collect and dispose in approved manner in a safe place.

