

BROWN

**PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND
DOMESTIC ANIMALS**

CAUTION! KEEP OUT OF REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED OR ABSORBED THROUGH SKIN. CAUSES EYE AND SKIN IRRITATION. KEEP AWAY FROM HEAT OR OPEN FLAME.

Use only in well-ventilated area. Do not breathe vapors or spray mist. Do not get product on skin or clothing. Wear rubber gloves and protective eyewear when handling heavily treated lumber.

FIRST AID: If in eyes, flush with clean water. If on skin, wash with soap and water. If swallowed, do not induce vomiting. Immediately seek medical attention. Call a physician if you are advised to do so.

ENVIRONMENTAL HAZARDS: Do not discharge into water. Do not discharge into soil. Do not discharge into air. Do not discharge into sewer.

PHYSICAL OR CHEMICAL HAZARDS: Do not use in confined spaces. Do not use in areas where fire or explosion is a hazard. Do not use in areas where it may come in contact with other materials.

STORAGE AND DISPOSAL: Do not store in unapproved containers. Do not store in areas where it may be accessible to children or pets. Do not dispose of in landfills or incinerators.

APPROXIMATE COVERAGE: One gallon covers approximately 100 square feet of smooth wood.

DRYING: Apply to clean, dry wood. Allow to dry for 24 hours before use.

CLEAN-UP: Wash hands thoroughly after use.

LIMITED WARRANTY: This product is warranted to be free of defects in material and workmanship for a period of one year from the date of purchase. The warranty is limited to the product and does not cover labor or other costs.

OLYMPIC STAIN
A division of COMERCO, INC.

ACCEPTED

PRESERVES WOOD BEAUTY

OLYMPIC

WEATHER-RESISTANT STAIN

PENETRATES. REPELS WATER. GUARDS AGAINST MILDREW FOR WOOD DECKS.

CAUTION KEEP OUT OF REACH OF CHILDREN
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

1 GALLON 3.785 LITERS

PRESERVES WOOD BEAUTIFULLY



OLYMPIC

WEATHER SCREEN

LINSEED OIL
SEMI
TRANSPARENT

STAIN AND WOOD PRESERVATIVE

PENETRATES, REPELS WATER, SCREENS SUN RAYS
GUARDS AGAINST MILDEW, ROT AND DECAY
FOR WOOD DECKS, FENCES AND SIDING

CAUTION KEEP OUT OF REACH OF CHILDREN
SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

1 GALLON 3.785 LITERS

ACTIVE INGREDIENTS
Bis (tributyltin) oxide 0.50%
Folpet (N-11-trichloromethyl-2-thio) phthalimide 0.50%
INERT INGREDIENTS 99.00%
TOTAL 100.00%

MEETS FED. SPEC. TT-W-572 B3.7
EPA Reg. No. 7313-51 EPA Est. No. 7313-WA-1 7313-11-1 7313-KV-1

DIRECTIONS

SURFACE PREPARATION:

STAIN PREPARATION:

EXTRACTIVE BLEEDING:

APPLICATION:

FOR ADDITIONAL INFORMATION

SEED OIL
SEMI
TRANSPARENT
EFFECTIVE
IN RAYS
CAY
IG

TA 100 904

7313 AA 1 7313 H 1 7313 K 1

DIRECTIONS FOR USE

Apply this product mix as specified on this label to a variety of surfaces with the product in a manner consistent with its labeling.

Weather-Screen is a penetrating, non-toxic, non-flammable and non-hazardous stain and wood preservative. Weather-Screen is made with TBT, a wood preservative and FOL-POL, a mildewicide and fungicide. Weather-Screen is registered with the Environmental Protection Agency and exceeds the Federal Government's tolerance, 11 W 572 B paragraph 3.

Weather-Screen is recommended for exterior use on wood decks, fences and logs which may be exposed to attack by wood rot, mold and excess moisture. It can be used on both new wood and over previous sealants, paint, stained surfaces. One coat is normally satisfactory for new applications to rough wood. Ideally, the wood should be dry and absorbent for maximum performance. A single brushout is always recommended to determine the actual color result. Do not use on glazed plywood or on a surface in contact with the ground. To protect and preserve wood before painting or staining, use Weather-Screen. To protect and preserve wood before painting or staining, use Weather-Screen. To protect and preserve wood before painting or staining, use Weather-Screen.

SURFACE PREPARATION: All surfaces must be clean, dry and free of mold. Remove dirt, dust, oil, soap or other contaminants by washing with a detergent solution. Rinse thoroughly and allow to dry completely before staining. Remove grease, stains, pencil marks, etc., by sanding. Where mildew is evident, remove it by scrubbing the surface with this solution. One cup Trisodium Phosphate (TSP) or other detergent and one quart of household bleach dissolved into 3 quarts water. CAUTION: TSP and household bleach are potentially harmful materials. Follow manufacturer's instructions, wear protective clothing, eye goggles and good rubber gloves. Rinse thoroughly with fresh water and immediately apply a solution of 5% household bleach and fresh water. Allow this final treatment to dry before staining.

STAIN PREPARATION: The stain may be used as a brush-on stain or a spray-on stain. If used as a brush-on stain, brush the stain into the wood and mix thoroughly. If used as a spray-on stain, spray the stain onto the wood and mix thoroughly. If used as a brush-on stain, brush the stain into the wood and mix thoroughly. If used as a spray-on stain, spray the stain onto the wood and mix thoroughly.

EXTRACTIVE BLEEDING: Some woods contain water-soluble tannins or extractives that may bleed through the stain. This may be detected by rubbing the stain into the wood and allowing it to dry. If the stain is found to be bleeding through, the stain should be removed and the wood should be treated with a water-soluble stain.

APPLICATION: Weather-Screen is best applied with a natural bristle brush. Thoroughly clean and dry the brush before use. Apply the stain to the wood and mix thoroughly. If used as a brush-on stain, brush the stain into the wood and mix thoroughly. If used as a spray-on stain, spray the stain onto the wood and mix thoroughly.

FOR ADDITIONAL INFORMATION - ASK YOUR DEALER