

7313-6, 17-83 11/10

305 159/03  
17 1

MAR 31 1986

The Olympic Homecare Products Company  
c/o The Clorox Technical Center, PS & RCII  
7200 Johnson Drive  
Pleasanton, CA 94566

Attention: Ms. Virginia C. Lew

Gentlemen:

Subject: Olympic Semi-Transparent Weather Screen  
EPA Registration No. 7313-5  
Olympic Wood Preservative (Clear)  
EPA Registration No. 7313-6  
Olympic Wood Preservative (Green)  
EPA Registration No. 7313-7  
Olympic Solid Color Weather Screen  
EPA Registration No. 7313-8  
Your Submissions Dated September 6 and October 30, 1985

The labeling referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, is acceptable subject to the comments listed below. Five copies of the finished labeling must be submitted.


1. Change the Precautionary Statement "Harmful or fatal if swallowed" to "May be fatal if swallowed" wherever it appears on the label.
2. Assure that the complete product name is used throughout the labels for each subject product or appropriate language, i.e., This product, in order to eliminate confusion between similarly named products referred to on the label.

88898:Jackson:J-4:KENCO:3/27/86:4/5/86:eg:VO

CONCURRENCES							
SYMBOL ▶							
SURNAME ▶							
DATE ▶							

3. Add "Statement of Practical Treatment" heading on each label along with associated precautionary statements and first aid procedures. This information block should follow the ingredient statement (see enclosed Attachment A for format guidelines). Also, move content statement to follow immediately after ingredient statement.
4. Storage and Disposal statement on proposed labeling of 55-gallon sized containers for products 7313-6 and 7317-7 is acceptable.

Sincerely yours,



Henry M. Jacoby  
Product Manager (21)  
Fungicide-Herbicide Branch  
Registration Division (TS-767C)

Enclosure

OLYMPIC WOOD PRESERVATIVE - CLEAR - Center Panel

1 GALLON - 614000-1

\*\*\*\*\*

PENETRATING-WATER REPELLENT

OLYMPIC<sup>R</sup>

WOOD CLEAR

PRESERVATIVE

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

MAR 31 1986

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.

7313-6

REPELS WATER, PAINTABLE,

GUARDS AGAINST MILDEW, ROT AND DECAY

FOR ABOVE GROUND USE ON WOOD EXPOSED TO

MOISTURE AND WEATHER

MADE FROM NATURAL LINSEED OIL ①

KEEP OUT OF REACH OF CHILDREN

DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE ②

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

1 GALLON - 3.785 LITERS

ACTIVE INGREDIENTS

Bis (tributyltin)oxide .....0.50%

Folpet [N-[(trichloromethylthio-phthalimide] .....0.50%

INERT INGREDIENTS .....99.00%

TOTAL....100.00%

MEETS FED. SPEC TT-W-572B 3.7

EPA Reg. No. 7313-6 EPA Est. No. 7313-WA-1, 7313-1L, 7313-KY-1

\*\*\*\*\*

PL/32

8/2/85

OLYMPIC WOOD PRESERVATIVE - CLEAR - Right (of Center) Panel

1 GALLON - 614000-1

\*\*\*\*\*

#### DIRECTIONS FOR USE

Apply this product only as specified on this label. It is a violation of federal law to use this product in a manner inconsistent with its labeling.

OLYMPIC<sup>R</sup> WOOD PRESERVATIVE CLEAR is a penetrating linseed oil base, water repellent wood preservative. It gives wood protection from rot, decay, mildew and moisture damage. Recommended only for EXTERIOR<sup>(4)</sup> above ground use, it also adds these protective qualities when used under finish coats, resulting in longer life for the wood and the finish. It exceeds the Federal specification for water repellency, TT-W-572B paragraph 3.7.

WOOD PRESERVATIVE CLEAR is recommended on exterior bare wood surfaces which may be exposed to attack by wood rot, mildew or excess moisture. Use on structural lumber, beams, timbers, sills, millwork and roofs. To maintain wood preservation properties, reapplications are recommended every 2 to 4 years<sup>(5)</sup>.

When used prior to painting or staining<sup>(6)</sup>, allow to dry thoroughly (at least 24 to 48 hours) before applying OLYMPIC<sup>R</sup> Stain or Primecoat<sup>TM</sup>. Applications of oil base top coats may result in a higher gloss in some areas which will normally become more uniform with weathering.

OLYMPIC WOOD PRESERVATIVE - CLEAR - Right Panel, continued

1 GALLON - 614000-1

\*\*\*\*\*

Surfaces treated with WOOD PRESERVATIVE CLEAR will be protected from moisture damage, mildew and rot but will "weather" naturally. Depending on the exposure and the type of wood, this weathering will include a gradual graying. To protect and beautify with color, use one of OLYMPIC'S<sup>R</sup> Semi-Transparent or Solid Color Stains. For severe exposure to wood rot, "pressure treated wood" offers maximum protection. Wood used below ground requires OLYMPIC<sup>R</sup> Wood Preservative Green.

SURFACE PREPARATION: Proper surface preparation is essential for satisfactory results. <sup>⑦</sup> Surfaces must be clean, dry and free of mildew. Rinse thoroughly and allow to dry before application. Where mildew is evident, remove by scrubbing surface with this solution: 1 cup non-ammoniated <sup>⑧</sup> detergent and 1 quart household bleach dissolved into 3 quarts water (CAUTION: Household bleach is a potentially harmful material. Follow manufacturer's precautions. Use protective clothing, eye goggles and good rubber gloves.) Rinse thoroughly with clear water and depending on the severity, apply a solution of 50% household bleach and 50% water. <sup>⑨</sup> Rinse and allow this final treatment to dry before application.

OLYMPIC WOOD PRESERVATIVE - CLEAR - Right Panel, Continued

1 GALLON - 614000-1

\*\*\*\*\*

EXTRACTIVE BLEEDING: Some woods contain water-soluble colorings or extractives that tend to "bleed" to the surface. This bleeding may be unsightly but is not damaging to the finish. If it has occurred, allow the coating to dry, then wash with a mild detergent solution and rinse with clear water. For stubborn stains, a solution of 50% alcohol and 50% water may be necessary. (10)

APPLICATION: Mix thoroughly prior to use. May be applied with a natural bristle brush, spray or by dipping. (11) Use one coat prior to applying paint or stain. For all other applications 2 coats are recommended. Thoroughly treat ends and edges of boards. DO NOT THIN.

FOR ADDITIONAL INFORMATION - ASK YOUR DEALER

OLYMPIC HOMECARE PRODUCTS COMPANY (12)

2233 112th Ave. N.E., Bellevue, WA 98004

MADE IN U.S.A.

© 1985 The Olympic HomeCare Products Company

OLYMPIC WOOD PRESERVATIVE - CLEAR - Left Panel

1 GALLON - 614000-1

\*\*\*\*\*

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND

DOMESTIC ANIMALS

(13)

DANGER! CONTAINS MINERAL SPIRITS. KEEP OUT OF REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED. CAUSES EYE AND SKIN IRRITATION. COMBUSTIBLE. Keep away from heat and open flame. Avoid contact with skin, eyes and clothing. Avoid breathing of vapors or spray mist. (14)

Wear rubber gloves and protective clothing when applying or handling freshly treated lumber. USE ONLY IN WELL VENTILATED AREAS. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, nausea or dizziness, leave the area until symptoms cease. Do not drive, operate machinery or climb ladders while symptoms persist. Increase fresh air or wear properly fitted respiratory protection (NIOSH/MSHA TC-23C with an organic vapor cartridge) before resuming application. Do not drink alcohol while working with product. (15)

FIRST AID: IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. EYES: Immediately flush eyes with water and continue for at least 15 minutes. Call a physician. SKIN: Wash with soap and water. Remove and wash contaminated clothing before reuse. (16)

OLYMPIC WOOD PRESERVATIVE - CLEAR - Left Panel, Continued

1 GALLON - 614000-1

\*\*\*\*\*

NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. (1)

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water or wet land. (18) Do not contaminate water by cleaning of equipment or disposal of waste.

PHYSICAL OR CHEMICAL HAZARDS: To avoid spontaneous combustion, soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. COMBUSTIBLE. Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Do not reuse empty container. Wrap container and put in trash collection. Keep away from food and feed.

APPROXIMATE COVERAGE: Depending on texture, porosity and dryness of wood: 150 to 250 square feet per gallon.

DRYING: WOOD PRESERVATIVE CLEAR will require 24 to 48 hours to dry under ideal conditions.

CLEANUP: Clean brushes and other tools with mineral spirits.



OLYMPIC WOOD PRESERVATIVE - CLEAR - Left Panel, Continued

1 GALLON - 614000-1

\*\*\*\*\*

LIMITED WARRANTY: If, after proper surface preparation and proper application in accordance with label directions, this product is shown to be defective within one year of the date of purchase, Olympic, at its option, will either replace the product or refund its purchase price. Contact your Olympic dealer to make a claim under this warranty. You must supply proof of purchase.

Proper surface preparation is essential to the applicability of this warranty. Read and follow the label instructions.

Labor costs are not covered by this warranty. Cracking, peeling or blistering caused by inadequate ventilation or the breakdown of the underlying surface or previous paint film are also not covered by this warranty.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.



OLYMPIC WOOD PRESERVATIVE - CLEAR - Center Panel

55 GALLONS - 614003-1

\*\*\*\*\*

PENETRATING-WATER REPELLENT

OLYMPIC<sup>R</sup>

WOOD CLEAR

PRESERVATIVE

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

MAR 31 1986

Under the Federal Insecticide,  
Fungicide, and Rodenticide Act  
as amended, for the pesticide  
registered under EPA Reg. No.

7313-6

REPELS WATER, PAINTABLE,

GUARDS AGAINST MILDEW, ROT AND DECAY

FOR ABOVE GROUND USE ON WOOD EXPOSED TO

MOISTURE AND WEATHER

MADE FROM NATURAL LINSEED OIL

KEEP OUT OF REACH OF CHILDREN

DANGER! HARMFUL OR FATAL IF SWALLOWED. COMBUSTIBLE

SEE BACK PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

55 GALLONS - 208.175 LITERS

# ACTIVE INGREDIENTS

Bis (tributyltin)oxide .....0.50%

Folpet [N-[(trichloromethylthio-phthalimide] .....0.50%

INERT INGREDIENTS .....99.00%

TOTAL.....100.00%

MEETS FED. SPEC TT-W-572B 3.7

EPA Reg. No. 7313-6 EPA Est. No. 7313-WA-1, 7313-1L, 7313-KY-1

\*\*\*\*\*

PL/2-2

8/2/85

OLYMPIC WOOD PRESERVATIVE - CLEAR - Right (of Center) Panel

55 GALLONS - 614003-1

\*\*\*\*\*

#### DIRECTIONS FOR USE

Apply this product only as specified on this label. It is a violation of federal law to use this product in a manner inconsistent with its labeling. -

③  
OLYMPIC<sup>R</sup> WOOD PRESERVATIVE CLEAR is a penetrating linseed oil base, water repellent wood preservative. It gives wood protection from rot, decay, mildew and moisture damage. Recommended only for EXTERIOR above ground use, it also adds these protective qualities when used under finish coats, resulting in longer life for the wood and the finish. It exceeds the Federal specification for water repellency, TT-W-572B paragraph 3.7.

WOOD PRESERVATIVE CLEAR is recommended on exterior bare wood surfaces which may be exposed to attack by wood rot, mildew or excess moisture. Use on structural lumber, beams, timbers, sills, millwork and roofs. To maintain wood preservation properties, reapplications are recommended every 2 to 4 years. ⑤

⑥  
When used prior to painting or staining, allow to dry thoroughly (at least 24 to 48 hours) before applying OLYMPIC<sup>R</sup> Stain or Primecoat<sup>TM</sup>. Applications of oil base top coats may result in a higher gloss in some areas which will normally become more uniform with weathering.

OLYMPIC WOOD PRESERVATIVE - CLEAR - Right Panel, continued

55 GALLONS - 614003-1

\*\*\*\*\*

Surfaces treated with WOOD PRESERVATIVE CLEAR will be protected from moisture damage, mildew and rot but will "weather" naturally. Depending on the exposure and the type of wood, this weathering will include a gradual graying. To protect and beautify with color, use one of OLYMPIC'S<sup>R</sup> Semi-Transparent or Solid Color Stains. For severe exposure to wood rot, "pressure treated wood" offers maximum protection. Wood used below ground requires OLYMPIC<sup>R</sup> Wood Preservative Green.

( SURFACE PREPARATION: Proper surface preparation is essential for satisfactory results. <sup>(7)</sup> Surfaces must be clean, dry and free of mildew. Rinse thoroughly and allow to dry before application. Where mildew is evident, remove by scrubbing surface with this solution: 1 cup non-ammoniated detergent and 1 quart household bleach dissolved into 3 quarts water <sup>(8)</sup> (CAUTION: Household bleach is a potentially harmful material. Follow manufacturer's precautions. Use protective clothing, eye goggles and good rubber gloves.) Rinse thoroughly with clear water and depending on the severity, apply a solution of 50% household bleach and 50% water. <sup>(9)</sup> Rinse and allow this final treatment to dry before application.

OLYMPIC WOOD PRESERVATIVE - CLEAR - Right Panel, Continued

55 GALLONS - 614003-1

\*\*\*\*\*

EXTRACTIVE BLEEDING: Some woods contain water-soluble colorings or extractives that tend to "bleed" to the surface. This bleeding may be unsightly but is not damaging to the finish. If it has occurred, allow the coating to dry, then wash with a mild detergent solution and rinse with clear water. For stubborn stains, a solution of 50% alcohol and 50% water may be necessary. (10)

APPLICATION: Mix thoroughly prior to use. May be applied with a natural bristle brush, spray or by dipping. (11) Use one coat prior to applying paint or stain. For all other applications 2 coats are recommended. Thoroughly treat ends and edges of boards. DO NOT THIN.

FOR ADDITIONAL INFORMATION - ASK YOUR DEALER

OLYMPIC HOMECARE PRODUCTS COMPANY

2233 112th Ave. N.E., Bellevue, WA 98004

MADE IN U.S.A.

© 1985 The Olympic HomeCare Products Company

(12)

OLYMPIC WOOD PRESERVATIVE - CLEAR - Left Panel

55 GALLONS - 614003-1

\*\*\*\*\*

## PRECAUTIONARY STATEMENTS

### HAZARDS TO HUMANS AND

### DOMESTIC ANIMALS

(13)

DANGER! CONTAINS MINERAL SPIRITS. KEEP OUT OF REACH OF CHILDREN. HARMFUL OR FATAL IF SWALLOWED. CAUSES EYE AND SKIN IRRITATION. COMBUSTIBLE. Keep away from heat and open flame. Avoid contact with skin, eyes and clothing. Avoid breathing of vapors or spray mist. (14)

Wear rubber gloves and protective clothing when applying or handling freshly treated lumber. USE ONLY IN WELL VENTILATED AREAS. To avoid breathing vapors or spray mist, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, nausea or dizziness, leave the area until symptoms cease. Do not drive, operate machinery or climb ladders while symptoms persist. Increase fresh air or wear properly fitted respiratory protection (NIOSH/MSHA TC-23C with an organic vapor cartridge) before resuming application. Do not drink alcohol while working with product. (15)

FIRST AID: IF SWALLOWED, DO NOT INDUCE VOMITING. CALL A PHYSICIAN IMMEDIATELY. EYES: Immediately flush eyes with water and continue for at least 15 minutes. Call a physician. SKIN: Wash with soap and water. Remove and wash contaminated clothing before reuse. (16)

OLYMPIC WOOD PRESERVATIVE - CLEAR - Left Panel, Continued

55 GALLONS - 614003-1

\*\*\*\*\*

NOTICE: Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. (13)

ENVIRONMENTAL HAZARDS: This product is toxic to fish and wildlife. Do not apply directly to water or wet land. Do not contaminate water by cleaning of equipment or disposal of waste. (16)

PHYSICAL OR CHEMICAL HAZARDS: To avoid spontaneous combustion, soak oily cloths in water after use or place in a closed metal container away from buildings and other combustible materials. COMBUSTIBLE. Do not use or store near heat or open flame.

STORAGE AND DISPOSAL: Do not use or store inside the home. Triple rinse (or equivalent), offer for recycling or reconditioning, or puncture and dispose of in a sanitary land fill, or by other approved state and local procedures.

APPROXIMATE COVERAGE: Depending on texture, porosity and dryness of wood: 8250 to 13750 square feet per drum.

DRYING: WOOD PRESERVATIVE CLEAR will require 24 to 48 hours to dry under ideal conditions.

CLEANUP: Clean brushes and other tools with mineral spirits.

OLYMPIC WOOD PRESERVATIVE - CLEAR - Left Panel, Continued

55 GALLONS - 614003-1

\*\*\*\*\*

LIMITED WARRANTY: If, after proper surface preparation and proper application in accordance with label directions, this product is shown to be defective within one year of the date of purchase, Olympic, at its option, will either replace the product or refund its purchase price. Contact your Olympic dealer to make a claim under this warranty. You must supply proof of purchase.

Proper surface preparation is essential to the applicability of this warranty. Read and follow the label instructions.

Labor costs are not covered by this warranty. Cracking, peeling or blistering caused by inadequate ventilation or the breakdown of the underlying surface or previous paint film are also not covered by this warranty.

This warranty gives you specific legal rights and you may also have other rights which vary from state to state.

(19)